




55EF5C open-frame OLED signage



Because the 55EF5C is an open-frame curved signage, it can be used in a variety of sizes and shapes in many different spaces due to its extendable nature and curved format. Also, by adding impact to the space, it will become a perfect landmark. In addition, because it is an IPS panel, even if it takes up a lot of space like a video wall, visibility and image quality are excellent regardless of the angles.

Why OLED Technology?



Limitless contrast and deepest black Self-lighting pixels switch off completely to

reproduce black. No light bleeding. Absolute black offers infinite contrast.





LCD



Perfect Color

Accurate & stable color reproduction Self-lighting pixels bring colors to life

with superb accuracy.





Perfect Viewing Screen

Wide viewing angle

LG OLED Signage delivers awe-inspiring picture quality across the entire screen, even from wide viewing angles.





LG OLED Signage



Crisp, Clear Motion

Faster response time

LG OLED Signage provides a 5,000-times faster motion-picture response time, for perfectly clear images without blurring.







Perfect Design

Slim and light

With just two layers, the LG OLED Signage display is unbelievably lightweight and thin.













Learn more www.lg.com/b2b or www.lgecommercial.com You Tube youtube.com/c/LGECommercialDisplay

 $\ensuremath{\mathsf{LG}}$ may make changes to specifications and product descriptions without notice. $Copyright © 2016 LG \ Electronics \ Inc. \ All \ rights \ reserved. \ "LG \ Life's \ Good" \ is \ a \ registered \ trademark \ of \ LG \ Corp.$ The names of products and brands mentioned here may be the trademarks of their respective owners.



Artistic Space Beyond Display

55EF5C open-frame OLED signage



Screen Size

- Brightness: 400 cd/m² (APL* 25%) * APL: Average Picture Level
- Bezel: 7.2 mm (U/B/R/L, Off-bezel)
- Available in 2,000R for landscape, 1,500R for portrait (Concave & Convex)
- HDMI, DP, RJ45, IR, RS232C, USB, Audio out, Internal memory (64 GB), SuperSign OLED/C

Key Features

Artistic Display that Becomes a Landmark

Its curved display means that its space efficiency is outstanding, and it can be positioned in a variety of ways because it is extendable and curved, so by simply installing, it can gather much attention.





Space-fitting Design Option

Extendable and curved



In Landscape

Max Curvature in Landscape: ~2,000R

- Radius: 2,000 mm
- Circumference: 12,560 mm



Max Curvature in Portrait: ~1,500R

- Radius: 1,500 mm
- Circumference: 9,420 mm












- 3 ea (55EF5C-M3) • Accessory 1: A1****EF5C • Accessory 2: A2****EF5C

Field-assembly Process



curvature jig

Components & Model Codes

- 2 ea (55EF5C-M2/55EF5C-M3)

OLED Module & Signage Box & T-Con Box & Cables

bar & center bar

Specifications

		55EF5C
	Screen Size	55"
PANEL	Panel Technology	OLED
	Aspect Ratio	16:9
	Native Resolution	1,920 x 1,080 (FHD)
	Brightness	100/400 cd/m² (APL 100%/25%) *Average Picture Level
	Viewing Angle (H x V)	178 x 178
	Response Time	1 ms (G to G), 8 ms (MPRT)
	Surface Treatment	Hard coating (2H), Anti-reflection treatment of the front polarizer (Reflectance Typ. 1.0%)
	Operation Hours	18 hrs/7 days (Moving video only)
	Orientation	Portrait & Landscape
CONNECTIVITY	Input	HDMI, DP
	Output	DP, Audio
	External Control	RS232C in/out, RJ45 in, IR receiver, LAN out, IR out, USB
	Bezel Color	Black
	Bezel Width	7.2, 7.2, 7.2, 7.2 mm (U, B, L, R *Off-bezel)
PHYSICAL SPECIFICATION	Dimension (W x H x D) Weight Carton Dimensions (W x H x D)	Head 1. Landscape (W x H) - 1,950R, In-curve: TBD - 2,000R, Concave: 1,213.7 x 704.1 mm - 2,000R, Convex: 1,214.2 x 704.1 mm - 3,000R, In-curve: TBD - 4,000R, Out-curve: TBD - 4,500R, Out-curve: TBD - 5,000R, In-curve: 1,227.5 x 704.1 mm - 5,000R, Out-curve: TBD - 8,000R, In-curve: 1,228.8 x 704.1 mm - 5,000R, In-curve: 1,228.8 x 704.1 mm 2. Portrait (W x H) - 1,500R, Concave: 1,229 x 700.7 mm - 1,500R, Concave: 1,229 x 701.2 mm 3. Landscape/Portrait (D) - not affected by orientation/curvatur - Module Only: 21.4 mm (Incl. case top) - Module + Center Bar: 30 mm - Module + Center Bar: 30 mm - Module + Center Bar: T-Con Box: 41.2 mm
	Packed Weight	70.2 kg (Panel 3 ea, T-CON Box 3 ea, Signage Box 3 ae)
SPECIAL FEATURES	5	Temperature Sensor, Tile mode, Cooling FAN, DPM Select, Energy Saving, Motion Eyecare, File Play with USB, PIP/PBP, Internal Memory (64 GB), USB Cloning, DP Daisy Chain, Wake on LAN, PM Mode, Contents Scheduling, Local Time Auto Setting, Failover
ENVIRONMENT	Operation Temperature	0°C to 40°C
CONDITIONS	Operation Humidity	10% to 80%
DOLLIED	Power Supply	100-240 V~, 50/60 Hz
POWER	Power Type	Built-in Power
POWER CONSUMPTION	Тур.	TBD
	DPM	TBD
	Power Off	TBD
STANDARD (CERTIFICATION)	Safety	UL/cUL/CB/TUV/KC
	EMC	FCC Class "A"/CE/KCC
	ErP/Energy Star	Yes/NA
MEDIA PLAYER	OPS-Type Compatible	Yes
COMPATIBILITY	External Media Player Attachable	Yes
SOFTWARE COMPATIBILITY	SuperSign OLED	Yes
	SuperSign C	Yes
ACCESSORIES	Basic	Remote Controller (including battery 2 ea), Power Cord, QSG, Mini HDMI Cable (3M x 2 ea, for connection between head and signage box), Power Harness Cable (3M x 2 ea, for connection between head and signage box), Regulation Book, Phone to RS232C Gender, Jack Cover, Signage Box Mounting Bracket
	Optional	OPS Kit (KT-OPSA), Fixed Ceiling Mount Kit (ACC-CF-EH5C), Rotational Ceiling Mount Kit (ACC-CR-EH5C), Wall Mount Kit (ACC-W-EH5C), Stand Kit 1 (ACC-S-EH5C), Stand Kit 2 (ACC-S1-EH5C), Signage Box Cover (ACC-C-EH5C)