



HIGH STATIC BLOWERS

Versatile Powerful Inflatable Blowers

XPOWER offers the most complete high static inflatable blower line - starting at 1/8 HP all the way up to 3 HP - to fill any inflatable, whether it's a small holiday decoration or a full sized exhibition dome.

- Injection molded using durable high quality polypropylene
- Energy-efficient power usage
- UL/CUL safety certified for indoor and outdoor use
- Lightweight and compact for easy storage



BR-2C01A



BR-201A



BR-232A



BR-252A



BR-282A



BR-292A



SPECIFICATIONS

Model No.	BR-2C01A	BR-201A	BR-232A	BR-252A	BR-282A	BR-292A
Volts/Hertz	120V/60Hz	120V/60Hz	120V/60Hz	120V/60Hz	120V/60Hz	120V/60Hz
Motor	1/8HP	1/4HP	1/2HP	1HP	2HP	3HP
Power	0.8A	2.2A	5.5A	9.8A	12A	18 A
Rated Airflow	120CFM	250CFM	600CFM	1000CFM	1500CFM	1700CFM
Speed	SINGLE	SINGLE	SINGLE	SINGLE	SINGLE	SINGLE
Cord Length	6'	6'	6'	6'	12'	12'
Unit Weight	3.8lbs	8lbs	12lbs	16.2lbs	22lbs	30.4lbs
Unit Dimensions	8"x5.7"x8.5"	12.6"x8.5"x12.6"	15"x10.5"x15"	15.5"x11.2"x16.7"	18.5"x10.6"x19.9"	18.5"X10.6"X19.9"
Box Weight	4.5lbs	9.6lbs	14.2lbs	18.6lbs	25.8lbs	33.3lbs
Box Dimensions	8.7"x6.3"x9.4"	13.6"x13.6"x10.4"	15.8"x15.8"10.8"	17.1"x17.1"x12.4"	20"x18.5"x11.2"	20"X18.5"X11.2"
Safety Certification	UL/CUL	UL/CUL	UL/CUL	UL/CUL	UL/CUL	

Direct Import

Model No.	BR-2C01E	BR-201E	BR-222E	BR-232E	BR-242E	BR-282E
Volts/Hertz	240V/50Hz	240V/50Hz	240V/50Hz	240V/50Hz	240V/50Hz	240V/50Hz
Motor	70 W	280 W	480 W	680 W	950 W	1500 W
Power	0.3 A	1.2 A	2.1 A	2.9 A	4.1 A	6.5 A
Rated Airflow	120CFM	200 CFM	500 CFM	800 CFM	1000CFM	1300 CFM
Speed	SINGLE	SINGLE	SINGLE	SINGLE	SINGLE	SINGLE
Cord Length	1.8m	1.8m	1.8m	1.8m	1.8m	3.6m
Unit Weight	1.9kg	3.8kg	5.3kg	6.8kg	8.2kg	12kg
Unit Dimensions (CM)	20.5x14.5x21.5	32x21.5x32	38x26.5x38.5	39.5x28.5x42.5	45.6x29x46	47x27x50.5
Box Weight	2.1kg	4.6kg	6.2kg	7.8kg	10.2kg	13.6kg
Box Dimensions (CM)	22X16X24	34x33.5x26	40x40x27.5	43x43x30.5	49.7x49.7x32	52x47x29
Safety Certification	-	-	CE,GS,SAA	CE,GS,SAA	CE	CE

