

















Axis fixed dome network cameras








	Indoor	Indoor	Indoor	Indoor	Indoor	Indoor	Indoor	Indoor	Indoor / Outdoor
	AXIS 209FD 	AXIS 209FD-R 	AXIS 209MFD 	AXIS 209MFD-R 	AXIS M3011 	AXIS 216FD AXIS 216FD-V 	AXIS 216MFD AXIS 216MFD-V 	AXIS P3301 AXIS P3301-V 	AXIS 225FD AXIS 225FD 22 mm 
Image sensor	1/4" progressive scan CMOS	1/4" progressive scan CMOS	1/3" progressive scan CMOS 1.3 megapixel	1/3" progressive scan CMOS 1.3 megapixel	1/4" progressive scan CMOS	1/4" progressive scan CMOS	1/3" progressive scan CMOS 1.3 megapixel	1/4" progressive scan CMOS	1/4" progressive scan CCD
Lens	3.0 mm/F2.0 fixed iris	3.0 mm/F2.0 fixed iris	3.6 mm/F1.8 fixed iris	3.6 mm/F1.8 fixed iris	3.0 mm/F2.0 fixed iris	Varifocal 2.8 - 10 mm/F1.3 DC-iris	Varifocal 2.8 - 10 mm/F1.3 DC-iris	Varifocal 2.8 - 10 mm/F1.3 DC-iris	Varifocal, DC-iris Standard: 2.8 - 5.8 mm/F1.4 22 mm: 9 - 22 mm/F1.5
Day and night									Automatic
Min illumination/ light sensitivity (lux)	1.5 - 10,000	1.5 - 10,000	3 - 10,000	3 - 10,000	1 - 10,000	1	2	1	Standard: 1 (color), 0.2 (B/W) 22 mm: 1.5 (color), 0.3 (B/W)
Compression	MPEG-4, Motion JPEG	MPEG-4, Motion JPEG	MPEG-4, Motion JPEG	MPEG-4, Motion JPEG	H.264, Motion JPEG MPEG-4	MPEG-4, Motion JPEG	MPEG-4, Motion JPEG	H.264, Motion JPEG	MPEG-4 Motion JPEG
Max video resolution (pixels)	640 x 480	640 x 480	1280 x 1024	1280 x 1024	640 x 480	640 x 480	1280 x 1024	640 x 480	640 x 480
Frames per second	30 (640x480)	30 (640x480)	12 (1280x1024)	12 (1280x1024)	30 (640x480)	30 (640x480)	12 (1280x1024) 30 (800x600)	30 (640 x 480)	30 (640x480)
Audio support						Two-way, Half Duplex	Two-way, Half Duplex	Two-way, Half Duplex	
Alarm in-/outputs						1/1	1/1	1/1	2/1
Intelligent video	Motion detection	Motion detection Active tampering alarm	Motion detection	Motion detection Active tampering alarm	Motion detection Active tampering alarm	Motion detection Audio detection Active tampering alarm	Motion detection Audio detection Active tampering alarm	Motion detection Audio detection Active tampering alarm	Motion detection Active tampering alarm
Security	Multi-level passwords IP filtering HTTPS encryption	Multi-level passwords IP filtering HTTPS encryption	Multi-level passwords IP filtering HTTPS encryption	Multi-level passwords IP filtering HTTPS encryption	Multi-level passwords IP filtering HTTPS encryption	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X
Network	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS
Power over Ethernet (IEEE 802.3af)	Class 1	Class 1	Class 1	Class 1	Class 1	Class 1	Class 1	Class 2	Class 2 (without heater)
Serial connectors									RS-485
Outdoor use									●
Other	Tamper-resistant	IP66-rated, rugged, for mobile video surveillance	Tamper-resistant	IP66-rated, rugged, for mobile video surveillance	Recessed mounting	AXIS 216FD: Tamper-resistant AXIS 216FD-V: Vandal-resistant	AXIS 216MFD: Tamper-resistant AXIS 216MFD-V: Vandal-resistant	WDR, Tamper-resistant	Vandal-resistant, IP66-rated, heater and fan
Axis part #	0281-004	0275-004	0283-004	0286-004	0284-004	AXIS 216FD: 0240-004 AXIS 216FD-V: 0268-004	AXIS 216MFD: 0278-004 AXIS 216MFD-V: 0279-004	AXIS P3301: 0290-004 AXIS P3301-V: 0292-004	AXIS 225FD: 0243-004 AXIS 225FD 22mm: 0243-064

Axis fixed network cameras – Indoor

	Indoor	Indoor	Indoor	Indoor	Indoor	Indoor	Indoor
	AXIS 206 	AXIS 207/ AXIS 207W 	AXIS 207MW 	AXIS M1011/ AXIS M1011-W 	AXIS M1031-W 	AXIS 210/ AXIS 210A 	AXIS P1311 
Image sensor	1/4" progressive scan CMOS	1/4" progressive scan CMOS	1/3" progressive scan CMOS 1.3 megapixel	1/4" progressive scan CMOS	1/4" progressive scan CMOS	1/4" progressive scan CCD	1/4" progressive scan CMOS
Lens	4.0 mm/F2.0 fixed iris	4.0 mm/F2.0 fixed iris	3.6 mm/F1.8 fixed iris	4.4 mm/F2.0 fixed iris	4.4 mm/F2.0 fixed iris	4.0 mm/F1.2 fixed iris CS mount	4.0 mm/F1.2 fixed iris, CS mount
Day and night							
Min illumination/light sensitivity (lux)	4 - 10,000	1 - 10,000	2 - 10,000	1 - 10,000	1 - 10,000 0 with LED on	1 - 10,000	0.6 - 30,000
Video compression	Motion JPEG	MPEG-4, Motion JPEG	MPEG-4, Motion JPEG	H.264, Motion JPEG MPEG-4	H.264, Motion JPEG MPEG-4	MPEG-4, Motion JPEG	H.264, Motion JPEG, MPEG-4
Max video resolution (pixels)	640 x 480	640 x 480	1280 x 1024	640 x 480	640 x 480	640 x 480	640 x 480
Frames per second	30 (640x480)	30 (640x480)	12 (1280 x 1024)	30 (640x480)	30 (640x480)	30 (640x480)	30 (640 x 480)
Audio support		One-way	One-way		Two-way, built-in mic and	210A: Two-way,	Two-way,
Alarm in-/outputs		1/1	1/1			1/1	1/1
Intelligent video		Motion detection Audio detection	Motion detection Audio detection	Motion detection Tampering alarm	Motion detection Audio detection Tampering alarm	Motion detection	Motion detection Audio detection Tampering alarm
Security	Multi-level passwords	Multi-level passwords IP filtering ⁴ HTTPS encryption ⁴ IEEE 802.1X ⁴	Multi-level passwords IP filtering HTTPS encryption	Multi-level passwords IP filtering HTTPS encryption	Multi-level passwords IP filtering HTTPS encryption	Multi-level passwords IP filtering HTTPS encryption ⁵ IEEE 802.1X ⁵	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X
Network	IPv4	IPv4	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS
Power over Ethernet (IEEE 802.3af)	PoE splitter available #5008-001	PoE splitter available #5008-001	PoE splitter available #5008-001	PoE splitter available #5008-001	PoE splitter available #5008-001	AXIS 210: PoE splitter AXIS 210A: Class 2	Class 1
Serial connectors							
Outdoor use							
Other			Wireless 802.11g/b	AXIS M1011-W: Wireless IEEE 802.11b/g	Built-in PIR sensor and illumination LED, Wireless 802.11g/b	Changeable lens	SD/SDHC memory card slot
Axis part #	0199-004	AXIS 207: 0235-004 AXIS 207W: 0241-004	0264-004	AXIS M1011: 0302-004 AXIS M1011-W: 0301-004	0300-004	AXIS 210: 0197-004 AXIS 210A: 0233-004	0293-004








1) Camera can be used with C/CS lens 2) Instant one-click pan/tilt/zoom with no moving parts 3) Requires the AXIS 213 Connection Module Axis part #22581 4) AXIS 207W only 5) AXIS 210A only

Axis fixed network cameras – Indoor / Outdoor

	Indoor / Outdoor	Indoor / Outdoor	Indoor / Outdoor	Indoor / Outdoor	Indoor / Outdoor	Indoor / Outdoor	Indoor / Outdoor
	AXIS 211¹ 	AXIS 211A¹ 	AXIS 211W¹ 	AXIS 211M¹ 	AXIS 221¹ 	AXIS 223M¹ 	AXIS Q1755¹ 
Image sensor	1/4" progressive scan CCD	1/4" progressive scan CCD	1/4" progressive scan CMOS	1/3" progressive scan CMOS 1.3 megapixel	1/3" progressive scan CCD	1/2.7" progressive scan CCD 2 megapixel	1/3" progressive scan CMOS 2 megapixel
Lens	Varifocal 3.0 - 8.0 mm/F1.0 DC-iris, CS mount	Varifocal 3.0 - 8.0 mm/F1.0 DC-iris, CS mount	Varifocal 3.0 - 8.0 mm/F1.0 DC-iris, CS mount	Varifocal 3.0 - 8.0 mm/F1.0 DC-iris, CS mount	Varifocal 3.0 - 8.0 mm/F1.0 DC-iris, CS mount	Varifocal 4.0 - 8.0 mm/F1.4 DC-iris, C mount ¹	5.1 - 51 mm/F1.8 auto iris and autofocus 10x optical zoom 12x digital zoom
Day and night					Automatic	Automatic	Automatic
Min illumination/light sensitivity (lux)	0.75	0.75	0.75	1	0.65 (color) 0.08 (B/W)	1.5 (color) 0.2 (B/W)	2 (color) 0.2 (B/W)
Video compression	MPEG-4, Motion JPEG	MPEG-4, Motion JPEG	MPEG-4, Motion JPEG	MPEG-4, Motion JPEG	MPEG-4, Motion JPEG	MPEG-4, Motion JPEG	H.264, Motion JPEG
Max video resolution (pixels)	640 x 480	640 x 480	640 x 480	1280 x 1024	640 x 480	1600x900 1600x1200	HDTV 1080i 1920x1080 HDTV 720p, 1280x720
Frames per second	30 (640x480)	30 (640x480)	30 (640x480)	12 (1280x1024) 30 (800x600)	45 (640x480) 60 (480x360)	12 (1600x900) 9 (1600x1200)	30 (all resolutions)
Audio support		Two-way, Full Duplex	Two-way, Full Duplex	Two-way, Full Duplex		Two-way, Half Duplex	Two-way, built-in mic, Half Duplex
Alarm in-/outputs	1/1	1/1	1/1	1/1	2/1	2/1	2 configurable inputs/outputs
Intelligent video	Motion detection	Motion detection Audio detection	Motion detection Audio detection	Motion detection Audio detection	Motion detection Active tampering alarm	Motion detection Audio detection Active tampering alarm	Motion detection Audio detection Tampering alarm Gatekeeper
Security	Multi-level passwords IP filtering	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X
Network	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS
Power over Ethernet (IEEE 802.3af)	Class 2	Class 2	Class 2	Class 2	Class 2	Class 2	Class 3
Serial connectors					RS-232, RS-485	RS-232, RS-485	RS-422, RS-485
Outdoor use	Outdoor use requires weather-proof housing	Outdoor use requires weather-proof housing	Outdoor use requires weather-proof housing	Outdoor use requires weather-proof housing	Outdoor use requires weather-proof housing	Outdoor use requires weather-proof housing	Outdoor use requires weather-proof housing
Other	Changeable lens	Changeable lens	Wireless 802.11g/b, changeable lens	Changeable lens	Changeable lens	Changeable lens	SD/SDHC memory card slot and analog video out
Axis part #	0198-004	0223-004	0270-004	0269-004	0221-004	0247-004	0304-001

1) Camera can be used with C/CS lens 2) Instant one-click pan/tilt/zoom with no moving parts 3) Requires the AXIS 213 Connection Module Axis part #22581 4) AXIS 207W only 5) AXIS 210A only























Axis pan/tilt/zoom network cameras

	Indoor	Indoor	Indoor / Outdoor	Indoor / Outdoor	Indoor / Outdoor	Indoor / Outdoor	Indoor / Outdoor	Indoor / Outdoor	Indoor / Outdoor
	AXIS 212 PTZ²	AXIS 212 PTZ-V²	AXIS 213 PTZ¹	AXIS 214 PTZ¹	AXIS 215 PTZ¹	AXIS 215 PTZ-E	AXIS 231D+¹	AXIS 232D+¹	AXIS 233D
									
	1/2" progressive scan CMOS 3 megapixel	1/2" progressive scan CMOS 3 megapixel	1/4" CCD	1/4" ExView HAD CCD	1/4" CCD	1/4" CCD	1/4" ExView HAD CCD	1/4" ExView HAD CCD	1/4" ExView progressive scan HAD CCD
Lens	2.7 mm/F1.8 fixed iris 3x instant zoom	2.7 mm/F1.8 fixed iris 3x instant zoom	3.5 - 91 mm auto iris and auto focus 26x optical zoom 12x digital zoom	4.1 - 73.8 mm auto iris and auto focus 18x optical zoom 12x digital zoom	3.8 - 46 mm auto iris and auto focus 12x optical zoom 4x digital zoom	3.8 - 46 mm auto iris and auto focus 12x optical zoom 4x digital zoom	4.1 - 73.8 mm auto iris and auto focus 18x optical zoom 12x digital zoom	4.1 - 73.8 mm auto iris and auto focus 18x optical zoom 12x digital zoom	3.4 - 119 mm auto iris and auto focus 35x optical zoom 12x digital zoom
Day and night			Configurable Built-in IR lamp	Automatic	Automatic	Automatic		Automatic	Automatic
Min illumination/light sensitivity (lux)	10 lux wide mode 20 lux tele mode	10 lux wide mode 20 lux tele mode	1 (color) 0.1 (B/W)	0.3 (color) 0.005 (B/W)	1 (color) 0.3 (B/W)	1 (color) 0.3 (B/W)	0.3 (color)	0.3 (color) 0.005 (B/W)	0.5 (color) 0.008 (B/W)
Video compression	MPEG-4, Motion JPEG	MPEG-4, Motion JPEG	MPEG-4, Motion JPEG	MPEG-4, Motion JPEG	MPEG-4, Motion JPEG	MPEG-4, Motion JPEG	MPEG-4, Motion JPEG	MPEG-4, Motion JPEG	MPEG-4, Motion JPEG
Max video resolution (pixels)	640 x 480	640 x 480	4CIF: 704x480	4CIF: 704x480	4CIF: 704x480	4CIF: 704x480	4CIF: 704x480	4CIF: 704x480	4CIF: 704x480
Frames per second	17 (640 x 480) in overview 30 (640 x 480) at max zoom	17 (640 x 480) in overview 30 (640 x 480) at max zoom	30 (4CIF)	30 (4CIF)	30 (4CIF)	30 (4CIF)	30 (4CIF)	30 (4CIF)	30 (4CIF)
Pan/Tilt/Zoom	20 presets 140° pan, 105° tilt Guard tour	20 presets 140° pan, 105° tilt Guard tour	20 presets 340° pan, 100° tilt	20 presets 340° pan, 120° tilt	20 presets 360° pan via auto-flip 180° tilt	20 presets 360° pan via auto-flip 180° tilt	50 presets 360° endless pan, 90° tilt, Guard tour	50 presets 360° endless pan, 90° tilt, Guard tour	100 presets 360° endless pan, 180° tilt, Guard tour
Audio support	Two-way, Half Duplex	Two-way, Half Duplex	Two-way with AXIS 213CM ³	Two-way, Full Duplex	Two-way, Full Duplex				Two-way, Full Duplex
Alarm in-/outputs	1/1	1/1	2/3 with AXIS 213CM ³	1/1	1/1		4/4	4/4	4/4
Intelligent video	Motion detection Audio detection	Motion detection Audio detection	Motion detection	Motion detection Audio detection	Motion detection Audio detection	Motion detection	Motion detection	Motion detection	Motion detection Audio detection
Security	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering	Multi-level passwords IP filtering HTTPS encryption	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X
Network	IPv4/v6, QoS	IPv4/v6, QoS	IPv4	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS
Power over Ethernet (IEEE 802.3af)	Class 1	Class 1	T8121 Midspan T8126 Splitter (12V)	T8121 Midspan T8126 Splitter (12V)	T8121 Midspan T8126 Splitter (12V)		T8121 Midspan T8128 Splitter (24V)	T8121 Midspan T8128 Splitter (24V)	T8121 Midspan T8128 Splitter (24V)
Serial connectors			RS-232 with AXIS 213CM ³						
Outdoor use			Outdoor use requires weather-proof housing	Outdoor use requires weather-proof housing	Outdoor use requires weather-proof housing	Enclosure included -4 °F to 104 °F	Outdoor use requires weather-proof housing	Outdoor use requires weather-proof housing	Outdoor use requires weather-proof housing
Other	Continuous motion 24/7	Continuous motion 24/7 Vandal-resistant	Built-in IR light up to 3 m, Analog video with AXIS 213CM ³		Auto-flip and E-flip	Auto-flip and E-flip	Continuous motion 24/7, WDR	Continuous motion 24/7, WDR	Continuous motion 24/7, E-flip, Image stabilizer, WDR, Auto-tracking
Axis part #	0257-004	0280-004	0220-004	0246-004	0274-004	0306-001	0251-001	0253-001	0266-004











1) Camera can be used with C/CS lens 2) Instant one-click pan/tilt/zoom with no moving parts 3) Requires the AXIS 213 Connection Module Axis part #22581 4) AXIS 207W only 5) AXIS 210A only

Axis network camera housings

Axis network camera housings

Part #	Product	Compatible with:
 5015-101	AXIS T92A10 Housing - Aluminum construction - Indoor/outdoor	AXIS 210, AXIS 210A, AXIS 211, AXIS 211A, AXIS 211M, AXIS 221, AXIS 223M, AXIS Q1755
 5010-001	AXIS T95A00 Dome Housing ¹ - Aluminum construction - Indoor/outdoor	AXIS 213 PTZ, AXIS 214 PTZ, AXIS 215 PTZ, AXIS 231D+, AXIS 232D+, AXIS 233D
 5010-611	AXIS T95A61 Extension Bracket	Wall Bracket for AXIS T95A00 and T95A10 Dome Housing.
 5010-641	AXIS T95A64 Corner Bracket	Requires AXIS T95A61 Wall Bracket.
 5010-671	AXIS T95A67 Pole Bracket	Requires AXIS T95A61 Wall Bracket.
 5010-101	AXIS T95A10 Dome Housing ² - Aluminum construction - Indoor/outdoor	AXIS 213 PTZ, AXIS 214 PTZ, AXIS 215 PTZ, AXIS 231D+, AXIS 232D+, AXIS 233D
 24886	AXIS Indoor Fixed Wall Housing ³	AXIS 210, AXIS 210A, AXIS 211, AXIS 211A, AXIS 221, AXIS 223M
 24887	AXIS Indoor Fixed Corner Housing ³	
 24888	AXIS Indoor Fixed Ceiling Housing ³	
 21899	AXIS Indoor Fixed Housing - Aluminum construction - Indoor	AXIS 210, AXIS 210A, AXIS 211, AXIS 211A, AXIS 221, AXIS 223M
 22870	AXIS Indoor Fixed Camera Dome - Steel construction - Indoor	AXIS 210, AXIS 210A, AXIS 211, AXIS 211A, AXIS 221, AXIS 223M
 21898	AXIS Indoor Recessed Enclosure - Steel construction - Indoor	AXIS 213 PTZ, AXIS 214 PTZ, AXIS 215 PTZ, AXIS 231D+,AXIS 232D+, AXIS 233D
 26549	AXIS 206/207 Ceiling-Mount Housing - Steel construction - Indoor	AXIS 206, AXIS 207 (not wireless)
 26550	AXIS 206/207 Vandal-Resistant Housing - Aluminum construction - Indoor	AXIS 206, AXIS 207 (not wireless)
 24889	AXIS Outdoor Fixed Housing - Aluminum construction - Outdoor	AXIS 211, AXIS 211A, AXIS 221, AXIS 223M
 29892	AXIS Fixed Wireless Housing - Aluminum construction - Outdoor	AXIS 211W
 25735	AXIS Pendant Dome Indoor - Plastic construction - Indoor	AXIS 213 PTZ, AXIS 214 PTZ, AXIS 215 PTZ, AXIS 231D+,AXIS 232D+, AXIS 233D
 25733	AXIS Pendant Dome Outdoor - Plastic construction - Indoor/outdoor	AXIS 213 PTZ, AXIS 214 PTZ, AXIS 215 PTZ, AXIS 231D+, AXIS 232D+, AXIS 233D
 25734	AXIS Pendant Vandal Dome - Aluminum construction - Indoor/outdoor	AXIS 213 PTZ, AXIS 214 PTZ, AXIS 215 PTZ, AXIS 231D+, AXIS 232D+
 25736	Gooseneck Wall Mount	Gooseneck wall mount for the AXIS Pendant Dome
 25738	Parapet Mount	Parapet mount for the AXIS Pendant Dome
 22059	Corner Mount Adapter	Corner mount adaptor for the AXIS Pendant Indoor, Outdoor, and Vandal Dome Housings
 21896	Pole Mount Adapter	Pole mount adaptor for the AXIS Pendant Indoor, Outdoor, and Vandal Dome Housings.
 26349	Ceiling Mount 12" Extension	Secures AXIS Pendant Dome housings to hard ceilings
 26350	Ceiling Mount 24" Extension	Secures AXIS Pendant Dome housings to hard ceilings
 5502-001	AXIS 225FD Pendant Kit	Connects AXIS 225FD to 25736 and 25738




Axis video encoders

	1-channel video encoders						4- and 6-channel video encoders			
	AXIS 241S 	AXIS M7001 ⁵ 	AXIS 243SA 	AXIS 247S 	AXIS Q7401 ¹ 	AXIS 240Q 	AXIS 241Q 	AXIS 241QA 	AXIS 243Q 	AXIS Q7406 
Video compression	MPEG-4, Motion JPEG	H.264, Motion JPEG	MPEG-4, Motion JPEG	MPEG-4, Motion JPEG	H.264, Motion JPEG	Motion JPEG	MPEG-4, Motion JPEG	MPEG-4, Motion JPEG	MPEG-4, Motion JPEG	H.264, Motion JPEG
Max video resolution (pixels)	4CIF: 704x480	D1: 720x480	4CIF: 704x480	4CIF: 704x480	D1: 720x480	4CIF: 704x480	4CIF: 704x480	4CIF: 704x480	4CIF: 704x480	D1: 720x480
Frames per second H.264 in maximum resolution		30 (D1)			30 (D1)					30 (D1) per channel
Frames per second MPEG-4 in maximum resolution	21 (4CIF), 30 (2CIF)		30 (4CIF)	27 (4CIF), 30 (VGA)			21 (4CIF) using 1 channel, 20 (CIF) per channel using 4 channels	21 (4CIF) using 1 channel, 20 (CIF) per channel using 4 channels	30 (4CIF) per channel	
Frames per second Motion JPEG in maximum resolution	30 (4CIF)	30 (D1)	30 (4CIF)	30 (4CIF)	30 (D1)	6 (4CIF) per channel	30 (4CIF) using 1 channel, 30 (CIF) per channel using 4 channels	30 (4CIF) using 1 channel, 30 (CIF) per channel using 4 channels	30 (4CIF) per channel	30 (4CIF) per channel
Video source	1 BNC composite or Y/C video input ²	1 BNC composite input	1 BNC composite or Y/C video input ²	1 BNC composite input	1 BNC composite input	4 BNC composite inputs	4 BNC composite inputs	4 BNC composite inputs	4 BNC composite inputs	6 BNC composite inputs
Audio support			Two-way, Full Duplex	One-way	Two-way, Half Duplex			Two-way, Full Duplex		
Alarm in-/outputs	4/4		4/4	1/1	4 configurable inputs/outputs	4/4	4/4	4/4	4/4	2 configurable inputs/outputs per channel w/Q7900
Intelligent video	Motion detection	Motion detection	Motion detection, Audio detection, Active tampering alarm	Motion detection, Audio detection	Motion detection, Audio detection, Active tampering alarm	Motion detection	Motion detection	Motion detection, Audio detection, Active tampering alarm	Motion detection, Active tampering alarm	Motion detection, Active tampering alarm
Pan/tilt/zoom support	● ³	● ³	● ³		● ³	● ³	● ³	● ³	● ³	● ³
Security	Multi-level passwords, IP filtering, HTTPS encryption, IEEE 802.1X	Multi-level passwords, IP filtering, HTTPS encryption	Multi-level passwords, IP filtering, HTTPS encryption, IEEE 802.1X	Multi-level passwords, IP filtering, HTTPS encryption, IEEE 802.1X	Multi-level passwords, IP filtering, HTTPS encryption, IEEE 802.1X	Multi-level passwords, IP filtering, HTTPS encryption, IEEE 802.1X	Multi-level passwords, IP filtering, HTTPS encryption, IEEE 802.1X	Multi-level passwords, IP filtering, HTTPS encryption, IEEE 802.1X	Multi-level passwords, IP filtering, HTTPS encryption, IEEE 802.1X	Multi-level passwords, IP filtering, HTTPS encryption, IEEE 802.1X
Network	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS
Power over Ethernet (IEEE 802.3af)		Class 2		Class 2/3 ⁴	Class 2/3 ⁴					
Serial connectors	RS-232, RS-485	RS-422/RS-485	RS-232, RS-485		RS-422/485	RS-232, RS-485	RS-232, RS-485	RS-232, RS-485	RS-485	RS-485
Standalone version	0186-004	0298-001	0256-004	0272-001	0288-004	0232-004	0185-004	0230-004		
Blade version	0210-011					0232-024	0209-011		0261-001	0289-001

1) Supports local storage with SD/SDHC card 2) Y/C video requires converter cable 3) Requires additional third-party pan/tilt/zoom device 4) Includes power output for analog camera 5) AXIS M7001 Covert Surveillance Kit also includes covert camera

Rack solutions

Designed for high-density installations, Axis video encoder rack solutions accommodate multiple video encoder blades in the same rack.

	AXIS 291 1U Video Server Rack	AXIS Video Server Rack	AXIS Q7900 Rack
			
Number of slots	3	12	14
Blades supported	AXIS Q7406 AXIS 240Q AXIS 241Q AXIS 241S AXIS 243Q	AXIS 240Q AXIS 241Q AXIS 241S	AXIS Q7406 AXIS 240Q AXIS 241Q AXIS 241S AXIS 243Q
Maximum number of channels	18	48	84
Rack size	1U	3U	4U
Rack height	19"	19"	19"
Built-in power supply	●	●	● Redundant Power Supply
Network	Ethernet 10BaseT/ 100BaseTX/1000BaseT (1 Gigabit Ethernet Port)	10BaseT/100BaseTX	Ethernet 10BaseT/ 100BaseTX/1000BaseT (4 Gigabit Ethernet Ports)
Axis part #	0267-004	0192-004	0287-004

Accessories

AXIS 295 Video Surveillance Joystick

AXIS 295 Video Surveillance Joystick is a USB device specifically designed for responsive and accurate control of all Axis pan/tilt/zoom and dome network cameras. It features a three-axis, durable (Hall-effect) joystick and twelve programmable push-buttons. Easy to install, just connect the joystick to the USB port and control the Axis cameras.



Axis part # 0248-001

Illuminators

Illuminators for indoor/outdoor surveillance in low light or complete darkness. Use with Axis day & night cameras.



AXIS T90A11 850nm 50 Deg	Axis part # 5013-111
AXIS T90A01 850nm 50 Deg PoE	Axis part # 5013-011
AXIS T90A20 850nm 120-180 Deg	Axis part # 5013-201
AXIS T90A21 850nm 50-100 Deg	Axis part # 5013-211
AXIS T90A33 850nm 10-20 Deg	Axis part # 5013-331
AXIS T90A40 850nm 120-180 Deg	Axis part # 5013-401

Power-over-Ethernet Midspans and Splitters

Axis Power over Ethernet midspan and splitters offer an easy, fast and cost-effective solution for powering network video products without the need to install power outlets and electrical cabling.



High PoE midspans and splitters are available for network cameras such as PTZ and PTZ dome cameras that require higher power consumption.

Power-over-Ethernet Midspans

1-port (high PoE)	Axis part # 5014-004
1-port	Axis part # 0226-004
8-port	Axis part # 5012-004
16-port	Axis part # 5012-014

Power-over-Ethernet Active Splitters

Axis part # 5014-501 (high PoE 12V)
Axis part # 5014-511 (high PoE 24V)
Axis part # 0170-004-01¹
Axis part # 0227-001
Axis part # 5008-001 (5V)

AXIS 292 Network Video Decoder

AXIS 292 Network Video Decoder decodes digital video and audio streams into analog video signals (Axis products only).



AXIS part # 0213-004

1) Not 802.3af compliant

©2009 Axis Communications AB. AXIS COMMUNICATIONS, AXIS, ETRAX, ARTPEC and VAPIX are registered trademarks or trademark applications of Axis AB in various jurisdictions. All other company names and products are trademarks or registered trademarks of their respective companies. We reserve the right to introduce modifications without notice.

Video management software

AXIS Camera Station

Comprehensive, easy-to-use video management software for monitoring, recording, playback and event management. Specially designed for Axis network cameras and video encoders.



10-camera base license
4-camera base license
20-camera add on license
5-camera add on license
1-camera add on license
1-year software upgrade

Axis part # 0202-004
Axis part # 0202-054
Axis part # 0202-264
Axis part # 0202-014
Axis part # 0202-034
Axis part # 0202-024

AXIS Camera Station One


Software solution for viewing and recording live video from a single Axis network camera. Available for free download.



For more information, visit www.axis.com/products/video/software/

AXIS Camera Management

Powerful and efficient installation and management tool for Axis network video products. Available for free download.



Axis' Application Development Partners

A wide variety of software solutions for video surveillance, remote monitoring or broadcasting are available from more than 500 Axis Application Development Partners.



Distributed by: