



This model is Discontinued. Consider the <a href="M112xa">M112xa</a> instead.

## **Key Features**

- Ultra-low purchase price
- Long life lamp of up to 10,000 hours lowers costs even more
- 3,200 lumens of brightness
- High 15000:1 contrast ratio for darker blacks and whiter whites
- SVGA (800 x 600) resolution
- Accurate and vivid color reproduction with BrilliantColor™ technology
- HDMI connectivity
- Display 3D content from Blu-ray, PCs, cable boxes and more
- ♦ Instant on/off

"The colors are vivid and the picture is bright." -Customer Review via <u>B&H</u>









# Lowest Total Cost of Ownership

The IN112x is one of the lowest priced office and classroom projectors we've ever offered. With lamps that last up to an amazing 10,000 hours and no filters to replace, it's an unbeatable value. Activate the Eco Blanking feature on the remote control when the projector isn't being used and lower the lamp's power usage by 70%, saving energy and significantly extending the life of the lamp.





3,200 lumens mean bright, clear images even with the lights on. Preset modes give you the best image quality on a beige wall, whiteboard, blackboard or other surface. The IN112x supports multiple forms of 3D, including Blu-Ray, 3D broadcasting, video games and PC connectivity. All your audience needs are 144Hz DLP Link 3D glasses (sold separately).



## Easy to Move and Install

At only 5.4 lbs. (2.45 kg), the IN112x projector's compact size and weight make it easy to move from room to room, but powerful enough to install. Built-in speaker and 3.5mm audio out port provide clear audio, and a RS232 port means it can be easily integrated into room control systems.



# Specifications\*

Projector	IN112x
Resolution – Native	SVGA (800 x 600)
Resolution – Maximum	WUXGA (1920 x 1200)
Display Technology	DLP
Video Standard Compatibility	NTSC, PAL, SECAM, 480i, 480p, 576i, 576p, 720p, 1080i, 1080p
Speakers	Mono 2W x 1
Lamp Brightness	3,200 lumens
Lamp Brightness – Low Power	2,900 lumens
Lamp Life	5,000 hours
Lamp Life – Low Power	10,000 hours
Lamp Power	203W
Lamp Power – Eco Mode	61W
Replacement Lamp	SP-LAMP-093
Contrast Ratio	15,000:1
Color Wheel	6 Segment, 2x Speed
Number of Colors	1.07 billion
Aspect Ratio	4:3
Aspect Ratio Compatibility	16:9, 16:10
Projection Distance – Minimum	1 m
Projection Distance - Maximum	10 m
Lens Type	Manual zoom and focus
Projection Offset	15
Keystone Correction	± 40°
Connectors – Inputs	3.5mm stereo audio, RS232, HDMI 1.4 (rear), Composite video, S-video, VGA x2, USB Type B (control & firmware)
Connectors – Outputs	3.5mm stereo audio, Monitor out (VGA)
Audible Noise	< 32 dBA at 0°F / -17.8°C
Audible Noise – Eco Mode	< 30 dBA at 0°F / -17.8°C
Included Accessories	Power cord, Remote, VGA cable, Documentation
Product Warranty	2 years

Projector	IN112x
Lamp Warranty	6 months
Accessories Warranty	90 days
Computer Compatibility	PC, Mac
Menu Languages	English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Traditional Chinese, Korean, Swedish, Russian, Finnish, Polish, Turkish, Danish, Arabic, Indonesian, Persian, Portuguese, Vietnamese, Czech, Romanian, Hungarian
Approvals	UL and c-UL, FCC, CE, CCC+CECP, KCC, NOM, PCT/CU/EAC, PSB, SABS, SASO, CB, Nemco/GS, KC
Throw and Zoom	
Throw Ratio – Minimum	1.90:1
Throw Ratio – Maximum	2.09:1
Zoom Ratio	1.1:1
Shipping	
Product Dimensions	8.7 x 11.5 x 4.7 in / 221 x 292.1 x 119.4 mm
Product Weight	5.4 lbs / 2.4 kg
Shipping Dimensions	12 x 14.3 x 7.8 in / 304.8 x 362 x 196.9 mm
Shipping Weight	7.1 lbs / 3.2 kg

<sup>\*</sup> Product specifications, terms, and offerings are subject to change at any time without notice.

#### **Accessories**

Universal Projector Ceiling Mount (PRJ-MNT-UNIV)

Motorized Electric Projector Screen: 120 in., 4:3 (SC-MOT-120)

Projector Lamp for the IN112x, IN114x, IN116x, IN118HDxc, IN119HDx, SP1080 (SP-LAMP-093)

LiteShow 4 DB+ Dual Band Wireless Adapter (INLITESHOW4DB+)

Presenter 4 RF Remote with Laser Pointer (HW-PRESENTER-4)

Replacement Remote for Meeting Room Projectors (HW-NAVIGATOR-4)

Soft Carry Case for Value Projectors (CA-SOFTVAL-2)

Projector Ceiling Mount System (Black) (PRJ-MNTKIT-UNIVB)

Projector Ceiling Mount System (White) (PRJ-MNTKIT-UNIVW)

SMART Mount Adapter (INA-SMRTADPT)

VGA Cable (36 ft / 11 m) (SP-VGA-11M)

Manual Pull Down Projector Screen: 84 in., 4:3 (SC-MAN-84)

Motorized Electric Projector Screen: 84 in., 4:3 (SC-MOT-84)

Motorized Electric Projector Screen: 100 in., 4:3 (SC-MOT-100)

Fixed Frame Projector Screen: 100 in., 4:3 (SC-FF-100)

Fixed Frame Projector Screen: 120 in., 4:3 (SC-FF-120)

Manual Pull Down Projector Screen: 100 in., 4:3 (SC-MAN-100)

Manual Pull Down Projector Screen: 120 in., 4:3 (SC-MAN-120)

Fixed Frame Projector Screen: 84 in., 4:3 (SC-FF-84)

Manual Pull Up Projector Screen: 80 in., 4:3 (SC-PU-80)

Manual Pull Up Projector Screen: 100 in., 4:3 (SC-PU-100)

DLP Link 3D Glasses by XPAND (X103-EDUX3-R1)

1 Year Extended Warranty for IN1XX Projectors (EPW-PJV1)

2 Year Extended Warranty for IN1XX Projectors (EPW-PJV2)