

All Specifications

Optical

Throw Ratio	0.35
Zoom Ratio	Fixed
Lens Control	Manual Zoom and Focus
Lens Shift	Vertical: 4%
Keystone Correction	2D; Vertical \pm 15 degrees, Horizontal \pm 15 degrees
Projection Offset**	125%
Projection Size (diagonal)	80" ~ 100"

Display

Projection System	DLP Single 0.65" WXGA (1280x800)
Resolution	1280x800 pixels
Brightness	3,500 ANSI Lumens
Display Color	1.07 Billion Colors
Aspect Ratio	Native 16:10 (5 aspect ratio selectable)
Light Source	Lamp (240W)
Light Source Life*	3000/4000/6000 hours (Normal/Eco/SmartEco mode)
Contrast Ratio	10000:1
DMD Type	DC3 DMD Chip

Audio

Built-in Speaker	20W (10Wx2)
------------------	-------------

Special Feature

Security Lock	Kensington Lock Security Bar
---------------	---------------------------------

Connectivity

I/O Port	HDMI x 2 (HDMI-1 share with MHL) PC In (D-sub 15pin) x 2 (share with component video) Monitor Out (D-sub 15pin) x 1 Composite Video In (RCA) x 1 S-Video In x 1 Audio In (mini jack) x 1 Audio L/R In (RCA) x 1 Audio Out (mini jack) x 1 LAN RJ45 x 1 (LAN control) RS232 (DB-9pin) x 1 USB (type A) x 1 (5V 2A power supply) USB (type B) x1 (firmware download) USB (type mini B) x 1 (optional interactive camera) IR Receiver x1 (front)
----------	--

Compatibility

Resolution Support	VGA (640 x 480) to WUXGA (1920 x 1200)
Horizontal Frequency	15K - 102kHz
Vertical Scan Rate	23 - 120Hz
HDTV Compatibility	480i, 480p, 576i, 576p, 720p, 1080i, 1080p
Video Compatibility	NTSC, PAL, SECAM

Power

Power Consumption (Max/Normal/Eco)	Max 350W. Normal 320W. Eco 260W
Standby Power Consumption	Network <2W, Standby<0.5W

Dimension and Weight

Product Dimensions (WxHxD)	373.3 x 130.2 x 287.5mm (w/o mirror) 373.3 x 201 x 287.5mm (w/ mirror)
Product Weight	5kg (w/o wall mount plate)

Operation Condition

Operating Temperature	0° ~ 40°C
-----------------------	-----------

Noise Level (Normal/Eco)

34/29 dBA

Accessories

Accessories (Standard)

Remote Control w/ Battery RCS011 x 1
 Power Cord (by region) x 1
 User Manual CD x 1
 Quick Start Guide x 1
 Warranty Card (by region) x 1
 VGA (D-sub 15pin) Cable x 1
 Wall Mount Kit (with installation guide) x 1

Accessories (Optional)

Spare Lamp Kit 5J.JC505.001
 3D Glasses DGD5 5J.J9H25.001
 Document Camera S30 9H.J9L78.T3E
 PointWrite Kit PW01U 5J.J8L26.20E
 PointWrite Touch Module PT12
 5J.J8L26.13E

OSD

On Screen Display Language

Arabic/ Bulgarian/ Croatian/ Czech/ Danish/
 Dutch/ English/ Finnish/ French/ German/
 Greek/ Hindi/ Hungarian/ Italian/ Indonesian/
 Japanese/ Korean/ Norwegian/ Polish/
 Portuguese/ Romanian/ Russian/ Simplified
 Chinese/ Spanish/ Swedish/ Turkish/ Thai/
 Traditional Chinese (28 languages)

LS2LT1

Lens

F=2.5, f=5.1mm

InstaShow Host

Power Supply

AC100V to 240V, 50Hz to 60Hz