



### Commercial status

Discontinued on: 14 January 2021

To be end-of-service on: 31 December 2030

⚠ To be discontinued

### Overview

Lead time	Usually Ships within 2 Weeks
-----------	------------------------------

### General

Provided equipment	Installation guide
--------------------	--------------------

### Physical

Colour	Grey
Depth	92.5 cm
Height	149.9 cm
Net weight	776 kg
Width	52.3 cm

### Input

Network frequency	50/60 Hz
Input voltage	208 V 3 phases 400 V 3 phases

### Conformance

Product certifications	CSA
Standards	CSA C22.2 No 107.1

### Environmental

Ambient air temperature for operation	-5...45 °C
Operating altitude	0...10000 ft
Relative humidity	0...85 %
Ambient air temperature for storage	0...30 °C
Storage altitude	0.00...4572.00 m
Storage Relative Humidity	0...85 %

## Batteries & Runtime

Battery location	Battery cabinet
Number of battery blocks per string	4
Number of battery free slots	0
Number of battery filled slots	6
Device mounting	Enclosed battery cabinet
Battery type	Lead-acid battery

## Packing Units

Package 1 Weight	807 kg
Package 1 Height	164.3 cm
Package 1 width	65 cm
Package 1 Length	106.2 cm

## Offer Sustainability

EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>

## Contractual warranty

Warranty	1 year repair or replace
----------	--------------------------