

LU950 5000lms WUXGA Conference

Let Your Innovation Shine through Accurate True Color

- 3,000,000:1 contrast ratio
- 95% Rec.709 color coverage
- Digital HDMI output for multi-screen projection
- Wired remote control for easy operation
- IP5X dustproof mechanism reducing maintenance costs

\$ 2999

Quotation

Out of stock



LU950	Overview	Specifications	Q&A	Downloads	Quotation
-------	----------	-----------------------	-----	-----------	------------------

All Specifications

Optical

Throw Ratio	1.36 ~ 2.18
Zoom Ratio	1.6x
Lens Control	Manual Zoom and Focus
Lens Shift	Manual lens shift, V: ±60 %; H: ±23 %
Keystone Correction	2D keystone, V: ±30 degree; H: ±30 degree
Projection Size	30" ~ 300"

Display

Projection System	DLP Single 0.47" WUXGA
DMD type	DC3 DMD Chip
Resolution	1920x1200 pixels
Brightness	5000 ANSI Lumens

Contrast Ratio*	3,000,000:1
Display Color	30 Bits (1.07 billion colors)
Aspect Ratio	Native 16:10 (5 aspect ratio selectable)
Light Source	Laser
Light Source Life*	20,000 hrs

Audio

Built-in Speaker	10W
------------------	-----

Special Feature

Security(anti-theft)	Security Bar
----------------------	--------------

Feature

Feature	Digital Shrink and Shift, Image Memory, Projector/ Remote Control ID Setting, Auto High Altitude Mode, HDBaseT, LAN Control, 360°Projection, Dust-Proof Filter
---------	--

Connectivity

I/O Port	Wired Remote In x1 RS232 In (D-sub 9pin, male) x1 USB Mini-B(Service) x1 USB TypeA(5V/2A power) x1 LAN Port(RJ45 for Network control) x1 HDBaseT x1 HDMI In x3 HDMI Out x1 S-Video in x1 Composite Video(RCA) x1 RCA Audio in- L/R x1 PC In x1 Monitor out (D-sub 15pin,Female) x1 Audio in(mini jack) x1 Audio out (mini jack) x1 12V Trigger x1 IR Receiver(Front) x1 IR Receiver(Rear) x1
----------	---

Compatibility

Resolution Support	VGA(640 x 480) to WUXGA_RB(1920 x 1200) *RB-Reduced Blanking"
Horizontal Frequency	15~102KHz
Vertical Scan Rate	24 ~ 120 Hz
HDTV Compatibility	480i, 480p, 576i, 567p, 720p, 1080i, 1080p
Video Compatibility	NTSC, PAL, SECAM

Power

Power Consumption (Max/Normal/Eco)	Max 530W/ Normal 475W/ Eco 365W
Standby Power Consumption	Normal < 0.5W, Network <2W

Dimension and Weight

Product Dimensions (WxHxD)	490 mm x 159 mm x 380 mm
Product Weight	9.4 kg

Operation Condition

Operating Temperature	0 ~ 40°C
Noise Level (Normal/Eco)	37 /35 dBA

Accessories

Accessories (Standard)	Power Cord Remote control (RCA011) Lens cover AAA Batteryx2 Installation Guide/Regulatory Statement(Combined) Warranty card(by sku) Anti-dust Filter
Accessories (Optional)	Ceiling mount (CMG3) 3D glasses InstaShow™ (WDC10)

OSD

On Screen Display Language	Arabic/ Bulgarian/ Croatian/ Czech/ Danish/ Dutch/ English/ Finnish/ French/ German/ Greek/ Hindi/ Hungarian/ Italian/ Indonesian/ Japanese/ Korean/ Norwegian /Persian/ Polish/ Portuguese/ Romanian/ Russian/ Simplified Chinese/ Spanish/ Swedish/ Turkish/ Thai/ Traditional Chinese/ Vietnam (30 languages)
----------------------------	--

InstaShow Host

Power Supply	100 ~ 240V AC
--------------	---------------

Contact Us

We would love to hear from you.

[Email Us](#)

Subscribe To Our Newsletter

[Sign Up](#)

Your Local Office

BenQ America Corp.
5741 Legacy Dr #210, Plano, TX 75024,
USA
Tel: 888-818-5888
Fax: +1-214-473-9998
[Or find your local office](#)

Follow Us

-  BenQ North America
-  BenQ North America
-  BenQ America
-  Business & Education
-  BenQ North America

Solutions

- Retail
- Restaurant
- Transportation
- Education
- Exhibition
- Corporate
- Hospitality
- Museums
- Healthcare

Products

- Digital Signage
- Interactive Displays
- Projectors
- Monitors
- Wireless Presentation
- Software

Resources

- Trends and Knowledge
- Success Stories
- News and Events

Support

- FAQs
- Downloads
- Member Login for IAM

Region and Language

- Choose your region
- About BenQ Business