



# Rack PDU, Switched, Zero U, 10A, 230V, (16) C13

**AP7950**

Call for More Information 18001030011

- Includes: Cord retention bracket(s), Installation guide, Rack mounting brackets, Toolless mounting kit, User manual

Output	
Nominal Output Voltage	230V
Overload Protection	No
Maximum Total Current Draw	10
Output Connections	(16) IEC 60320 C13

Input	
Nominal Input Voltage	200V, 208V, 230V
Input frequency	47 - 63 Hz
Input Connections	IEC 60320 C14
Cord Length	3.1meters
Acceptable Input Voltage	200 - 240VAC
Number of Power Cords	1
Maximum Input Current	10A
Maximum Line Current	10A

Physical	
Maximum Height	1245MM, 124.5CM
Maximum Width	56MM, 5.6CM
Maximum Depth	44MM, 4.4CM
Net Weight	4.32KG
Shipping weight	5.23KG
Shipping Height	2134MM, 213.4CM

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

## Technical Specifications

Rack PDU, Switched, Zero U, 10A, 230V, (16) C13 | AP7950 | Downloaded on 01/27/2022 (EST)

Physical	
Shipping Width	152MM, 15.2CM
Shipping Depth	127MM, 12.7CM
Color	Black

Environmental	
Operating Temperature	-5 - 45 °C
Operating Relative Humidity	5 - 95 %
Operating Elevation	0 - 3048meters
Storage Temperature	-25 - 65 °C
Storage Relative Humidity	5 - 95 %
Storage Elevation	0 - 15240meters

Conformance	
Approvals	CE, EN 55022 class A, EN 55024, EN 61000-3-2, EN 61000-3-3, GOST, IRAM, VDE
Standard warranty	2 years repair or replace

Sustainable Offer Status	
RoHS	Compliant
PEP	Available in Documentation tab
EOLI	Available in Documentation tab

**Disclaimer:** Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.