



## **Key Features**

- Ultra-low purchase price
- Long life lamp of up to 10,000 hours lowers costs even more
- 3,200 lumens of brightness
- High 15000:1 contrast ratio for darker blacks and whiter whites
- WXGA (1280 x 800) resolution
- 16:10 aspect ratio
- Accurate and vivid color reproduction with BrilliantColor™ technology
- HDMI connectivity
- Display 3D content from Blu-ray, PCs, cable boxes and more
- Instant on/off





# Lowest Total Cost of Ownership

The IN116x is one of the lowest priced office and classroom projectors we've ever offered. With lamps that last up to an amazing 10,000 hours and no filters to replace, it's an unbeatable value. Activate the Eco Blanking feature on the remote control when the projector isn't being used and lower the lamp's power usage by 70%, saving energy and significantly extending the life of the lamp.



### **Top-notch Image Quality**

3,200 lumens mean bright, clear images even with the lights on. Preset modes give you the best image quality on a beige



wall, whiteboard, blackboard or other surface. The IN116x supports multiple forms of 3D, including Blu-Ray, 3D broadcasting, video games and PC connectivity. All your audience needs are 144Hz DLP Link 3D glasses (sold separately).



### Easy to Move and Install

At only 5.4 lbs. (2.45 kg), the IN116x projector's compact size and weight make it easy to move from room to room, but powerful enough to install. Built-in speaker and 3.5mm audio out port provide clear audio, and a RS232 port means it can be easily integrated into room control systems.



# Specifications\*

| Resolution – Native           | WXGA (1280 x 800)   |
|-------------------------------|---|
| Resolution – Maximum          | WUXGA (1920 x 1200)   |
| Display Technology            | DLP   |
| Video Standard Compatibility  | NTSC, PAL, SECAM, 480i, 480p, 576i, 576p, 720p, 1080i, 1080p  |
| Speakers                      | Mono 2W x 1   |
| Lamp Brightness               | 3,200 lumens  |
| Lamp Brightness – Low Power   | 2,900 lumens  |
| Lamp Life                     | 5,000 hours   |
| Lamp Life – Low Power         | 10,000 hours  |
| Lamp Power                    | 203W  |
| Lamp Power – Eco Mode         | 61W   |
| Replacement Lamp              | SP-LAMP-093   |
| Contrast Ratio                | 15,000:1  |
| Color Wheel                   | 6 Segment, 2x Speed   |
| Number of Colors              | 1.07 billion  |
| Aspect Ratio                  | 16:10   |
| Aspect Ratio Compatibility    | 4:3, 16:9   |
| Projection Distance – Minimum | 1 m   |
| Projection Distance – Maximum | 10 m  |
| Lens Type                     | Manual zoom and focus   |
| Image Size – Maximum          | 299 in  |
| Projection Offset             | 15  |
| Keystone Correction           | ± 40°   |
| Connectors – Inputs           | 3.5mm stereo audio, RS232, HDMI 1.4 (rear), Composite video, S-video, VGA x2, USB Type B (control & firmware) |
| Connectors – Outputs          | 3.5mm audio output, Monitor out (VGA)   |
| Audible Noise                 | < 32 dBA at 0°F / -17.8°C   |
| Audible Noise – Eco Mode      | < 30 dBA at 0°F / -17.8°C   |
| Included Accessories          | Power cord, Remote, VGA cable, Documentation  |
| Product Warranty              | 2 years   |
| Lamp Warranty                 | 6 months  |

| Projector              | IN116x  |
|------------------------|---|
| Accessories Warranty   | 90 days   |
| Computer Compatibility | PC, Mac   |
| Menu Languages         | English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Traditional Chinese, Korean,<br>Swedish, Russian, Finnish, Polish, Turkish, Danish, Arabic, Indonesian, Persian, Portuguese, Vietnamese, Czech,<br>Romanian, Hungarian |
| Approvals              | UL and c-UL, FCC, CE, CCC+CECP, KCC, NOM, PCT/CU/EAC, PSB, SABS, SASO, CB, Nemco/GS, KC   |
| Throw and Zoom         |   |
| Throw Ratio – Minimum  | 1.50:1  |
| Throw Ratio – Maximum  | 1.80:1  |
| Zoom Ratio             | 1.2:1   |
| Shipping               |   |
| Product Dimensions     | 8.7 x 11.5 x 4.7 in /<br>221 x 292.1 x 119.4 mm   |
| Product Weight         | 5.4 lbs / 2.4 kg  |
| Shipping Dimensions    | 12 x 14.3 x 7.8 in /<br>304.8 x 362 x 196.9 mm  |
| Shipping Weight        | 7.1 lbs / 3.2 kg  |

\* Product specifications, terms, and offerings are subject to change at any time without notice.

#### Accessories

Universal Projector Ceiling Mount (PRJ-MNT-UNIV) Motorized Electric Projector Screen: 130 in., 16:10 (SC-MOTW-130) Projector Lamp for the IN112x, IN114x, IN116x, IN118HDxc, IN119HDx, SP1080 (SP-LAMP-093) LiteShow 4 DB+ Dual Band Wireless Adapter (INLITESHOW4DB+) Presenter 4 RF Remote with Laser Pointer (HW-PRESENTER-4) Replacement Remote for Meeting Room Projectors (HW-NAVIGATOR-4) Soft Carry Case for Value Projectors (CA-SOFTVAL-2) Projector Ceiling Mount System (Black) (PRJ-MNTKIT-UNIVB) Projector Ceiling Mount System (White) (PRJ-MNTKIT-UNIVW) VGA Cable (36 ft / 11 m) (SP-VGA-11M) Manual Pull Down Projector Screen: 94 in., 16:10 (SC-PDW-94) Manual Pull Down Projector Screen: 109 in., 16:10 (SC-PDW-109) Fixed Frame Projector Screen: 130 in., 16:10 (SC-FFW-130) Motorized Electric Projector Screen: 94 in., 16:10 (SC-MOTW-94) Motorized Electric Projector Screen: 113 in., 16:10 (SC-MOTW-113) Fixed Frame Projector Screen: 94 in., 16:10 (SC-FFW-94) DLP Link 3D Glasses by XPAND (X103-EDUX3-R1) SMART Mount Adapter (INA-SMRTADPT) 1 Year Extended Warranty for IN1XX Projectors (EPW-PJV1) 2 Year Extended Warranty for IN1XX Projectors (EPW-PJV2)