

# Product data sheet

## Characteristics

# AP8753

Free up space and secure power cords between rack-mount PDUs and attached IT equipment with this exclusive easy-to-use cord retention method. While these cords will fit into any standard IEC receptacle or power inlet; the "locking" feature is enabled only when used with APC AP8000 series Rack PDUs or IT equipment with built-in locking receptacles. These locking connectors reduce the probability of accidentally disconnecting cords and dropping loads.



### Overview

Description	<![CDATA[Free up space and secure power cords-between rack-mount PDUs and attached IT equipment with this exclusive easy-to-use cord retention-method. While these cords will fit into any standard IEC receptacle or power inlet; the "locking" feature is enabled only when used with APC AP8000 series Rack-PDUs or IT equipment with built-in locking receptacles. These locking connectors reduce the probability-of accidentally disconnecting cords and dropping loads.]]>
Model Name	Power Cord, Locking C19 to L6-20P, 3.0m
Standard Lead Time	Usually in Stock
Product Distribution	Canada , United States

### Output

Nominal Output Voltage	208V
Maximum Total Current Draw per Phase	20 A
Output Connections	(1) IEC 320 C19 (Battery Backup)
Always on Outlets	0
Cord Length	10

### Input

Regulatory Derated Input Current (North America)	16 A
Input Connections	NEMA L6-20P
Cord Length	9.84 feet (3 meters)
Number of Power Cords	0
Maximum Line Current per phase	20 A
Maximum Input Current per phase	20 A
Load Capacity	0 VA

### Physical

Net Weight	1.59 lbs (0.72 kg)
Maximum Height	9.06 inches (230.0 mm)
Maximum Width	9.06 inches (230.0 mm)
Maximum Depth	1.77 inches (45.0 mm)
Shipping Weight	1.59 lbs (0.72 kg)
Shipping Height	9.06 inches (230.0 mm)

Shipping Width	9.06 inches (230.0 mm)
Shipping Depth	1.77 inches (45.0 mm)
Color	Black

### Environmental

Operating Environment	32 - 221 °F (0 - 105 °C)
Operating Relative Humidity	20 - 80 %
Operating Elevation	0-10000 feet (0-3000 meters)
Storage Temperature	-13 - 221 °F (-25 - 105 °C)
Storage Relative Humidity	20 - 80 %
Storage Elevation	0-50000 feet (0-15000 meters)

### Conformance

Approvals	CSA , UL Listed
Standard warranty	2 years repair or replace

### Sustainable Offer Status

RoHS	Compliant
------	-----------