

AP4452



Provides redundant rack mount power to single-corded equipment.

Includes: Mounting hardware, Rack Mounting brackets, Serial configuration cable

Technical Specifications

Output

Overload Protection	No
Maximum Total Current Draw	20

Input

Input frequency	50/60 Hz
Number of Power Cords	2
Load Capacity	1920VA
Maximum Input Current	20A
Maximum Line Current	20A
Regulatory Derated Input Current (North America)	16A

We use cookies to provide you with a better onsite experience. By continuing to browse the site you are agreeing to our use of cookies in accordance with our Cookie Policy.

Physical

OK

Maximum Height	1.72inches (44MM, 4.4CM)
Maximum Width	17.0inches (432MM, 43.2CM)
Maximum Depth	9.3inches (236MM, 23.6CM)
Net Weight	9.7lbs. (4.4KG)
Shipping weight	13.6lbs. (6.17KG)
Shipping Height	4.5inches (114MM, 11.4CM)
Shipping Width	23.63inches (600MM, 60.0CM)
Shipping Depth	14.0inches (356MM, 35.6CM)
Color	Black

Environmental

Operating Temperature	23 - 113 °F (-5 - 45 °C)
Operating Relative Humidity	5 - 95 %
Operating Elevation	0-10000ft (0-3000meters)
Storage Temperature	-25 - 65 °C
Storage Relative Humidity	5 - 95 %
Storage Elevation	0-50000ft (0-15000meters)

Conformance

Approvals	EN 55022 Class A, FCC Part 15 Class A
Standard warranty	2 years repair or replace

Sustainable Offer Status

RoHS	Compliant
REACH	REACH: Contains No SVHCs
Battery Directive	Compliant
Other Environmental Compliance	China RoHS