



### Overview

Presentation	Housing equipment with side to side airflow creates many challenges for IT and facility managers, particularly in regards to cooling. Because most enclosures are designed for a front to back airflow pattern, it is difficult to maintain ideal operating temperatures on side to side airflow equipment. The Rack Side Air Distribution Unit is a 2U rack mountable air distribution product for networking equipment or servers with side to side airflow. It pulls in conditioned air from the front of the rack and distributes it to the side air intake of the networking equipment.
Lead time	Usually in Stock

### General

Provided equipment	Installation guide User Manual
Air flow	260 ft <sup>3</sup> /min (122.71 l/s)

### Physical

Number of rack unit	2U
Color	Black
Maximum Depth	26.34 in (66.9 cm)
Maximum Height	3.43 in (8.7 cm)
Net Weight	32.08 lb(US) (14.55 kg)
Maximum Width	16.97 in (43.1 cm)

### Input

Number of cables	2
Input Frequency	50/60 Hz
Plug standard	IEC 60320 C13 IEC 60320 C14
Nominal Input Voltage	200 V 208 V 230 V

### Conformance

Product certifications	CUL Recognized CE GOST UL Recognized
------------------------	---

### Communications & Management

Control panel	Power on/off indicator
---------------	------------------------

### Ordering and shipping details

GTIN	00731304232933
Package weight(Lbs)	43.10 lb(US) (19.55 kg)

## Packing Units

Package 1 Height	9.49 in (24.1 cm)
Package 1 width	25.98 in (66 cm)
Package 1 Length	30.98 in (78.7 cm)

## Offer Sustainability

EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
-------------------	--

## Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------