



Overview

Presentation	Free up space and secure power cords between rack-mount PDUs and attached IT equipment with this exclusive easy-to-use cord retention method. While these cords will fit into any standard IEC receptacle or power inlet; the "locking" feature is enabled only when used with APC AP8000 series Rack PDUs or IT equipment with built-in locking receptacles. These locking connectors reduce the probability of accidentally disconnecting cords and dropping loads.
Lead time	Usually in Stock

Physical

Cable length	4 ft (1.22 m)
Color	Black
Maximum Depth	2.76 in (7 cm)
Maximum Height	11.81 in (30 cm)
Net Weight	3.62 lb(US) (1.64 kg)
Maximum Width	2.76 in (7 cm)

Input

Plug standard	IEC 60320 C20
Number of cables	6
Max line current	16 A
Input current limits	16 A

Output

Maximum Total Current Draw per Phase	16 A
Number of power socket outlets	1 IEC 60320 C19
Cord Length	4 ft (1.22 m)

Conformance

Product certifications	CCC CSA PSE UL Listed VDE
------------------------	---------------------------------------

Environmental

Ambient air temperature for operation	32...167 °F (0...75 °C)
Relative humidity	20...80 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-13...167 °F (-25...75 °C)
Storage altitude	0...50000 ft (0.00...15240.00 m)

Ordering and shipping details

Category	11309 - APC RESALE PRODUCTS
GTIN	00731304279709
Nbr. of units in pkg.	1
Package weight(Lbs)	1 lb(US) (0.45 kg)
Returnability	No
Country of origin	CN

Packing Units

Package 1 Height	11.81 in (30 cm)
Package 1 width	2.76 in (7 cm)
Package 1 Length	2.76 in (7 cm)
SCC14	10731304279706
Number of Units in Package 3	270

Offer Sustainability

Sustainable offer status	Green Premium product
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Lead free	Yes
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Halogen content performance	Halogen free product

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------