



Overview

Presentation	The Step-Down Transformer converts high voltage (208 or 200 VAC) output into low voltage (120 or 100 VAC) output for powering low voltage AC equipment.
Lead time	Usually in Stock

General

Provided equipment	User Manual Rack Mounting brackets
--------------------	---------------------------------------

Physical

Color	Black
Depth	24.02 in (61 cm)
Height	3.50 in (8.9 cm)
Net Weight	95.20 lb(US) (43.18 kg)
Width	17.52 in (44.5 cm)

Input

Permissible voltage	208 V
Max line current	24 A
Input current limits	30 A
Load Capacity	5000 VA
Plug standard	NEMA L6-30P
Nominal Input Voltage	208 V

Output

Maximum Total Current Draw per Phase	24 A
Number of power socket outlets	12
Efficiency	90 %
Number of power socket outlets	12 NEMA 5-20R
Output voltage	120 V

Conformance

Product certifications	CSA
Standards	OSHPD UL 1778

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Environmental

Ambient air temperature for operation	32...104 °F (0...40 °C)
Relative humidity	0...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	5...113 °F (-15...45 °C)
Storage Relative Humidity	0...95 %
Storage altitude	0...50000 ft (0.00...15240.00 m)




Ordering and shipping details

GTIN	00731304249139
Package weight(Lbs)	110.23 lb(US) (50 kg)

Packing Units

Package 1 Height	10.00 in (25.4 cm)
Package 1 width	24.49 in (62.2 cm)
Package 1 Length	37.52 in (95.3 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant  EU RoHS Declaration
Lead free	Yes
Mercury free	Yes
RoHS exemption information	 Yes
Halogen content performance	Halogen free product
Optimized Energy Efficiency	Energy efficient product

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------