DS-LEDLSCB-5X5, 6X6, 8X8

TO MAKE YOUR NECK SHINE

LSCB015 (1.5mm) LSCB018 (1.8mm) LSCB025 (2.5mm)

SEAMLESS KITTED

Flat dvLED Mounting System

FOR LG LSCB SERIES DIRECT VIEW LED DISPLAYS

Peerless-AV's SEAMLESS Kitted Series Flat dvLED Mounting System is designed exclusively for the LG LSCB Series Direct View LED Displays, offering slim, space-saving, and aesthetically appealing designs for multiple configurations. With integrated cable management, easy-hang hardware, and a lightweight aluminum frame, integrators can quickly and easily build the perfect video wall. Peerless-AV® also offers start to finish support through the SEAMLESS dvLED Video Wall Integration Program. The Peerless-AV dvLED Solutions Team is there every step of the way to ensure every customer receives SEAMLESS product support and service.




- Lightweight aluminum frame is easy to install and

minimizes the wall load

- Modular design offers unlimited video wall display configurations
- Tight tolerances and wall plate spacers assure the cabinets are properly positioned





SEAMLESS by Peerless-AV® - dvLED Video Wall Integration Program offers:



EXPERT ENGINEERING & DESIGN



CUSTOM PROJECT MANAGERS



FULL INSTALLATION SERVICES



SEAMLESS dvLED MOUNTING SYSTEMS



Visit Peerless-AV.com/SEAMLESS to get your project started!

WARRANTY: Lifetime Model Numbers

DS-LEDLSCB-5x5 SEAMLESS Kitted Series Flat dvLED Mounting System for 5x5 LG LSCB Series Direct View LED Displays **DS-LEDLSCB-6X6** SEAMLESS Kitted Series Flat dvLED Mounting System for 6x6 LG LSCB Series Direct View LED Displays **DS-LEDLSCB-8X8** SEAMLESS Kitted Series Flat dvLED Mounting System for 8x8 LG LSCB Series Direct View LED Displays

Product Specifications

	DIMENSIONS (W x H x D)	PRODUCT WEIGHT	LOAD CAPACITY	FINISH	AVAILABLE COLORS
DS-LEDLSCB-5X5 DS-LEDLSCB-6X6 DS-LEDLSCB-8X8	118.11" x 65.50" x 2.16"-2.91" (3000 x 1664 x 55-74mm) 141.73" x 78.79" x 2.16"-2.91" (3600 x 2001 x 55-74mm) 188.98" x 105.36" x 2.16"-2.91" (4800 x 2676 x 55-74mm)	83lb (38kg) 102lb (46kg) 165lb (75kg)	286lb (130kg) 412lb (187.2kg) 733lb (332.8kg)	Powder Coat & Clear Anodized Finish	Black & Silver

Package Specifications


	PACKAGE SIZE (W x H x D)	PACKAGE SHIP WEIGHT	PACKAGE UPC CODE	PACKAGE CONTENTS	UNITS IN PACKAGE
DS-LEDLSCB-5X5 DS-LEDLSCB-6X6 DS-LEDLSCB-8X8	116.50" x 29.00" x 8.00" (2959 x 737 x 203mm) 116.50" x 29.00" x 8.00" (2959 x 737 x 203mm) 116.50" x 29.00" x 8.00" (2959 x 737 x 203mm)	200lb (91kg) 223lb (101kg) 284lb (129kg)	735029341970 735029340720 735029340737	Wall Plate, Mounting Bracket, Spacer & Hardware	1

Accessories

DS-LEDTK Models: Universal Trim Kit for dvLED Video Walls 3.5" to 5.9" Deep

All dimensions = inch (mm)

MODEL NO.	DIMENSION "A"	DIMENSION "B"	DIMENSION "C"	DIMENSION "D"	DIMENSION "E"	Video Wall Width	Video Wall Height
DS-LEDLSCB-5x5	65.50" (1664mm)	118.11" (3000mm)	108.61" (2759mm)	30.68" (779mm)	58.42"(1484mm)	118.11" (3000mm)	66.44" (1688mm)
DS-LEDLSCB-6x6	78.79" (2001mm)	141.73" (3600mm)	132.23" (3359mm)	30.68" (779mm)	71.71"(1821mm)	141.73" (3600mm)	79.72" (2025mm)
DS-LEDLSCB-8x8	105.36" (2676mm)	188.98" (4800mm)	179.48" (4559mm)	30.68" (779mm)	98.28"(2496mm)	188.98" (4800mm)	106.30" (2700mm)



Architect Specifications

The SEAMLESS Kitted Series Flat dvLED Mounting System shall be a Peerless-AV model DS-LEDLSCB-4X4, 5X5, 6X6, 8X8 and shall be located where indicated on the plans. Assembly and installation shall be done according to instructions provided by the manufacturer.

Visit peerless-av.com to see the complete line of AV solutions from Peerless-AV, including outdoor displays, kiosks, display mounts, projector mounts, carts/stands, and a full assortment of accessories.

Peerless-AV

2300 White Oak Circle Aurora, IL 60502 USA

(800) 865-2112 (630) 375-5100 Fax: (800) 359-6500

Peerless-AV EMEA

Unit 3 Watford Interchange Colonial Way, Watford Herts, WD24 4WP United Kingdom

+44 (0) 1923 200100 Fax: +44 (0) 1923 200101

Peerless-AV Latin America

Av. de las Industrias 413 Parque Industrial Escobedo General Escobedo, N.L., México, 66062

+52 (81) 8384-8300 Fax: +52 (81) 8384-8360

