



Enduring Quality, Exceptional Value

www.marathonbroadband.com

Natural and UV Black Nylon 6.6 Cable Ties

- Great for bundling cable, wire, hoses, ducts and countless other applications
- Good resistance to bases, oils, grease, oil derivatives and chloride solvents
- Flammability rating: UL 94 - V2
- UL Certified for electrical installations under UL62275
- UL Certified to support flexible metal conduits and cables in construction under UL Type 21



Natural RoHS and Reach Compliant

Part Number / SIM Number	Pack Size	Length	Tensile Strength	Min Bundle Diameter	Max Bundle Diameter	UV Resistant	Barb Type	UL Type / Plenum / ROHS-Reach	Min/Max Operating Temp	Min Install Temp
CTNAT15IN50100 / 40156499968	100	370mm/14.5in	230N/50lbs	3.5mm/0.14in	1035mm/3.94in	No	Plastic	UL 21/AH-2/Yes	-40°F/185°F (-40°C/85°C)	14°F (-10°C)
CTNAT8IN401000 / 40156499964	1000	200mm/8in	180N/40lbs	3.5mm/0.14in	52.5mm/2.07in	No	Plastic	UL 21/AH-2/Yes	-40°F/185°F (-40°C/85°C)	14°F (-10°C)
CTNAT8IN181000 / 40156499962	1000	200mm/8in	80N/18lbs	3.5mm/0.14in	52.5mm/2.07in	No	Plastic	UL 21/AH-2/Yes	-40°F/185°F (-40°C/85°C)	14°F (-10°C)
CTNAT8IN501000 / 40156499960	1000	190mm/7.5in	230N/50lbs	3.5mm/0.14in	46mm/1.81in	No	Plastic	UL 21/AH-2/Yes	-40°F/185°F (-40°C/85°C)	14°F (-10°C)
CTNAT5IN401000 / 40156499959	1000	140mm/5.5in	180N/40lbs	3.5mm/0.14in	33mm/1.3in	No	Plastic	UL 21/AH-2/Yes	-40°F/185°F (-40°C/85°C)	14°F (-10°C)
CTNAT8IN50100 / 40156499954	100	200mm/8in	230N/50lbs	3.5mm/0.14in	49.5mm/1.95in	No	Plastic	UL 21/AH-2/Yes	-40°F/185°F (-40°C/85°C)	14°F (-10°C)

High Performance Black UV Resistant

Part Number / SIM Number	Pack Size	Length	Tensile Strength	Min Bundle Diameter	Max Bundle Diameter	UV Resistant	Barb Type	UL Type / Plenum / ROHS-Reach	Min/Max Operating Temp	Min Install Temp
CTBHP15IN501000 / 40156499972	1000	370mm/14.5in	230N/50lbs	3.5mm/0.14in	103.5mm/4.44in	Yes	Metal	UL 21/AH-2/No	-40°F/185°F (-40°C/85°C)	14°F (-10°C)
CTBHP12IN401000 / 40156499970	1000	300mm/11.8in	180N/40lbs	3.5mm/0.14in	84mm/3.31in	Yes	Metal	UL 21/AH-2/No	-40°F/185°F (-40°C/85°C)	14°F (-10°C)
CTBHP8IN501000 / 40156499965	1000	200mm/8in	230N/50lbs	3.5mm/0.14in	49.5mm/1.95in	Yes	Metal	UL 21/AH-2/No	-40°F/185°F (-40°C/85°C)	14°F (-10°C)

Marathon products are available from the following distributors:

Wesco
buy.wesco.com
 866.746.3519

TVC Communications
www.tvcinc.com
 888.644.6075

D230131-102519



Enduring Quality, Exceptional Value

www.marathonbroadband.com



Standard Black UV Resistant ROHS/Reach Compliant

Part Number / SIM Number	Pack Size	Length	Tensile Strength	Min Bundle Diameter	Max Bundle Diameter	UV Resistant	Barb Type	UL Type/ Plenum/ ROHS-Reach	Min/Max Operating Temp	Min Install Temp
CTB15IN50100 / 40156499971	100	370mm/14.5in	230N/50lbs	3.5mm/0.14in	103.5mm/4.44in	Yes	Plastic	UL 21/AH-2/Yes	-40°F/185°F (-40°C/85°C)	14°F (-10°C)
CTB15IN501000 / 40156499969	1000	370mm/14.5in	230N/50lbs	3.5mm/0.14in	1035mm/3.94in	Yes	Plastic	UL 21/AH-2/Yes	-40°F/185°F (-40°C/85°C)	14°F (-10°C)
CTB8IN501000 / 40156499967	1000	190mm/7in	230N/50lbs	3.5mm/0.14in	46mm/1.69in	Yes	Plastic	UL 21/AH-2/Yes	-40°F/185°F (-40°C/85°C)	14°F (-10°C)
CTB15IN50500 / 40156499966	500	370mm/14.5in	230N/50lbs	3.5mm/0.14in	103.5mm/4.44in	Yes	Plastic	UL 21/AH-2/Yes	-40°F/185°F (-40°C/85°C)	14°F (-10°C)
CTB5IN401000 / 40156499963	1000	140mm/5.5in	180N/40lbs	3.5mm/0.14in	33mm/1.3in	Yes	Plastic	UL 21/AH-2/Yes	-40°F/185°F (-40°C/85°C)	14°F (-10°C)
CTB12IN501000 / 40156499961	1000	300mm/11.8in	230N/50lbs	3.5mm/0.14in	81mm/3.19in	Yes	Plastic	UL 21/AH-2/Yes	-40°F/185°F (-40°C/85°C)	14°F (-10°C)
CTB4IN181000 / 40156499958	1000	100mm/4in	80N/18lbs	3mm/0.12in	20.5mm/0.81in	Yes	Plastic	UL 21/AH-2/Yes	-40°F/185°F (-40°C/85°C)	14°F (-10°C)
CTB8IN40100 / 40156499957	100	200mm/8in	180N/40lbs	3.5mm/0.14in	52.5mm/2.07in	Yes	Plastic	UL 21/AH-2/Yes	-40°F/185°F (-40°C/85°C)	14°F (-10°C)
CTB11IN40100 / 40156499956	100	280mm/11in	180N/40lbs	3.5mm/0.14in	78mm/3.07in	Yes	Plastic	UL 21/AH-2/Yes	-40°F/185°F (-40°C/85°C)	14°F (-10°C)
CTB15IN40100 / 40156499955	100	370mm/14.5in	180N/40lbs	3.5mm/0.14in	106mm/4.17in	Yes	Plastic	UL 21/AH-2/Yes	-40°F/185°F (-40°C/85°C)	14°F (-10°C)
CTB8IN50100 / 40156499953	100	200mm/8in	230N/50lbs	3.5mm/0.14in	49.5mm/1.95in	Yes	Plastic	UL 21/AH-2/Yes	-40°F/185°F (-40°C/85°C)	14°F (-10°C)
CTB11IN50100 / 40156499952	100	280mm/11in	230N/50lbs	3.5mm/0.14in	81mm/3.19in	Yes	Plastic	UL 21/AH-2/Yes	-40°F/185°F (-40°C/85°C)	14°F (-10°C)
CTB14IN50100 / 40156499951	100	360mm/14in	230N/50lbs	3.5mm/0.14in	100mm/3.94in	Yes	Plastic	UL 21/AH-2/Yes	-40°F/185°F (-40°C/85°C)	14°F (-10°C)
CTB8IN120100 / 40156499950	100	200mm/8in	540N/120lbs	8.5mm/0.33in	50.9mm/2in	Yes	Plastic	UL 21/AH-2/Yes	-40°F/185°F (-40°C/85°C)	14°F (-10°C)
CTB14IN120100 / 40156499949	100	365mm/14in	540N/120lbs	8.5mm/0.33in	1033.5mm/4.07in	Yes	Plastic	UL 21/AH-2/Yes	-40°F/185°F (-40°C/85°C)	14°F (-10°C)

Marathon products are available from the following distributors:

Wesco
buy.wesco.com
 866.746.3519

TVC Communications
www.tvcinc.com
 888.644.6075

D230131-102519