

THERMOSTATS AND RELAY KITS



T4800A

ELECTRONIC T4800A

- Euro styling
- High sensitivity solid state temperature sensing thermistor
- Precision differential of $\pm 0.5C/1F$
- LED status indication
- Energy efficient offering the highest degree in accuracy
- Temperature range: 5-27C/40-80F



T4600A

PROGRAMMABLE T4600A

- Modern contemporary styling
- LCD display of time, temperature and load status
- Precision differential of $\pm 0.4C/1F$
- Solid state temperature sensing thermistor
- 5-2 day programming, with weekly "away" mode for weekend flexibility
- Energy efficient offering the highest degree in accuracy
- Temperature range: 7-27C/45-80F




TS931/TD932


LINE VOLTAGE

TS931/TD932 & TS901/TD902

- Euro styling (TS931/TD932)
- Temperature control offers a wide range of comfort settings
- Temperature range: 10-32C/50-90F
- Operating differential of $\pm 1C/1.8F$
- Rigid aluminum base for durability and performance accuracy
- Attractive styling blends into any décor



TS901W/TD902W



LOW VOLTAGE

T86A & T822D

- Traditional styling
- Adjustable anticipator setting
- Temperature range: 10-30C/50-86F
- To be used with 24V control systems

T86AW

T822DW



ACCESSORIES (FIELD INSTALLATION)

CAT. No. F29-0143

DESCRIPTION

Universal plastic thermostat guard c/w locking key. Fits all of the above units. 162mm (L) x 89mm (W) x 82.8mm (D)

ORDERING GUIDE (THERMOSTATS)

CAT. No.	RATING		SWITCH	COLOUR
	NON-INDUCTIVE	INDUCTIVE		
Line Voltage				
T4800A	500W/240V min, 3800W/240V max.	N/A	SPST	White
T4600A	500W/240V min, 2500W/240V max.	N/A	SPST	White
TS931	5000W/240V max.	1/3HP/240V	SPST	White
TD932	5000W/240V max.	1/3HP/240V	DPST	White
TS901	5000W/240V max.	1/3HP/240V	SPST	Almond
TS901W	5000W/240V max.	1/3HP/240V	SPST	White
TD902	5000W/240V max.	1/3HP/240V	DPST	Almond
TD902W	5000W/240V max.	1/3HP/240V	DPST	White
Low Voltage				
T86A	30V AC max, 1.5 Amp.	N/A	Mercury	Beige
T86AW	30V AC max, 1.5 Amp.	N/A	Bulb	White
T822D	30V AC max, 1.5 Amp.	N/A	Mercury	Almond
T822D2642	30V AC max, 1.5 Amp.	N/A	Bulb	White

ORDERING GUIDE (RELAYS & TRANSFORMERS)

CAT. No.	WATTAGE RATING	SUPPLY VOLTAGE
R841C1193	2640	120
R841C1011	4575	208
R841C1227	5200	240
R841C1144	6000	347
R841C1151	6000	600
Relay less Transformer		
R841D1028	22A up to 240V, 17A @ 347V, 10A @ 600V	
Remote Mounted 24 Volt Transformers		
AT72D1865	40VA	120
AT72D1733	40VA	208
AT72D1972	40VA	240