




# WALKER NONMETALLIC FLOOR BOXES

## Cover Plates for Modulink Floor Boxes


### 828R\* COVER PLATE

Brass duplex cover plate, flip lids. Can also be used with a 106 type communication bezel. Interlink 106 Bezel part number AC-DP106.




### 8286FI\* COVER PLATE

Brass GFI cover plate. May be used with Interlink Activate Connectivity System in conjunction with 817B, 827B and 837B flanges.





### 828P COVER PLATE

Brass duplex cover plate, screw plugs. Screw plugs are 1 1/2" [38mm] in diameter.




### 829CK COVER PLATE

Brass communications cover plate, 2 5/8" [67mm] and 2 1/4" [57mm] plugs.





### 829CK-1 COVER PLATE

Brass communications cover plate, 2 5/8" [67mm] and 1" [25mm] plugs.



### 829CK-3/4 COVER PLATE

Brass communications cover plate, 2 5/8" [67mm] and 3/4" [19.1mm] plugs.



**NOTE:** Brass cover plates can be used only with brass flanges.

\*For Activate UTP, STP, coaxial, audio, video and fiber optic inserts, face plates, mounting bezels and identification products see section P2.




## WALKER NONMETALLIC FLOOR BOXES

**Modulink™ 880MP Series Rectangular Floor Box**


### 880MP NONMETALLIC RECTANGULAR FLOOR BOX



Box comes complete with reusable mud-cap and conduit plugs and reducers. Reducers provided for reduction to 1" [25mm], 3/4" [19.1mm] and 1/2" [12.7mm] conduit. Minimum capacity is 50 cubic inches [819ml] and maximum capacity is 100 cubic inches [1639ml]. Box dimensions are 4 1/8" [105mm] W x 5 1/2" [140mm] L x 6" [152mm] H.




*Minimum box depth is 3 1/2" [89mm] and maximum box depth is 6" [152mm].*




### 880MPA NONMETALLIC RECTANGULAR FLOOR BOX ADJUSTING RING\*



Comes with fiber storage loop. Also includes brass inserts for flange connection and green ground wire for ground connection. Interlink Activate Connectivity System modular inserts can snap directly into the adjusting ring without the need for a bezel. Also includes mounting screws to attach flange to box body.



*One 880MPA is needed for each 880MP used. For example, a three-gang box will require three 880MPA adjusting rings.*



\* For Activate UTP, STP, coaxial, audio, video and fiber optic inserts, faceplates, mounting bezels and identification products see section P2.

---

## LIMITATION OF LIABILITY

The Wiremold Company's sole obligation (and buyer's sole and exclusive remedy) with respect to any goods that are proven to be defective shall be the repair or replacement of such goods, at The Wiremold Company's option.

The Wiremold Company shall not be liable for any damages in excess of the purchase price of such goods and under no circumstances shall The Wiremold Company be liable for incidental or consequential damages or losses of any nature or description whatever.

Certain products may have a specific Warranty or Limitation of Liability different from the above and are included with the goods affected, and the terms of any such specific warranty or limitation of liability will supercede the above.

To better serve your project requirements, The Wiremold Company strives to improve products on a continuous basis. The information and/or specifications contained in this catalog may change without prior notice.

---

Wiremold Raceways and Fittings are listed by Underwriters Laboratories Inc. and the Canadian Standards Association. Registered Trademarks of The Wiremold Company and its subsidiaries include: Airey-Thompson, CabinetMATE, Cable Tuck, Centerex, Chan-L-Wire, ColorMatch, CordMate, Conduct, EndZone, EZ-Pole, Fantom Flex, Flexible Pancake, Flushduct, HideAcord, Linetamer, N-R-G-Bloc, N-R-G-Floor, On-Wall, Pancake, PanelZone, Perma Power, Plug-In Outlet Center, Plugmold, Plugmold Plus, Plugtrim, Power Commander, Power Tender, Presource III, Quick-E-Pole, Quick Tap, Resource RFB, Sentinel Lighting, Sentrex, Snapicoil, Sockets Plus, Sonic Connections, Sonictim, Source I, Source II, Sure-Snap, SurgeREACTOR, Synergy, Tele-Power, Thin Mau, Uniduct, Walker, Walkerbox, Walkercell, Walkerdeck, Walkerdut, Walkerdut Pro, Walkerflex, Walkermold, Walkerpole, Walkertap, Wire Light, Wiremold, and Wiring Projects Made Easy. Trademarks of The Wiremold Company include Access, Activate, AnySize, CLub Performance, CrossWay -110, DoubleUPS, EntryZone, EZ-Flex, FiberReady, FibreReady, FiberSmart, FibreSmart, FlexGuard, FloorSource, Future Proof, Interlink, Interlink Label, Isoduct, Modulink, Multiplex, Omnibox, On-Call, Prewired Select, ProComm, Profile Series, Quick Fit, Ratchet-Pro, RCI, ScuffCoat, Senflex, Size-Up, Source III, SpecMate, SurgeMan, Terminal, Twin Snap, V200, V500, V700, Wall Ready, WallSource, and Wiremold Logistics. Wiremold Prewired XPress is a Service Mark of The Wiremold Company. All brand and product names are registered trademarks or trademarks of their respective holders.

All Wiremold products, unless specifically noted, are listed by Underwriters Laboratories Inc. and conform to Federal Specifications W-C-582 and the National Electrical Code. Products designed for use in telephone or communications wiring normally do not require UL listing. Most products in this catalog are also certified by the Canadian Standards Association. Special ordering information for products to be installed in Canada is available upon request.