

Refurbished CISCO A9KV-V2-DC-E Datasheet

CISCO > ROUTERS

Cisco ASR 9000 Series Aggregation Services Routers

Cisco ASR 9000v and Cisco ASR 9000v-V2 Interfaces

| | |
|---------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 44 Small Form-Factor Pluggable (SFP) ports (10, 100 and 1000 Mbps) | SFP ports deliver 10, 100, and 1000 Mbps services. See the Cisco Optical Pluggable Modules for ASR 9000v Data Sheet for details on the supported pluggable ports. |
| 4 SFP+ 10-GE Pluggable Ports | SFP+ interfaces provide mix-and-match interface types. For a complete list of supported interfaces, see the Cisco Optical Pluggable Modules for ASR 9000v Data Sheet for details on the supported pluggable ports. |
| AC | Cisco ASR 9000v AC Chassis only, this three-connector receptacle is intended for use with external AC cables. |
| ANSI DC-A and DC-B | Cisco ASR 9000v DC-A Chassis only, these two redundant DC power inputs are ANSI compliant. |
| ETSI DC-A and DC-B | Cisco ASR 9000v DC-E Chassis only, these two redundant DC power inputs are ETSI compliant. |
| EOBC | Ethernet management port that can be optionally used for local Cisco ASR 9000v management. |
| Console | Serial port that can be optionally used for local Cisco ASR 9000v management. |
| Time of day (ToD) and packets per second (PPS) | Reserved for future use. |

The next steps...

[ORDER NOW](#)

[VIEW ONLINE](#)

Tel: +44 (0)1279 408 777

Email: sales@gocomsys.com

Website: www.gocomsys.com