

JTouch Interactive Displays

Touchscreens that enhance collaboration & captivate audiences



JTouch Interactive Displays

Whether you're in a classroom or huddle space, a conference room or auditorium, there's a JTouch interactive display solution to fit your needs and engage your audience.



Full Touch Control

Display your PC, Mac, or Chromebook via HDMI or VGA & control it from the display via touch using a USB cable.

- Extend the reach of your computer's USB ports with easily-accessible USB ports on the display
- No calibration or special stylus means it's quick and easy to use with just your fingertips

High Brightness and HD Clarity

JTouch helps you get your message across and connect with your audience with incredible brightness, color and clarity. With 1080p and 4K resolution, your images, text and video will be seen and enjoyed even in large spaces with high ambient light.

Key Features

- Giant, high resolution touch displays for a great price
- Incredibly sharp 4K or 1080p HD resolution
- Run all your apps, even the older ones, with touch
- Accurate and responsive touch overlay with multi-touch capability

Cast Content Wirelessly

Easily connect and share content from nearly any computer or mobile device to your JTouch. You'll make meetings, lessons and teamwork more efficient, engaging and easy. InFocus casting technology works seamlessly with any device and supports all operating systems, including Chrome OS.

Browse the Weh

Access your favorite online content without a connected computer.

View Documents

View and present Office files, as well as most photo and video file formats, directly from the JTouch.

Create on an Interactive Whiteboard

Write, draw, and capture ideas on a giant, multi-screen canvas.

Interactive Whiteboard and Annotation

Stop taking photos of your old dry-erase board & step up to a digital whiteboard. You'll never lose an idea & your meetings will be more efficient & productive.

Draw, Write, & Capture Notes

- Create a whiteboard on a multi-screen canvas, with room for free-form drawings, diagrams, images, and notes
- Write or draw with complete collection of digital pens, highlighters, shapes, lines and colors
- Use with fingers or a stylus
- View and annotate over PowerPoint, images, Word and more.
- Save and share your notes electronically



The most education-friendly JTouch ever JTouch Plus INF7530eAG & INF8630eAG

The totally customizable INF7530eAG and INF8630eAG feature 4K resolution, Total Touch Control™, and the ability to natively run Android applications.

- Brilliant 75- or 86-inch, 4K resolution screen with anti-glare
- Easy-for-anyone interface with Total Touch Control[™] no need for a remote
- Built-in whiteboard, browser, media player, and AirPlay capability
- Annotate over any application or video input
- · Comment and draw over websites, documents, and more
- Add Android apps
- · Customize your whiteboard background
- · Erase with three-finger touch



"Overall the JTouch is a jack of all interactive trades – it has the ability to draw in a rainbow of colors, display smooth video and let you connect without needing a new app."

Choose Your JTouch

	65-inch	75-inch	86-inch
Wireless	✓	✓	✓
Digital Whiteboard	✓	✓	✓
Internet Browser	✓	✓	✓
Document Viewer*	✓	Limited**	Limited**
4K Resolution	Resolution 1080p		✓
Capacitive Touch	✓	Infrared	Infrared
Anti-Glare	✓	✓	✓

^{*}Document viewer supports the following file types: pdf, doc, docx, xls, xlsx, ppt, pptx, avi, mkv, mpg, mpeg, mov, mp4, 3gp, rm, rmvb, jpg, jpeg, bmp, and png

 $^{^{\}star\star}$ Full featured document viewer app available: www.infocus.com/products/ins-and-file

	65-inch	75-inch	86-inch
Offices	✓		
Meeting Rooms	✓	✓	
Large Meeting Rooms	✓	✓	✓
Classrooms	✓	✓	✓
Lecture Halls		✓	✓



"I use my iPad to cast live camera feed of what students have created to the JTouch.

-Mrs. Joy, 5th Grade School Teacher

Accessories for JTouch Displays

LiteShow 4 DB+

Add the InFocus LiteShow 4 DB+ wireless presentation adapter to any base model display with a VGA or HDMI input to quickly and easily share data, audio, and HD video over a secure wireless connection.

- Connect LiteShow 4 DB+ to your network to create a new, secure wireless access point
- 2.4GHz / 5GHz Dual Band wireless technology for ultra-fast transmission
- · On-board video decoding for fast, smooth playback
- Guests guickly connect with LiteShow USB drive
- Compatible with Windows 7, 8 & 10, Mac & iOS and Android mobile devices
- Connect and display multiple computers at the same time

SimpleShare

A true cable replacement, Simple Share is the easiest, most direct way to share videos, presentations, documents, data, and more—with no software to install and nothing to manage on the network.

- Plug & play-no software installation
- Easily switch presenters with the click of a button
- Transmit high quality HD video and sound in real time
- Works with any HDMI input, PC, Mac, DVD player, or other devices
- Available with touch adapter to wirelessly control your PC from the display

Mobile Carts

Easily roll your JTouch around the room or around the building.

- Integrated cable management with flexible covers to hide cables for a clean installation
- Smooth rolling casters for effortless positioning (2 locking casters)
- Height adjustment 4-6' (1.2-1.8 m)

Lift Case

Easily store, transport, and use a 65" flat screen display. Set up displays with only one or two people and be ready for use in less than 5 minutes.

- Full range of viewing heights
- Mounted multi-outlet surge protected power strip
- Shock-mounted lift mechanism
- Integrated cable management system
- 2-piece clamshell locking lid
- Stable, yet portable with four heavy duty casters

Qwizdom Software Bundle

The Qwizdom bundle is designed for use with InFocus displays in the classroom.

- Includes Oktpus, Oktopus Blend, and Ximbus software
- · Offers curriculum and educational tools for traditional and cloud-based environments
- · Includes a one year license for the teacher and up to 40 students













Specifications*



Display	INF6505 INF6505e INF6505AG INF6505eAG	INF6502WB INF6502WBp INF6502WBAG INF6502WBAGp	INF7530AG INF7530eAG	INF8630AG INF8630eAG		
Size	65" Di	agonal	75" Diagonal	86" Diagonal		
Resolution	FULL HD 1:	920 × 1080	4K 384	0 × 2160		
Anti-Glare	INF6505AG INF6505eAG	INF6502WBAG INF6502WBAGp	Yes	Yes		
Wireless Collaboration	Casting embedded					
Mounting Orientation	Landscape					
Technology	Direct LED Backlight					
Pixel Pitch	0.40mm	0.744mm	0.429mm			
Response Time	8ms	6.5ms	8ms			
Contrast Ratio	4,000:1	5,000:1	1,2	00:1		
Brightness	300cd/m2	3500	cd/m2	450cd/m²		
Input Connections	HDMI x4, USB x3 on front, USB x2 on rear RJ-45 Ethernet, VGA, 3.5mm line-in audio (mono), component video, composite video, RS232	HDMI ×4, VGA, Component Video, USB-A x4 on panel, USB-A x2 on bottom for embedded software, RS232, 3.5mm line-in audio (mono), RCA stereo audio, 3.5mm microphone	HDMI x 5, VGA, RJ45, PC Audio In (stereo, VGA Audio source), component video, composite video, 1/8° Microphone (Mono linked to OPS), RS232, USB 2.0 x 2, USB 3.0 x 2, OPS PC USB x 2, RCA Audio (L/R, link to Component and Composite Video), Media USB (Android)			
Output Connections	RCA Stereo Audio (L/R), 3.5mm Stereo Audio, USB-B for Touchscreen Control		HDMI Out, USB-B x 4 for Touchscreen Control, 3.5mm PC Audio, 3.5mm Headphone, SPDIF, RCA Audio (L/R), RS232	USB-B x 4 for Touchscreen Control, 3.5mm PC Audio, 3.5mm Headphone, SPDIF, RCA Audio (L/R), RS232		
Touch Technology	PC	AP	IR			
Touch Points	10					
Scratch Resistance	7 Mohs					
Glass Strength	2.5mm thick, chemically tre	eated for damage resistance	4mm thick, heat treated			
Speakers	10W x 2					
Mount	Vesa 400 x 400mm M8 screws		Vesa 400 × 600mm M8 screws	Vesa 400 x 700mm M8 screws		
Accessories Included	HDMI cable, USB A-B cable, LightCast Key,** Power cord, Remote, Stylus, Quick Start Guide	VGA cable, USB A-B cable, LightCast Key,** Power cord, Remote, Stylus, Quick Start Guide	HDMI cable, USB cable, USB Wi-Fi Adapter, Power cord, Stylus, Remote, Quick Start Guide	HDMI cable, USB cable, USB Wi-Fi Adapter, Power cord, Stylus, Remote, Quick Start Guide		
Product Weight	110.2lbs / 50kg	117.5lbs / 53.5kg	139lbs / 63kg	184.5lbs / 83.75kg		
Product Dimensions (H × W × D)	38.3 × 59.9 × 3.3in / 972 × 1521 × 83mm	32.3 × 59.9 × 3.3in / 895 × 1520.5 × 83.1mm	41.6 x 68.4 x 4.4 in / 1055.4 x 1736.8 x 111 mm	47.3 x 78.3 x 4.6in / 1201 x 1990 x 116mm		
Shipping Weight	136.7lbs / 62kg	148.4lbs / 67.3kg	177lbs / 80kg	242.5lbs / 110kg		
Shipping Dimensions (H × W × D)	44.9 x 66.4 x 8.4in / 1141 x 1687 x 213mm	44 x 69 x 10.6in / 1128 x 1752 x 270mm	45.7 x 74 x 11 in / 1160 x 1880 x 280 mm	58.7 x 86.6 x 14.2in / 1490 x 2200 x 360 mm		
Warranty	2 Years					

^{*}Product specifications, terms, and offerings are subject to change at any time without notice.

Additional Display Specifications

Refresh Rate: 120 Hz Viewing Angle: 176°

Computer Touch Compatibility (via USB): PC, Mac, Chromebook

Power: AC 100 to 240V, 50/60 Hz

Operating Conditions: 32° to 104° F at 0 to 10K feet / 0° to 40° at 0 to 3,048 m

Noise: <40dBA at 77 F / 25 C

Accessories

Wall Mount for 65-75 Inch Display (INF-WALLMNT2)

Mobile Carts for 65-75 Inch Display (INF-MOBCART, INF-MOBCARTPRO-B, INF-MOBCARTPRO-S)

Wall Mount for 86 Inch Display (INF-WALLMNT3)

Mobile Cart for 86 Inch Display (INF-MCART-PL)

Deluxe Mobile Cart with PTZ Mount and Accessory Shelf (INA-MCARTDX)

Lift Assist Mount for 65-75 Inch Display (INA-MNTBB70) Floor Support for Lift Assist Wall Mount (INA-SUPPORTBB) Mobile Cart for List Assist Mount (INA-CARTBB) VESA Interface Bracket for Lift Assist Mount (INA-VESABB) LiteShow 4 DB+ (INLITESHOW4DB+) SimpleShare (INA-SIMS1) SimpleShare Presentation System (INA-SIMPS1) SimpleShare Touch Presentation System (INA-SIMINT1) Touchscreen Stylus (INA-STYLUS) BigNote Whiteboard Software (INS-BIGNOTE) Oktopus Blend Software (INS-QBUNDLE) Ximbus Software (INS-QXIM1T40-1Y)

Extended Warranties: 65-Inch (EPW-65JT1, EPW-65JT2, EPW-65JT3, EPW-65SV1, EPW-65SV2, EPW-65SV3) / 75-inch (EPW-75JT1, EPW-75JT2, EPW-75JT3) / 86-inch (EPW-86JT1, EPW-86JT2, EPW-86JT3)

 $[\]hbox{**Wireless casting features of LightCast enabled when LightCast Key is inserted into any USB port.}$

