# FUJITSU

## Data Sheet Fujitsu FUTRO S700 Thin Client

### The Affordable Thin Client

The individually configurable Fujitsu FUTRO S700 thin client is ideal for secure server-based computing and desktop virtualization. Silent and easy to use, it also offers straightforward integration and manageability. User convenience is supported through a small footprint, dual monitoring and unique connectivity options. Exceptional quality guarantees a long lifecycle. Combined with low energy consumption, this minimizes your TCO.

### Green technology

Your company's contribution to environmental protection A modern, environmentally conscious product concept - from development to recycling

### Relaxed working

Quiet system for a pleasant working environment

Flash memory and passive cooling concept

### Energy efficiency

Saves energy and reduces CO2 emissions

Integrated system concept with high-level power-saving components

### Manageability

Easy administration while reducing total cost of ownership Outstanding manageability solution

### Backpack solution

- Less space needed
- The FUTRO S700 can be mounted behind the screen





Green II

### Technical details Components

Memory modules	1 GB (1 module(s) 1 GB) DDR3, 1066 MHz, PC3-8500, SO DIMM	
	2 GB (1 module(s) 2 GB) DDR3, 1066 MHz, PC3-8500, SO DIMM	
Graphics	DP to DVI-D (single link) Adapter Cable	
Hard disk drives (internal)	mSATA, 1 GB Flash drive	
	mSATA, 2 GB Flash drive	
	mSATA, 4 GB Flash drive	
	mSATA, 8 GB Flash drive	
Interface add on cards/components (optional)		
· · ·	WLAN module	
	Internal speaker	
	2nd LAN/Power-over-Ethernet module	
Base unit	FUTRO S700	
Operating system and software (Linu	x)	
Operating system	eLux® RL - Embedded Linux	
	eLux® RP – Embedded Linux	
Functions	eLux® RL V3.8.0 or newer	
	Adobe Flash Player 11 for Linux, V11.2.202.236-2 or newer	
	Eterm 97801 terminal emulation, V3.1-1 or newer	
	Mozilla Firefox Browser, V3.6.19.1-1 or newer	
	RDP client, V1.7.1.2-4 or newer	
	ICA client, V12.1.0-9 or newer	
	VMware® View Client, V5.0.1.1-2 or newer (optional) (including support for PCoIP)	
	RDPConnect, V3.0-1 or newer	
	Updates and optional software packages are available at www.myelux.com	
Options available via customizing	Wireless LAN support	
	Remote administration	
	VPN support	
	Firewall support	
Manageability	Scout Enterprise, Flash memory management, Embedded operating system update and system monitoring,	
	Managing devices by location, group or user, Individual operating system composition with ELIAS (only with eLux®	
	RL)	
VPN (Linux)	VPN client (optional)	
Operating system and software (Wind	lows)	
Operating system	Windows® Embedded Standard 7 (WS7E)	
	Windows® Embedded Standard 7 (WS7E multimedia)	
	Windows® Embedded Standard 7 (WS7P)	

Operating system and software (Wine	dows)	
Functions	WS7E: Citrix <sup>®</sup> Receiver V 2.1.45663.0_12202010 or newer	
	WS7E: Citrix® Online Plugin Full V 12.1.0.30_10282010 or newer	
	WS7E: VMware® View Client V 4.6.0-366101 or newer (including support for PCoIP)	
	WS7E: RDP-Client Protocol V 7.1 with RemoteFX or newer	
	WS7E: Internet Explorer 8	
	WS7E: Acrobat Reader V 9.3 or newer	
	WS7E: .NET Framework 2.0 or newer	
	WS7E: Scout Agent for Windows® Embedded Standard 7 (optional)	
	WS7E multimedia: Citrix <sup>®</sup> Receiver Enterprise V 3.3 or newer	
	WS7E multimedia: VMware® View Client V 5.2.0-848202 or newer (including support for PCoIP)	
	WS7E multimedia: RDP-Client Protocol V 7.1 with RemoteFX or newer	
	WS7E multimedia: Internet Explorer 9	
	WS7E multimedia: Acrobat Reader X or newer	
	WS7E multimedia: .NET Framework 4.0 or newer	
	WS7E multimedia: Scout Agent for Windows® Embedded Standard 7	
	WS7E multimedia: WEDM Microsoft Windows Embedded Device Manager	
	WS7P: Language: EN, DE (FR, IT in addition for pre-installation 1) WS7P: Citrix Receiver Enterprise 3.4	
	WS7P: Clark Receiver Enterprise 3.4 WS7P: VMware View Client 5.2.1	
	WS7F: VMWale view Cleric 5.2.1 WS7F: RDP-Client Protocol V 7.1 with RemoteFX	
	WS71: Kor cherk rotocor v 7.1 with Kender X WS7P: Scout Agent for WES 7 (Build 57)	
	WS7P: WEDM Microsoft Windows Embedded Device Manager	
	WS7P: Sumatra PDF Reader 2.1.1	
	WS7P: DotNET Framework 2.0, 3.0, 3.5 (4.0 in addition for pre-installation 1)	
	WS7P: Internet Explorer 9	
	WS7P: Media Player 12	
	WS7P: Premium Multimedia Codecs	
	WS7P: Adobe Flashplayer 11.5	
	WS7P: Security (SmartCard Reader support)	
	WS7P: FBWF File Base Write Filter, EWF Enhanced Write Filter	
Manageability	Scout Enterprise	
VPN (Windows)	VPN through CUZ available	
Mainboard		
Mainboard type	D3003-B	
Formfactor	minilTX	
Processor	AMD G-Series G-T44R (1.2 GHz, )	
Chipset	AMD A55E Controller Hub	
Processor quantity maximum	1	
Memory slots	1 SO DIMM (DDR3, 1066 MHz)	
Supported capacity RAM (max.)	2 GB	
LAN	Built-in 10/100/1000 MBit/s	
BIOS features	BIOS Flash EPROM update by software	
	Recovery BIOS	
	Unified Extensible Firmware Interface (UEFI)	
Audio type	On board	
Audio codec	Realtek ALC262	
Audio features	AC'97 codec	
Interfaces		
Audio: line-in	1	
Audio: line-out	1	
Front audio: headphone	1	
Front audio: line-in / microphone	1	
USB 2.0 total	8	
USB front	2	
USB rear	4	

Interfaces	2	
USB internal	2	
DisplayPort		
	1 DVI-I (integrated VGA can be used with DVI-VGA adapter)	
Serial (RS-232)	1 external	
Mouse / Keyboard (PS/2)	2	
Ethernet (RJ-45)	1	
Kensington Lock support	1	
Graphics		
Graphics brand name	AMD Radeon™ HD 6250	
Graphics color depth	32 bit colors	
Shared video memory	up to 256 MB	
TFT resolution (VGA)	up to 1920 x 1200 pixel	
TFT resolution (DVI)	up to 1920 x 1200 pixel	
TFT resolution (DisplayPort)	up to 2560 x 1600 pixel	
Graphics features	DirectX 11	
	Shader Model 5 Open CL™ 1.1 (depending on CPU)	
	OpenGL 4.1	
Graphics notes	Graphics resolution depending on operating system and management solution.	
Network		
Network	TCP/IP with DNS and DHCP Point-to-Point protocol	
	Supported Citrix Load Balancing over ICA	
	DHCP support for automatic firmware upgrades and unit configuration	
	Multiple master browser support on ICA	
Electrical values		
Rated voltage range	100 V - 240 V (AC Input)	
Rated frequency range	50 Hz - 60 Hz	
Operating voltage range	100 V - 240 V (AC Input)	
Operating line frequency range	50 Hz - 60 Hz	
Power consumption for standard config	uration with Windows Embedded Standard	
Power consumption: Maximum (SO,	19.9 W	
running appl.)		
Power consumption: Idle (S0, running	9.1 W	
OS, Idle mode)		
Power consumption: Minimum (ACPI	0.58 W	
status S5, soft off, WOL enabled)		
Dimensions / Weight / Environmental		
Dimension with stand $(W \times D \times H)$	97 x 191 x 266 mm	
Operating position	Vertical / horizontal	
Weight	1,2 kg	
Weight notes	Actual weight may vary depending on configuration	
Operating ambient temperature	10 - 35 °C	
Operating relative humidity	5 - 85 % (relative humidity)	
Compliance		
Product	FUTRO S700	
Model	TCS-D3003B	
Germany	20	
Europe	CE certification according to EC Directive 2004/108/EEC	
	СВ	

Compliance		
USA/Canada	CSA	
	FCC Class B (depending on wireless configuration)	
	CAN/CSA	
	ICES-003 Class B	
Global	ENERGY STAR® 5.0	
	RoHS (Restriction of hazardous substances)	
	WEEE (Waste electrical and electronic equipment)	
	EPEAT® Silver (dedicated regions)	
Japan	VCCI	
India	WPC	
Russia	GOST	
Compliance notes	Energy Star compliance may vary depending on actual configuration	
Compliance link	http://globalsp.ts.fujitsu.com/sites/certificates/default.aspx	
Security		
Audit proof protection	Write protection for the Flash module	
Warranty		
Standard Warranty	2 years (depending on country)	
Service level	Bring-in Service (for countries within region FTS CEMEA&I, for all other countries depending on local regulations,	
	minimum: 2 years material warranty)	
Warranty Terms & Conditions	http://support.ts.fujitsu.com/warranty	
Maintenance and Support Services	- the perfect extension	
Recommended Service	9x5, Response Time: Next Business Day	
Spare Parts availability	5 years after end of product life	
Service Weblink	http://www.fujitsu.com/fts/services/support	

### **Recommended Accessories**

Midspan Micro Semi PD-9501G	 Midspan Micro Semi PD-9501G is a single port Power over Ethernet solution, specially designed to power IEEE 802.11n and other high power Ethernet end Terminals with 60W. It is fully backward compatible and easy to implement in your existing Ethernet infrastructure.	Order Code: S26361-F1744-L10
Midspan Micro Semi PD-9512G	 Midspan Micro Semi PD-9512G is a Power over Ethernet solution with 12 ports, -72W per port, specially designed to power network devices like cameras, access control systems, Thin Clients and other Ethernet end terminals. It is fully backward compatible and supports IPv4 and IPv6.	Order Code: S26361-F1744-L20
Longshine Switch	The 16-Port 10/100/1000 Mbps Gigabit Longshine switch provides you a real Gigabit connection. Users are able to transfer large files with high bandwidth requirements faster while administrators experience a real efficiency improvement. The fanless Longshine switch is energy efficient, easy to install and fully compliant with all kinds of network protocols.	Order Code: S26391-F6055-L416
Mounting Kit Solution FUTRO S	The Fujitsu Mounting Kit Solution for FUTRO S gives you two options for mounting your thin client behind a display and hiding the system cables out of the way. The solid metal mounting bracket lets you mount directly to a VESA compatible display or via the included subadapter plate with Velcro <sup>™</sup> strap for non-VESA displays.	Order Code: S26361-F2601-L530

Display B22W-6 LED	The B22W-6 LED offers best ergonomics and usability for intensive office Order Code: use with a 4-in-1 stand. S26361-K1375-V140
Display B24W-6 LED	The Fujitsu Display B24W-6 LED combines the best ergonomic and energy saving solutions for intensive office use. The flexible stand with height adjust assures an individual and healthy posture for long-time working sessions. With its impressive screen size it allows working on different documents in parallel or standard CAD applications.
Wireless Mouse Touch WI910	The Fujitsu Wireless Mouse Touch WI910 has a special touch sensitive       Order Code:         surface that recognizes when your hand touches the mouse even       S26381-K465-L100         before you move it. This provides nearly instantaneous wake-up from       the intelligent energy saving sleep mode. Unbeatable responsiveness         combines with features like switchable resolution, and three programmable       buttons for a unique user experience.
Mouse MC200	The Fujitsu Mouse MC200 provides SMB and enterprise the right Order Code: combination of quality features and cost savings. It is appropriate for either S26381-K463-L100 right or left handed users and features two mouse buttons plus a scroll wheel that acts as a third button. It connects with a familiar plug and play USB interface for trouble free installation.
Keyboard KB900	The KB900 is a very flat keyboard with extra low keys and spill-resistant protection. The elegant design and top-quality construction makes the KB900 the ideal input device for any PC or Notebook user. If you accidently spill some water or coffee onto the keyboard, this special construction helps the liquid to flow away.
Wireless Keyboard Set LX900	The Wireless Keyboard LX900 is a top of the line desktop solution for lifestyle orientated customers, who want only the best for their desk. This superb keyboard set with offers ambitious users more functions, security and better features than a conventional interface device. It even includes 2.4 GHz technology and 128 AES encryption for security.

### More information

#### Fujitsu OPTIMIZATION Services

In addition to Fujitsu FUTRO S700, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

#### Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

### **Computing Products**

www.fujitsu.com/global/services/computing/

Software

www.fujitsu.com/software/

#### More information

Learn more about Fujitsu FUTRO S700, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website. www.fujitsu.com/fts/FUTRO

### Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at http://www. fujitsu.com/global/about/environment/



### Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

For further information see www.fujitsu.com/ terms

Copyright © Fujitsu Technology Solutions

### Disclaimer

Technical data are subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

Contact

FUJITSU Technology Solutions Website: www.fujitsu.com/fts 2013-04-05 CE-EN All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their

Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

For further information see www.fujitsu.com/terms Copyright © Fujitsu Technology Solutions