

Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

In some cases, enabling Local Echo may cause character duplication in Tera Term and Putty. Please keep Local Echo set to Disabled or Auto if this issue is encountered,

# 3-Port HDMI Mini Switch with Remote Control - 4K (HDMI F/3xF), 3D, HDCP 1.4, EDID

## MODEL NUMBER: B119-003-UHD-MN









Connect 3 HDMI source devices to a single HDMI monitor and switch back and forth between them.

#### Description

The B119-003-UHD-MN 3-Port Mini HDMI Switch allows you to connect three HDMI source devices to one port on an HDMI monitor and switch back and forth between them. For instance, you can connect your Blu-ray player, video game system and cable/satellite DVR to one HDMI port on your high-definition television. Or you can connect three computers or media centers to a monitor for displaying digital signage or giving presentations.

Switch between source devices using buttons on the unit or the included remote control. The included IR extender receiver lets you hide the unit out of sight while still being able to switch devices up to 16-ft. (4.88 m) away using the remote. When the currently used device is powered off, the unit automatically switches to the next powered-on device.

The B119-003-UHD-MN ensures top-quality audio/video applications with Ultra High Definition (UHD) video resolutions up to 4K @ 30 Hz (3840 x 2160) and 48-bit True Color (16 bits per channel), as well as DTS-HD, Dolby True-HD and 7.1-channel surround sound audio. It's compatible with 3D, HDCP and EDID. Hassle-free functionality requires no software, drivers or external power supply. Sets up in seconds.

### **Features**

Connects 3 HDMI Devices to 1 HDMI DisplaySwitch between source devices via pushbuttons on unit or included remote controlldeal for home audio/video applications, presentations and digital signageIncluded IR extender receiver lets you control devices from a distance using the remoteAutomatically switches to next available device when currently used device is powered off

**Features Top-of-the-Line Audio and Video**Supports Ultra High Definition (UHD) video resolutions up to 4K @ 30 Hz (3840 x 2160)Supports 48-bit True Color (16 bits per channel)Supports DTS-HD, Dolby True-HD and 7.1-channel surround sound audioCompatible with 3D, HDCP 1.4 and EDIDSupports all HDMI 1.4 specifications and capabilities

**Sets Up in Seconds**Plug and play right from the box with no software, drivers or external power supply needed (Note: Most HDMI sources will power switch. In the rare instance where additional power is required, see the manual for adapter specifications)

# **Specifications**

### **Highlights**

- Switch source devices using buttons or included remote control
- Switches to next port when current device is powered off
- Supports UHD video resolutions up to 4K @ 30 Hz as specified by HDMI 1.4
- Supports DTS-HD, Dolby TrueHD and 7.1-channel surround sound
- No software, drivers or external power supply required

### **System Requirements**

HDMI-enabled devices and monitor

### Package Includes

- B119-003-UHD-MN 3-Port Mini HDMI Switch
- · Remote control
- IR extender receiver
- Owner's manual





OVERVIEW		
UPC Code	037332189233	
Technology	HDMI; IR	
VIDEO		
Max Supported Video Resolution	4K @ 30Hz (3840 x 2160)	
Max Supported Color Depth	48-bit Deep Color	
3D Video Supported	Yes	
AUDIO		
Audio Specification	DTS-HD, Dolby TrueHD and 7.1 Channel Surround Sound	
INPUT		
Bus Powered	Yes	
USER INTERFACE, ALERTS & CONTROLS		
LED Indicators	Red (1, 2, 3)	
PHYSICAL		
Color	Black	
Material of Construction	ABS	
Rackmountable	No	
Shipping Dimensions (hwd / cm)	13.46 x 6.86 x 2.54	
Shipping Dimensions (hwd / in.)	5.30 x 2.70 x 1.00	
Shipping Weight (kg)	0.12	
Shipping Weight (lbs.)	0.26	
Unit Dimensions (hwd / in.)	0.7 x 3.2 x 2.3	
Unit Packaging Type	Вох	
Unit Weight (kg)	0.05	
Unit Weight (lbs.)	0.12	
ENVIRONMENTAL		
Operating Temperature Range	32 to 113 °F (0 to 45 °C)	
Storage Temperature Range	14 to 176 °F (-10 to 80 °C)	
BTUs	3.4 BTU/Hr	
Power Consumption (Watts)	1	
Operating Humidity Range	10% to 85 % RH, Non-Condensing	





Storage Humidity Range	5% to 90% RH, Non-Condensing	
Otorage Frankling Range	- Control Cont	
COMMUNICATIONS		
EDID Compatible	Yes	
IR Remote Extension Support	Yes	
Consumer Electronics Control (CEC) Supported	Yes	
CONNECTIONS		
Ports	3	
Side A - Connector 1	(3) HDMI (FEMALE)	
Side B - Connector 1	HDMI (FEMALE)	
FEATURES & SPECIFICATIONS		
Port Selection	Pushbutton	
HDMI Specification	1.4	
HDCP Specification	1.4	
Driver Required	No	
STANDARDS & COMPLIANCE		
Certifications	CE, FCC, RoHS, REACH	
WARRANTY		
Product Warranty Period (Worldwide)	3-year limited warranty	

© 2021 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <a href="https://www.tripplite.com/products/product-certification-agencies">https://www.tripplite.com/products/product-certification-agencies</a>