

Data Sheet

Juniper EX-SFP-10GE-DAC-3M Compatible 3m 10G SFP+ to SFP+ Direct Attach Cable Twinax - 10GbE SFP+ Copper DAC 10 Gbps Low Power Passive Mini GBIC/Transceiver Module DAC

Product ID: EXSFP10GEDA3



The EXSFP10GEDA3 is a Juniper EX-SFP-10GE-DAC-3M compatible direct-attach copper SFP+ cable that's designed, programmed and tested to work with Juniper® brand compatible switches and routers and complies with MSA industry standards.

This passive Twinax copper cable supports 10 Gigabit Ethernet applications connected through SFP+ (Mini-GBIC) ports. This copper SFP+ cable is hot-swappable, making upgrades and replacements seamless by minimizing network disruptions.

Designed for high-speed performance, this low-power, low-latency SFP+ cable is a cost-effective alternative to fiber-optic cable assemblies, supporting short-distance applications such as point-to-point in-rack network switch or server connections.

www.startech.com 1 800 265 1844



StarTech.com SFP Cables

All StarTech.com SFP & SFP+ cables are backed by a lifetime warranty and free lifetime multilingual technical support. StarTech.com offers a wide variety of direct-attach SFP cables and SFP modules, providing the convenience and reliability you need to ensure dependable network performance.

www.startech.com 1 800 265 1844



Data Sheet

Certifications, Reports and Compatibility







Applications

- Use in 10Gb Ethernet network applications
- Point-to-point in-rack and across-rack server or network switch connections

Features

- 100% JUNIPER EX-SFP-10GE-DAC-3M COMPATIBLE DAC: 10G direct attach cable works with Juniper switches and is MSA compliant
- TECHNICAL SPECS: 3m (9.8ft) | 10 Gbps | Passive Twinax (Copper) | 2 x SFP+ Pluggable Connector | 100 Ohm Impedance | 30 AWG Wire Gauge | PVC Cable Jacket | Hot swappable | MSA Compliant
- TESTED FOR OEM HOST COMPATIBILITY: Hot-swappable in Juniper routers and switches
- LIFETIME WARRANTY: Backed by a lifetime warranty on the life of the module itself, not the life of your switch; our modules won't void your OEM warranty and supported by our Tech Advisors 5/24
- WORKS WITH MSA COMPLIANT SWITCHES: Low power 10GbE DAC also works with switch models from Ubiquiti, D-Link, Netgear, Supermicro, TP-Link and more that accept uncoded modules and transceivers

www.startech.com 1 800 265 1844

StarTechcom

Hard-to-find made easy*

Data Sheet

	Warranty	Lifetime
Hardware	Cable Jacket Material	PVC - Polyvinyl Chloride
	Cable Type	Passive Copper Cable
	Compatible Brand	Juniper
Performance	Compatible Networks	10 Gbps
	Maximum Data Transfer Rate	10Gbps
Connector(s)	Connector A	1 - SFP+ Latching Plug
	Connector B	1 - SFP+ Latching Plug
Power	Power Consumption (In Watts)	< 0.5 W (per end)
Environmental	Operating Temperature	0°C to 70°C (32°F to 158°F)
	Storage Temperature	-40°C to 80°C (-40°F to 158°F)
Physical Characteristics	Cable Length	9.8 ft [3 m]
	Color	Black
Packaging Information	Package Height	0.8 in [20 mm]
	Package Height Package Length	0.8 in [20 mm] 9.1 in [23 cm]
	Package Length	9.1 in [23 cm]
	Package Length Package Width	9.1 in [23 cm] 8.1 in [20.7 cm]
Information	Package Length Package Width Shipping (Package) Weight	9.1 in [23 cm] 8.1 in [20.7 cm] 4.9 oz [138 g]
Information	Package Length Package Width Shipping (Package) Weight Included in Package	9.1 in [23 cm] 8.1 in [20.7 cm] 4.9 oz [138 g] 1 - SFP+ cable
Information	Package Length Package Width Shipping (Package) Weight Included in Package Impedance	9.1 in [23 cm] 8.1 in [20.7 cm] 4.9 oz [138 g] 1 - SFP+ cable 100 Ohm
Information	Package Length Package Width Shipping (Package) Weight Included in Package Impedance Product Height	9.1 in [23 cm] 8.1 in [20.7 cm] 4.9 oz [138 g] 1 - SFP+ cable 100 Ohm 0.5 in [1.2 cm]
Information	Package Length Package Width Shipping (Package) Weight Included in Package Impedance Product Height Product Length	9.1 in [23 cm] 8.1 in [20.7 cm] 4.9 oz [138 g] 1 - SFP+ cable 100 Ohm 0.5 in [1.2 cm] 9.8 ft [3 m]

Product appearance and specifications are subject to change without notice.

www.startech.com 1 800 265 1844