

SAFETY DATA SHEET

H.B. Fuller® SC-0672-HF

Version 1.2

Revision Date 02/17/2016

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : H.B. Fuller® SC-0672-HF
Product code : 100000001648

Manufacturer or supplier's details

Company : H.B. Fuller Company
Address : 1200 Willow Lake Boulevard
Vadnais Heights, MN 55110
Telephone : 1-888-423-8553

Medical Emergency Phone Number (24 Hours): 1-888-853-1758

Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300

Recommended use of the chemical and restrictions on use

Recommended use : Solvent based adhesive
Restrictions on use : For industrial use only.

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance	liquid
Color	tan
Odor	solvent

GHS Classification

Flammable liquids : Category 2
Skin irritation : Category 2
Skin sensitization : Category 1
Specific target organ systemic toxicity - single exposure : Category 3 (Central nervous system)
Aspiration hazard : Category 1

GHS Label element

Hazard pictograms :   

Signal Word : Danger

Hazard Statements:

H225 Highly flammable liquid and vapor. H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H336 May cause drowsiness or dizziness.

SAFETY DATA SHEET
H.B. Fuller® SC-0672-HF

Version 1.2

Revision Date 02/17/2016

Precautionary Statements:

Prevention: P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking. P233 Keep container tightly closed. P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment. P242 Use only non-sparking tools. P243 Take precautionary measures against static discharge. P261 Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray. P264 Wash skin thoroughly after handling. P271 Use only outdoors or in a well-ventilated area. P272 Contaminated work clothing should not be allowed out of the workplace. P280 Wear protective gloves/ eye protection/ face protection.

Response: P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/ physician. P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell. P331 Do NOT induce vomiting. P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention. P362 Take off contaminated clothing and wash before reuse. P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage: P403 + P233 Store in a well-ventilated place. Keep container tightly closed. P403 + P235 Store in a well-ventilated place. Keep cool. P405 Store locked up.

Disposal: P501 Dispose of contents/ container to an approved waste disposal plant.

Potential Health Effects
Carcinogenicity:
IARC

Known to be human carcinogen. During normal handling of the product, this substance is encapsulated within the product and will not present a cancer exposure risk.

Quartz (SiO₂) 14808-60-7
 cristobalite 14464-46-1

Group 2B: Possibly carcinogenic to humans. During normal handling of the product, this substance is encapsulated within the product and will not present a cancer exposure risk.

OSHA

titanium dioxide 13463-67-7
 No ingredient of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

NTP

Known to be human carcinogen. During normal handling of the product, this substance is encapsulated within the product and will not present a cancer exposure risk.

Quartz (SiO₂) 14808-60-7
 cristobalite 14464-46-1

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous ingredients

Chemical Name	CAS-No.	Concentration [%]
heptane	142-82-5	10 - 20
Rosin/rosin derivatives	Not Assigned	10 - 20
acetone	67-64-1	5 - 10

SAFETY DATA SHEET
H.B. Fuller® SC-0672-HF

Version 1.2

Revision Date 02/17/2016

kaolin	1332-58-7	5 - 10
Rosin	8050-09-7	1 - 5
Talc Non-Fibrous	14807-96-6	1 - 5
titanium dioxide	13463-67-7	0.1 - 1

SECTION 4. FIRST AID MEASURES

- General advice : Show this material safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.
If symptoms persist, call a physician.
- In case of skin contact : Wash off with soap and water.
Get medical attention if irritation develops and persists.
- In case of eye contact : Flush eyes with water at least 15 minutes. Get medical attention if eye irritation develops or persists.
- If swallowed : Do NOT induce vomiting.
If victim is fully conscious, give a cupful of water.
Never give anything by mouth to an unconscious person.
Obtain medical attention.

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.
- Specific hazards during fire fighting : Cool closed containers exposed to fire with water spray.
- Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Remove all sources of ignition.
Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.
Refer to protective measures listed in sections 7 and 8.
- Environmental precautions : Prevent spreading over a wide area (e.g. by containment or oil barriers).
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material.
Sweep up and shovel into suitable containers for disposal.
Non-sparking tools should be used.

SAFETY DATA SHEET
H.B. Fuller® SC-0672-HF

Version 1.2

Revision Date 02/17/2016

SECTION 7. HANDLING AND STORAGE

- Local/Total ventilation : Use only with adequate ventilation.
- Advice on safe handling : Avoid inhalation of vapor or mist.
 Do not use in areas without adequate ventilation.
 Keep away from fire, sparks and heated surfaces.
 Keep container closed when not in use.
 Take precautionary measures against static discharges.
- Conditions for safe storage : Take measures to prevent the build up of electrostatic charge.
 Use explosion-proof equipment.
 Keep containers tightly closed in a dry, cool and well-ventilated place.
 Keep away from sources of ignition - No smoking.
 Solvent vapors are heavier than air and may spread along floors.
- Materials to avoid : Strong oxidizing agents

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
Ingredients with workplace control parameters

Ingredients	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
-------------	---------	-------------------------------	--	-------

. During normal handling of the product, this substance is encapsulated within the product and will not present a cancer exposure risk.

heptane	142-82-5	TWA	500 ppm 2,000 mg/m ³	OSHA Z-1
		TWA	400 ppm 1,600 mg/m ³	OSHA P0
		STEL	500 ppm 2,000 mg/m ³	OSHA P0
		TWA	400 ppm	ACGIH
		STEL	500 ppm	ACGIH
acetone	67-64-1	TWA	500 ppm	ACGIH
		STEL	750 ppm	ACGIH
		TWA	1,000 ppm 2,400 mg/m ³	OSHA Z-1
		TWA	750 ppm 1,800 mg/m ³	OSHA P0
		STEL	1,000 ppm 2,400 mg/m ³	OSHA P0
kaolin	1332-58-7	TWA (Respirable fraction)	2 mg/m ³	ACGIH

SAFETY DATA SHEET
H.B. Fuller® SC-0672-HF

Version 1.2

Revision Date 02/17/2016

		TWA (total dust)	15 mg/m ³	OSHA Z-1
		TWA (respirable fraction)	5 mg/m ³	OSHA Z-1
		TWA (Total)	10 mg/m ³	OSHA P0
		TWA (Respirable fraction)	5 mg/m ³	OSHA P0
Talc Non-Fibrous	14807-96-6	TWA (Dust)	20 Million particles per cubic foot	OSHA Z-3
		TWA (Respirable fraction)	2 mg/m ³	OSHA P0
		TWA (Respirable fraction)	2 mg/m ³	ACGIH
Quartz (SiO ₂)	14808-60-7	TWA (Respirable fraction)	0.025 mg/m ³	ACGIH
		TWA (total dust)	30 mg/m ³ / %SiO ₂ +2	OSHA Z-3
		TWA (respirable)	10 mg/m ³ / %SiO ₂ +2	OSHA Z-3
		TWA (respirable)	250 mppcf / %SiO ₂ +5	OSHA Z-3
		TWA (Respirable fraction)	0.1 mg/m ³	OSHA P0
titanium dioxide	13463-67-7	TWA	10 mg/m ³	ACGIH
		TWA (total dust)	15 mg/m ³	OSHA Z-1
		TWA (Total)	10 mg/m ³	OSHA P0
cristobalite	14464-46-1	TWA (Respirable fraction)	0.025 mg/m ³	ACGIH
		TWA (Respirable fraction)	0.05 mg/m ³	OSHA P0

Engineering measures : Use local exhaust ventilation or other engineering controls to minimize exposures.

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Filter type : Organic vapor Type

SAFETY DATA SHEET**H.B. Fuller® SC-0672-HF**

Version 1.2

Revision Date 02/17/2016

Hand protection Material	: Nitrile rubber
Eye protection	: Safety glasses with side-shields
Hygiene measures	: Avoid contact with skin, eyes and clothing. Provide adequate ventilation.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: liquid
Color	: tan
Odor	: solvent
Odor Threshold	: No data available
Melting point/freezing point	: not determined
Boiling point/boiling range	: not determined
Flash point	: 0 °F
Evaporation rate	: not determined
Upper explosion limit	: upper flammability limit not determined
Lower explosion limit	: lower flammability limit not determined
Density	: 9.1 - 9.5 lb/gal
Solubility(ies)	
Water solubility	: not determined
Partition coefficient: n- octanol/water	: No data available
Autoignition temperature	: not determined
Viscosity	
Viscosity, kinematic	: not determined
Solid Content, % by weight:	: 71 - 77

SECTION 10. STABILITY AND REACTIVITY

Chemical stability	: The product is chemically stable.
Possibility of hazardous reactions	: Hazardous polymerization does not occur.
Conditions to avoid	: Heat, flames and sparks.
Hazardous decomposition products	: Stable under normal conditions.

SECTION 11. TOXICOLOGICAL INFORMATION

SAFETY DATA SHEET**H.B. Fuller® SC-0672-HF**

Version 1.2

Revision Date 02/17/2016

Acute toxicity**Product:**Acute oral toxicity : Acute toxicity estimate : > 5,000 mg/kg
Method: Calculation methodAcute dermal toxicity : Acute toxicity estimate : > 5,000 mg/kg
Method: Calculation method**Ingredients:****heptane:**

Acute oral toxicity : LD50 Oral mouse: 5,000 mg/kg

Acute dermal toxicity : LD50 Dermal rabbit: 3,000 mg/kg

Skin corrosion/irritation

No data available

Serious eye damage/eye irritation

No data available

Respiratory or skin sensitization

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

STOT-single exposure

No data available

STOT-repeated exposure

No data available

Aspiration toxicity

No data available

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity****Ingredients:****heptane :**

SAFETY DATA SHEET**H.B. Fuller® SC-0672-HF**

Version 1.2

Revision Date 02/17/2016

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 10 mg/l
Exposure time: 24 h
Test Method: static test

Rosin :

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 3.8 - 5.4 mg/l
Exposure time: 48 h
Test Method: static test

Persistence and degradability

No data available

Bioaccumulative potential**Mobility in soil**

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

Waste from residues : This product meets the definition of hazardous waste under the U.S. EPA Hazardous Waste Regulations 40 CFR 261. It is ignitable waste class D001. Disposal via incineration is recommended. Consult your state, local, or provincial authorities for more restrictive requirements.
The hazard and precautionary statements displayed on the label also apply to any residues left in the container.

SECTION 14. TRANSPORT INFORMATION**Special precautions for user**

Not applicable

Domestic regulation**49 CFR**

UN/ID/NA number : 1133
Proper shipping name : Adhesives
Class : 3
Packing group : II
Labels : 3
ERG Code : 128
Marine pollutant : no

International Regulation

SAFETY DATA SHEET**H.B. Fuller® SC-0672-HF**

Version 1.2

Revision Date 02/17/2016

IATA-DGR

UN/ID No. : 1133
Proper shipping name : Adhesives
Class : 3
Packing group : II
Labels : 3
Packing instruction (cargo aircraft) : 364
Packing instruction (passenger aircraft) : 353

IMDG-Code

UN number : 1133
Proper shipping name : ADHESIVES
Class : 3
Packing group : II
Labels : 3
EmS Code : F-E, S-D
Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

SECTION 15. REGULATORY INFORMATION

SARA 311/312 Hazards : Fire Hazard
Acute Health Hazard

SARA 302 : SARA 302: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 : SARA 313: This product does not contain any chemical components that exceed the reporting threshold.

Clean Air Act

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 12 (40 CFR 61).

US State Regulations

California Prop 65 WARNING! This product contains a chemical known in the State of California to cause cancer.

titanium dioxide	13463-67-7
Quartz (SiO ₂)	14808-60-7

SAFETY DATA SHEET
H.B. Fuller® SC-0672-HF

Version 1.2

Revision Date 02/17/2016

cristobalite

14464-46-1


The ingredients of this product are reported in the following inventories:

TSCA	On TSCA Inventory
DSL	All components of this product are on the Canadian DSL.
REACH	Not in compliance with the inventory
AICS	Not in compliance with the inventory
NZIoC	Not in compliance with the inventory
ENCS	Not in compliance with the inventory
KECI	Not in compliance with the inventory
PICCS	Not in compliance with the inventory
IECSC	Not in compliance with the inventory
TWINV	Not in compliance with the inventory

Inventories Legend TSCA (USA), DSL (Canada), REACH(Europe), AICS (Australia), NZIoC (New Zealand), ENCS (Japan), KECI (Korea), PICCS (Philippines), IECSC (China), TWINV (Taiwan)

SECTION 16. OTHER INFORMATION

Prepared by: Global Regulatory Department - phone: 1-651-236-5842 - email: msds.request@hbfuller.com

Further information
NFPA:

HMIS III:

HEALTH	2
FLAMMABILITY	3
PHYSICAL HAZARD	0

0 = not significant, 1 = Slight,
 2 = Moderate, 3 = High
 4 = Extreme, * = Chronic

The information and recommendations set forth herein are believed to be accurate. Because some of the information is derived from information provided to the H.B. Fuller Company from its suppliers, and because the H.B. Fuller Company has no control over the conditions of handling and use, the H.B. Fuller Company makes no warranty, expressed or implied, regarding the accuracy of the data or the results to be obtained from the use thereof. The information is supplied solely for your information and consideration, and the H.B. Fuller Company assumes no responsibility for use or reliance thereon. It is the responsibility of the user of H.B. Fuller Company products to comply with all applicable federal, state and local laws and regulations.

SAFETY DATA SHEET**H.B. Fuller® SC-0672-HF**

Version 1.2

Revision Date 02/17/2016
