

# Helping Agencies Overcome IT Challenges

ClearCube Technology is an American tech leader in centralized computing and desktop virtualization specializing in the development of secure VDI endpoints, Blade PCs, and workstations to help many of the world's largest organizations and government agencies embrace their digital transformation.

### **Contact Us**

ID Technologies POC AFWay Sales

AFWay@idtec.com

800-658-8520 **Option 1** for Sales

Option 2 for Customer Support

ClearCube Technology

sales@clearcube.com

866-652-3500





# **Dual Fiber Zero Client**Model CD7522

Secure, Full Desktop Experience & High Performance Video on Dual Monitors Over Fiber Network



#### **KEY FEATURES**

#### Chipset

Teradici TERA2321 PCoIP®

#### I/O Physical

DisplayPort × 1
Single-link DVI-I × 1
USB 2.0 × 6
3.5mm Headphone jack × 1
3.5mm Microphone jack × 1
Power Button × 1
Power Jack × 1

#### Display/Resolution

Single: 4K @ 30FPS Dual: 1920x1200 @ 60FPS

#### **Power Cord**

North America (Included) EU or UK (Optional)

#### **SPECIFICATIONS**

#### Network

LAN: SFP 100/1000Base-X × 1

#### Security

No OS, No local storage, No data sent over network In-session AES-256-GCM
Suite B security level, TLS 1.2 support
Kensington security slot for use with Kensington locks
Full control of USB device authorization may be disabled IPv6 support
802.1x network authentication

#### **Physical Characteristics**

Enclosure: Metal
Dimensions: 1.2 (H) × 6.5 (W) × 5 (D) in
Gross Weight: 1lb (500gr)

#### **Max Consumption**

6 Watts









#### **ORDERING INFORMATION**

#### **Part Description**

CD7522M Dual Fiber Zero Client

#### **Part Description**

Fiber SFP Module 100Base FX

#### **Part Description**

Fiber SFP Module 1000Base SX

**Part Number** 

G09007522

**Part Number** 

G0900249

#### **Part Number**

G0900138



REAR VIEW

Visit for More Information: clearcube.com/2021-ccs-2-qeb





# **Dual Fiber Zero Client**Model CD9522



Full Desktop Experience & High Performance Video on Dual Monitors Over Copper Network

#### **KEY FEATURES**

#### Chipset

Teradici TERA2321 PCoIP®

#### I/O Physical

DisplayPort × 1
Single-link DVI-I × 1
USB 2.0 × 6
3.5mm Headphone jack × 1
3.5mm Microphone jack × 1
Power Button × 1
Power Jack × 1

#### Display/Resolution

Single: 4K @ 30FPS Dual: 1920 x1200 @ 60FPS

#### **Power Cord**

North America (Included) EU or UK (Optional)

#### **SPECIFICATIONS**

#### Network

LAN: RJ45 10/100/1000 Base-T Gigabit Ethernet × 1

#### **Security**

No OS, No local storage, No data sent over network In-session AES-256-GCM
Suite B security level, TLS 1.2 support
Kensington security slot for use with Kensington locks
Full control of USB device authorization may be disabled IPv6 support
802.1x network authentication

#### **Physical Characteristics**

Enclosure: Metal

Dimensions: 1.2 (H)  $\times$  6.5 (W)  $\times$  5 (D) in

Gross Weight: 1lb (500gr)

#### **Max Consumption**

6 Watts









#### ORDERING INFORMATION

Part Description

CD9522M Dual Copper Zero Client

**Part Number** 

G0900452



**REAR VIEW** 

Visit for More Information: clearcube.com/2021-ccs-2-qeb

#### **CONTACT US**

ClearCube Sales | | sales@clearcube.com | AFWay Sales | | AFWay@idtec.com |





## **Dual Fiber Zero Client**Model CD9552

Feature-Rich, High Performance, Robust Quad Zero Client for Centralized and Virtualized Computing



#### **KEY FEATURES**

#### Chipset

Teradici TERA2140 PCoIP®

#### I/O Physical

DisplayPort × 4
USB 2.0 × 4
3.5mm Headphone Jack × 1
3.5mm Microphone Jack × 1
3.5mm Speaker Jack × 1
Power Button × 1
Power lack × 1

#### Display/Resolution

Single: 4K @ 30FPS

Dual: 4K @ 15FPS

Quad: 1920 x1200 @ 60FPS

#### **Power Cord**

North America (Included) EU or UK (Optional)

#### **SPECIFICATIONS**

#### Network

LAN: RJ45 10/100/1000 Base-T Gigabit Ethernet × 1

#### Security

No OS, no local storage, no data sent over network In-session AES-256-GCM Suite B security level, TLS 1.2 support Kensington security slot for use with Kensington locks Full control of USB device authorization may be disabled IPv6 support 802.1x network authentication

#### **Physical Characteristics**

Enclosure: Plastic

Dimensions: 7.21 (H) × 1.76 (W) × 5.22 (D) in

Gross Weight: 2lb (1000gr)

#### **Max Consumption**

12 Watts

#### **ORDERING INFORMATION**

#### **Part Description**

CD9552 Quad DP Copper Zero Client


#### **Part Number**

G0900328





**m**Ware READY





**REAR VIEW** 

Visit for More Information: clearcube.com/2021-ccs-2-qeb





### **Accessories & Add-Ons**

Increase Your Endpoint Capabilities with ClearCube Add-Ons & Accessories



#### **OPTIONS & ORDERING INFORMATION**

Part Description	Part Number
Fiber SFP Module 100Base FX	G0900249
Fiber SFP Module 1000Base SX	G0900138
Fiber Duplex Cable 1m - LC Male to SC Male cable OM1 62.5/125M	G0600234
Fiber Duplex Cable 1m - LC Male to SC Male OM4 50/125M	G0600261
Fiber Duplex Cable 1m - LC Male to MT-RJ Male OM3 50/125M	G0600262
Fiber Duplex Cable 1m - LC Male to ST Male OM4 50/125M	G0600263
Fiber Duplex Cable 1m - LC Male to ST Male OM2 50/125M	G0600264
European Universal Power Cord (EU)	G0600002
British Power Cord (UK)	G0600029

### SPECIFICATIONS FOR EVERY IT PROBLEM THERE IS A CLEARCUBE SOLUTION

#### ClearCube offers a wide selection of:

- PCoIP Zero Client options with 30 models (14 Copper and 16 Fiber)
- Multiple Security Level (MSL) KVM/KM Solutions
- Blade PCs & Workstations
- Copper & Fiber NUC Mini PCs
- · Copper & Fiber Thin Clients
- TEMPEST Solutions
- Custom Design & Engineer solutions.
   If you can't find the hardware solution you need for your deployment, don't worry: we'll build it for you!

Visit for More Information: clearcube.com/2021-ccs-2-qeb