

FS750 Series

Fast Ethernet WebSmart Edge Switches

The Allied Telesis FS750 Series of WebSmart network switches demonstrates the Allied Telesis commitment to environmentally-friendly processes and products, minimizing power consumption through the use of a high efficiency power supply and a low power chipset. Featuring PoE+, FS750 Series switches at the network edge are the ideal cost-effective solution for small businesses..



Ease of management and high performance

These advanced Allied Telesis WebSmart switches combine the simplicity of unmanaged switches with the performance and reliability of managed switches. This provides a cost-effective, secure and reliable solution for integrated management at the network edge. With user-friendly web-based management, the FS750 Series is ideal for integrating simple management and security into your network solution.

Power over Ethernet (PoE)

The FS750/28PS has 24 ports of 10/100TX, all PoE capable. The first four ports of the switch are PoE+ capable, up to 30W. The total PoE power budget is 193W across all 24 ports.

PoE allows users to connect and power a device using a single Ethernet cable, thus eliminating the need for additional power outlets and simplifying installation. Furthermore, this system is unaffected by any local variance in AC power, offering a standardized power infrastructure.

Exceptional value

Affordable management functionality at the network edge is a reality. Allied Telesis WebSmart switches help network managers get the most value for their dollar, with industry standard protocols, fiber media support via SFPs, and simple Plug and Play usability—right out of the box.

New Features

VLAN

- ▶ IEEE 802.1Q tagged
- ▶ Port-based
- ▶ Up to 256 groups

Quality of Service Classification

- ▶ IEEE 802.1p tagging
- ▶ Port-based priority
- ▶ Four priority queues per port

IP Multicast Support (IPv4)

- ▶ IGMP snooping (v1/v2)
- ▶ Static multicast group (up to 256)
- ▶ Spanning-Tree, IEEE 802.1d/w/s

IEEE 802.1x Port-based, MAC-based and Network Access Control

- ▶ Local authentication server (MD5 only)
- ▶ Remote authentication through RADIUS
- ▶ Dynamic VLAN assignment
- ▶ RADIUS Client

Other

- ▶ IEEE 802.3x flow control or HOL* blocking prevention (* when flow control is off)
- ▶ Port mirroring
- ▶ Destination MAC filtering
- ▶ Ingress/egress rate limiting
- ▶ Broadcast storming control
- ▶ 100/1000 SFP supported
- ▶ Jumbo Frames - up to 10K

Management Features

- ▶ Web-based configuration
- ▶ Discovery support
- ▶ SNMP trap view
- ▶ LLDP
- ▶ Firmware upgrade by FTP and HTTP
- ▶ Configuration backup/restore by FTP and HTTP
- ▶ Factory reset
- ▶ Password access control and restricted IP access list
- ▶ SNMPv1/v2c/v3
- ▶ Management IP: DHCP client for Web
- ▶ Management and static IP setting
- ▶ Syslog support
- ▶ System time configuration (SNTP, manual)

MIBs

- ▶ RFC 1213 MIB-II
- ▶ RFC 1643 Ethernet MIB
- ▶ RFC 1493 Bridge MIB
- ▶ RFC 2131 DHCP client
- ▶ Private Enterprise MIB (Allied Telesis provides the spec)

RMON Groups (1, 2, 3, 9)

- ▶ Stats
- ▶ History
- ▶ Alarms
- ▶ Events

ACL

- ▶ 200 entries (shared)

Specifications

| PRODUCT | SWITCHING CAPACITY | FORWARDING RATE | FAN | MAX POWER CONSUMPTION | OPERATING TEMPERATURE | WEIGHT | SIZE WIDTH X DEPTH X HEIGHT |
|---------------|--------------------|-----------------|---------|-----------------------|--------------------------------|-------------------|---|
| AT-FS750/20 | 11.2Gbps | 8.3Mpps | Fanless | 7.6W | 0°C to 40°C (32°F to 104°F) | 2.2 kg (4.85 lb) | 330 mm × 180 mm ×44 mm (13 in x 7.08 in x 1.73 in) |
| AT-FS750/28 | 12.8Gbps | 9.5Mpps | Fanless | 8.7W | 0°C to 40°C (32°F to 104°F) | 2.2 kg (4.85 lb) | 330 mm × 180 mm ×44 mm (13 in x 7.08 in x 1.73 in) |
| AT-FS750/28PS | 12.8Gbps | 9.5Mpps | Fan | 241W | 0°C to 40°C (32°F to 104°F) | 5.0 kg (11.00 lb) | 440 mm × 210 mm ×44 mm (17.3 in x 8.26 in x 1.73 in) |
| AT-FS750/52 | 17.6Gbps | 13.1Mpps | Fanless | 13.25W | 0°C to 40°C (32°F to 104°F) | 3.0 kg (6.61 lb) | 440 mm × 250 mm ×44 mm (17.3 in x 9.8 in x 1.73 in) |

Power characteristics

| PRODUCT | MAX POE POWER | MAX POE ENABLED PORTS | MAX POE+ ENABLED PPORTS | MAX POWER CONSUMPTION | | VOLTAGE | FREQUENCY |
|---------------|---------------|-----------------------|-------------------------|-----------------------|--------|-------------|-----------|
| | | | | POE OFF | POE ON | | |
| AT-FS750/20 | - | - | - | 7.6W | - | 100-240V AC | 50-60Hz |
| AT-FS750/28 | - | - | - | 8.7W | - | 100-240V AC | 50-60Hz |
| AT-FS750/28PS | 193W | 24 | 4 (port1-4) | 18W | 241W | 100-240V AC | 50-60Hz |
| AT-FS750/52 | - | - | - | 13.25W | - | 100-240V AC | 50-60Hz |

Performance

14,880pps for 10Mbps Ethernet
 148,800pps for 100Mbps Ethernet
 1,488,000pps for 1000Mbps Ethernet
 MAC addresses
 FS750/20, 28, 28PS: 8K
 FS750/52: 16K
 VLAN IDs available 4,000
 Max VLANs 256
 Packet buffer 4.1 Mbit
 DRAM 128MB
 Flash 16MB

Interface connections

10/100TX
 10/100/1000T RJ-45
 SFP 100FX, 1000T, 1000SX or 1000LX

Technical specifications

Wall-mount or desktop
 All units come with wall /19 in rack-mount brackets

Environmental specifications

Operating temperature: 0°C to 40°C (32°F to 104°F)
 Non-operating temperature: -25°C to 70°C (-13°F to 158°F)
 Operating humidity: 5% to 90% non-condensing
 Storage humidity: 5% to 95% non-condensing
 Vibration: IEC 68-2-36
 Shock: IEC 68-2-29
 Drop: IEC 68-2-32
 Flammability: UL94V-0

Environmental compliance

RoHS
 Eu-RoHS
 China RoHS
 WEEE

Electrical/mechanical approvals

UL60950-1 2nd edition (UL)
 FCC/EN55022/CISPR 22 Class A
 VCCI Class A
 C-Tick
 EN60950 (TUV)
 EN55024
 CE Mark
 CSA / cUL

Standards and compliance

IEEE 802.3 CSMA/CD IEEE 802.3i 10T
 IEEE 802.3u 100TX
 IEEE 802.3z 1000SX/LX
 IEEE 802.3z/ab 1000T
 IEEE 802.3x Flow control
 IEEE 802.1p Prioritization (four queues)
 IEEE 802.1x Authentication
 IEEE 802.1x Local authentication server(MD5)
 IEEE 802.1x Remote authentication through RADIUS
 IEEE 802.1x Dynamic VLAN assignment
 IEEE 802.1x MAC-based authentication
 IEEE 802.1x RADIUS
 IEEE 802.1d Bridging
 IEEE 802.3ad Link aggregation
 IEEE 802.3ad Port trunking and LACP
 IEEE 802.1Q Tagged VLAN
 IEEE 802.1d Spanning-Tree
 IEEE 802.1w Rapid Spanning-Tree
 IEEE 802.1s Multiple Spanning-Tree
 IEEE 802.3af PoE
 IEEE 802.3at PoE+
 IEEE 802.3az Energy Efficient Ethernet



Ordering information

AT-FS750/20-xx
16-port 10/100TX + 2 10/100/1000T + 2 SFP/1000T Combo Ports

AT-FS750/28-xx
24-port 10/100TX + 2 10/100/1000T + 2 SFP/1000T Combo Ports

AT-FS750/28PS-xx
24-port 10/100TX + 2 10/100/1000T + 2 1000T/SFP combo ports and PoE

AT-FS750/52-xx
48-port 10/100TX + 2 10/100/1000T + 2 SFP/1000T Combo Ports

Where xx = 10 for US power cord
20 for no power cord
30 for UK power cord
40 for Australian power cord
50 for European power cord

Package contents

Switch unit
Rack-mount brackets and screws
Power cord
Rubber feet
User manual/install guide on CD (GS950/8POE only)

Small Form Pluggable Optics Modules

AT-SPSX
SFP, MMF, 1000Mbps, 550 m, 850 nm, LC

AT-SPSX/1
SFP, MMF, 1000Mbps, 550 m, 850 nm, LC, industrial temperature

AT-SPLX10
SFP, SMF, 1000Mbps, 10 km, 1310 nm, LC

AT-SPFX/2
SFP, MMF, 100Mbps, 2 km, 1310 nm, LC

AT-SPFX/15
SFP, SMF, 100Mbps, 15 km, 1310 nm, LC

AT-SPBD10-13
SFP, SMF, 1000Mbps, 10 km, 1310/1490 nm, LC-BiDi

AT-SPBD10-14
SFP, SMF, 1000Mbps, 10 km, 1490/1310 nm, LC-BiDi