


# BELKIN®

# PR03 Series

## PR03 Series Launch Binder

The most cost effective  
way to manage PS/2  
& USB based server  
installations.





## Corporate background

Belkin is one of the world's leading manufacturers of peripherals and connectivity solutions for computer and consumer electronics users. The company's product ranges include:

- USB 1.0 and USB 2.0 hubs, PCI cards and devices
- FireWire hubs and PCI cards
- LAN and wireless peripheral sharing devices and cables
- Networking hardware and accessories
- Bluetooth adapters
- Gaming devices
- Power protection products, including UPS and surge protectors
- KVM (Keyboard, Video and Mouse) switches
- Mobile phone and PDA accessories
- PC, Mac and notebook accessories
- Computer and audio-visual cables

## Company history

Founded in 1982 by three employees in a residential garage, Belkin now employs more than 1200 people in offices throughout North America, Europe and Australia. During its 20 years of existence, Belkin has enjoyed continuous growth. For the financial year ending 2004 its gross sales exceeded USD 530 million worldwide, with European sales of over USD 85 million.

Belkin's headquarters in Compton, California established its first European operations in the UK in 1996, now located in Rushden, England. Since then, the company has experienced rapid growth and has established its European sales and marketing headquarters in Amsterdam, the Netherlands with additional sales and marketing offices in Germany, Spain, Italy, France, Scandinavia, Russia and Eastern Europe.

## Product development

Belkin invests heavily in research and development. During the past three years, it has expanded its engineering expertise to further strengthen its capabilities in USB and peripheral-sharing product lines. Belkin's New York-based engineering team works closely with the Industrial Design Group, a dedicated product design team based in Hollywood, to create the innovative yet functional products that continue to set Belkin apart from its competitors.

## Sales and distribution

Belkin's products are sold through distributors, mail order, retailers and OEM accounts. The company operates an end-to-end reseller support programme, as well as specific in-store training for retailers. Belkin is also the industry leader in business-to-business e-commerce integration, having consistently been at the forefront of the movement toward online integration with our resellers.

In recognition of its success in this area, Belkin has won a record number of awards from 1998 to 2005 at RetailVision, the leading IT retail channel event organised by Gartner. These have included Best European Vendor, Best Retail Strategy and Best Merchandising. Belkin has established a number of strategic partnerships with distributors and retailers throughout Europe and continues to follow an aggressive recruitment strategy. In addition, Belkin has relationships with distributors worldwide.

## Customer support

Belkin provides complete pre-sales and post-sales support for its customers across all product lines through a comprehensive, multilingual technical support service. In addition, all product packaging and supporting documentation is provided in the language of all countries in which its products are sold, a strategy which has been key to the company's success in the European market.

## Quality

Belkin's state-of-the-art 20,000 m2 European Headquarters and Distribution Centre enforces the strictest of quality standards in the industry. Belkin operate an advanced management system in compliance with BS EN ISO 9001:2000, conducting daily evaluations and quality control, ensuring the highest level of operation and service from product design and manufacture, to customer delivery and after-sales service.

# Contents

Introduction/Contents .....	2-3
Product Bulletin .....	4-5
4Port PRO3 KVMs .....	6
8-Port PRO3 KVMs .....	6
16-Port PRO3 KVMs .....	7
PRO2 Vs PRO3 .....	7
KVM Products Overview .....	8
KVM Cables & Accessories Overview .....	9
Compatibility .....	10
1U Rack Console .....	11



## PRO3 Series

---

The new PRO3 Series KVM Switch from Belkin delivers reliability, performance, advanced features, and centralized control necessary for today's SMB environment. Offering both PS2 and USB support, this KVM switch enables a System Administrator to control multiple platform CPUs from a single console. With our proprietary advanced video technology, the PRO3 delivers resolutions of up to 1920x1440@75Hz, designed to preserve image integrity.

## Control up to 256 computers with one keyboard, Monitor, and Mouse.

The new PRO3 Series KVM Switch from Belkin delivers reliability, performance, advanced features, and centralized control necessary for today's SMB environment. Offering both PS2 and USB support, this KVM switch enables a System Administrator to control multiple platform CPUs from a single PS/2 or USB console. With our proprietary advanced video technology, the PRO3 delivers resolutions of up to 1920x1440@75Hz, designed to preserve image integrity.

The new PRO3 KVM Switches from Belkin are designed with the advanced features necessary for managing SMB server environments. A built-in flash feature allows you to download firmware updates, ensuring compatibility with the latest servers and devices. Through a simple RJ11 interface, downloads are quick, easy, and reduce your server downtime. An elegant Multi-lingual user interface with active port LEDs and front panel push buttons allows for easy manual switching. A seven-segment display is used to indicate bank number when units are daisy-chained together. An enhanced On-Screen-Display (OSD) allows administrators to name and select computers, for fast and easy port identification and selection from your keyboard. Other features include: OSD Security and user access list per port; designated daisy-chain ports; fast hot key switching with 9 hot-key options; user-defined auto scan; native rack-mount enclosure; Backwards compatible with existing PRO2, SMB CAT5 and KVM-over-IP Series; and Belkin Three-Year Warranty.

Features	Benefits
<b>OSD Security and user access list (per port)</b>	Prevents unauthorized access to KVM switch and servers with multilevel security.
<b>Reduces wiring clutter</b>	Uses Dual-port Micro-cabling KVM Cables
<b>OSD Hotkey configuration</b>	Enables instantaneous selection of desired ports and servers with 9 user-definable hot keys.
<b>Dedicated Daisy chain ports</b>	Easily expands your KVM configuration by daisy chaining up to 16 KVM switches together
<b>Backwards compatible</b>	Offers compatibility with OmniView PRO2, SMB CAT5 and KVM-over-IP switches, so you can leverage your existing investment in Belkin KVM Products.



**F1DA104Zea**



**F1DA106Zea**



**F1DA116Zea**

### Features

- 4-, 8-, or 16-port models available
- Supports PS/2 and USB platforms
- Flash Upgradeable
- 1920x1440@75Hz video resolution
- Elegant User Interface with direct-access port selector buttons
- Hot key switching
- User-defined auto scan
- Multi-lingual On-Screen Display (8 languages)
- Natively rack mountable and stackable
- Uses Micro-cabling KVM cables
- PS/2 keyboard and mouse emulations

# Product Bulletin


## Specifications

Model No.	F1DA104Zea, F1DA108Zea, F1DA116Zea
<b>Enclosure:</b>	Metal enclosure with high-impact plastic faceplate
<b>Power:</b>	12V DC, 1A AC switching power adapter
<b>Daisy-Chain:</b>	Maximum of 16 OmniView KVM switches
<b>No. of Servers Supported:</b>	4, 8, 16 respectively for 4-port, 8-port and 16-port models— (256 servers max. via daisy-chaining)
<b>Monitors Supported:</b>	CRT and LCD (with VGA support)
<b>Resolution Support:</b>	Up to 1920x1440@75Hz
<b>Keyboard input:</b>	PS/2 (miniDIN6) & USB (Type A) with 101-/102-/104-key keyboards
<b>Mouse input:</b>	PS/2 (miniDIN6) & USB (Type A) having 2, 3, 4, or 5 buttons
<b>Monitor Port:</b>	HDDB15 female (VGA)
<b>CPU Ports:</b>	SCSI-50
<b>Daisy-Chain Ports:</b>	DB25 female
<b>Flash-Upgrade Port:</b>	RJ11
<b>Direct Port Selectors:</b>	4, 8, 16 respectively for 4-port, 8-port, and 16-port models
<b>Operating Temp:</b>	32° to 104° F (0~40° C)
<b>Storage Temp:</b>	-4° to 140° F (-20~60° C)
<b>Humidity:</b>	0-80% RH, non-condensing
<b>Dimensions:</b>	(F1DA104Zea) 11 x 1.75 x 6 in. (279mm x 44.5mm x 150mm) (F1DA108Zea) 17.25 x 1.75 x 7.5 in. (438mm x 44.5mm x 190mm) (F1DA116Zea) 17.25 x 3.5 x 7.5 in. (438mm x 89mm x 190mm)
<b>Weight:</b>	(F1DA104Zea) 5.3 lbs. (2.4kg.) (F1DA108Zea) 9.2 lbs. (4.2kg.) (F1DA116Zea) 12.0 lbs. (5.5kg.)
<b>Warranty:</b>	
<b>3 years</b>	

## Package Contents

- OmniView PRO3 KVM Switch
- Adjustable Rack-Mount Brackets with Screws (8- and 16-port models)
- 12V DC, 1A Power Adapter
- DB9-to-RJ11 Serial Flash-Upgrade Cable
- User Manual
- Quick Installation Guide.

Note: Specifications are subject to change without notice.



1. LED indicators
2. Dedicated port selectors
3. Console ports USB, PS/2 and VGA
4. Dedicated daisy-chain ports
5. Bank select DIP switch
6. Flash-upgrade port and DIP select switch
7. Server connections using micro cabling
8. DC power jack
9. Desktop or rack installation
10. Autoscan button



## 4-port PRO3 KVM

F1DA104Zea



- Multi-platform – PS/2 & USB
- On Screen Display (available in 8 languages)
- Video resolution support up to 1920x1440@75Hz
- Dedicated daisy-chain ports



Expected Launch Date	Expected in Stock Date
10th August 2007	7th August 2007

Prices	
Euro Pricing:	
Street (ex Vat)	€188.11
Street (inc Vat)	€224.99
GBP Pricing:	
Street (ex Vat)	£127.65
Street (inc Vat)	£149.99

Regional Part numbers	
UK	F1DA104Zea
Euro	F1DA104Zea

## 8-port PRO3 KVM

F1DA108Zea



- Multi-platform – PS/2 & USB
- On Screen Display (available in 8 languages)
- Rack-mountable with included brackets
- Port switching through OSD, direct-access port selectors and hot-keys



Expected Launch Date	Expected in Stock Date
10th August 2007	7th August 2007

Prices	
Euro Pricing:	
Street (ex Vat)	€334.44
Street (inc Vat)	€399.99
GBP Pricing:	
Street (ex Vat)	£229.78
Street (inc Vat)	£269.99

Regional Part numbers	
UK	F1DA108Zea
Euro	F1DA108Zea

# 16-Port PRO3 KVMs and PRO2 Vs Pro3

## 16-port PRO3 KVM

F1DA116Zea



- Multi-platform – PS/2 & USB
- On Screen Display (available in 8 languages)
- Backwards compatibility with existing PRO2, SMB CAT5 and KVM-over-IP Series
- Three-year Warranty



Expected Launch Date	Expected in Stock Date
10th August 2007	7th August 2007

Prices	
Euro Pricing:	
Street (ex Vat)	€526.74
Street (inc Vat)	€629.99
GBP Pricing:	
Street (ex Vat)	£357.44
Street (inc Vat)	£419.99

Regional Part numbers	
UK	F1DA116Zea
Euro	F1DA116Zea

## PRO2 Vs PRO3

Feature	PRO2	PRO3	Additional Information - PRO3
OSD	Yes	Yes	Superior On Screen Display
Password Protected	No	Yes	Admin & user accounts
User Accounts	No	Yes	Create up to 8 individual user accounts
User Access List	No	Yes	User Access Restriction Per Port
Multi Lingual OSD	No	Yes	English, French, German, Italian, Spanish & Russian
Hotkeys	Yes (1 option)	Yes	Offers choice of 9 hot key combinations
Autoscan	Yes	Yes	User definable
Console Input	PS/2	PS/2 & USB	Offers support for USB and PS/2 input devices
Server Support	PS/2 & USB	PS/2 & USB	
Flash Upgradeable	Yes	Yes	
Daisy-Chainable	Yes	Yes	Up to 16 levels (max 256 servers)
Form Factor	1 U (4 & 8) 2U (16)	1u (4, 8 & 16)	16 Port now just 1u
Resolution (Max)	2046x1538@85Hz	1920x1440@75Hz	
Backwards Compatible	Yes	Yes	Compatible with PRO2, SMB CAT5 and KVM-over-IP
Rack brackets included	Yes	Yes	
Micro Cable Support	No	Yes	Each port serves two servers (Q-B Cables)
Warranty	5 years	3 years	

## BELKIN® SMB KVM Solutions

For more information  
please visit  
[www.belkin.co.uk/KVM](http://www.belkin.co.uk/KVM)

Part No	Description	Input	Output	No. of ports	No. of Consoles	Audio Support	Flash Upgradable	Multi Login Support	Built in Security	Resolution	Cables Included	Hot Key Switching	Simultaneous Users	Daisy-Chain Port	Maximum KVM in Daisy Chain	Max. PCs Connected	On-Screen Display	Warranty
<b>PROFESSIONAL SERIES</b>																		
<b>PRO2 PS/2 Series</b>																		
F1DA104Pea	4-Port KVM with OSD	PS/2	PS/2	4	1	No	Yes	No	No	2048x1536@60/50/50Hz	No	Yes	1	Yes	4	16	Yes	3 Years
F1DA108Pea	8-Port KVM with OSD	PS/2	PS/2	8	1	No	Yes	No	No	2048x1536@60/50/50Hz	No	Yes	1	Yes	16	128	Yes	3 Years
F1DA116Pea	16-Port KVM with OSD	PS/2	PS/2	16	1	No	Yes	No	No	2048x1536@60/50/50Hz	No	Yes	1	Yes	16	256	Yes	3 Years
<b>PRO3 Series</b>																		
F1DA104Zea	4-Port KVM with OSD	PS/2 & USB	PS/2 & USB	4	1	No	Yes	Yes	Yes	1920x1440@75Hz	No	Yes	1	Yes	4	16	Yes	2 Years
F1DA108Zea	8-Port KVM with OSD	PS/2 & USB	PS/2 & USB	8	1	No	Yes	Yes	Yes	1920x1440@75Hz	No	Yes	1	Yes	16	128	Yes	2 Years
F1DA116Zea	16-Port KVM with OSD	PS/2 & USB	PS/2 & USB	16	1	No	Yes	Yes	Yes	1920x1440@75Hz	No	Yes	1	Yes	16	256	Yes	2 Years
<b>SMB CAT5 Series</b>																		
F1DP104Aea	4-Port CAT5 KVM	PS/2	PS/2, USB & SUN™	4	1	No	Yes	No	Yes	1600x1200@75Hz	No	Yes	1	Yes	4	16	Yes	5 Years
F1DP108Aea	8-Port CAT5 KVM	PS/2	PS/2, USB & SUN™	8	1	No	Yes	No	Yes	1600x1200@75Hz	No	Yes	1	Yes	16	128	Yes	5 Years
F1DP116Aea	16-Port CAT5 KVM	PS/2	PS/2, USB & SUN™	16	1	No	Yes	No	Yes	1600x1200@75Hz	No	Yes	1	Yes	16	256	Yes	5 Years
<b>SMB KVM-over-IP</b>																		
F1DP108Gea	OmniView SMB 1x8 KVM-over-IP Switch	PS/2	PS/2, USB & SUN™	8	1 local, 1 remote	No	Yes	No	Yes	1600x1200@75Hz	No	Yes	1	Yes	16	128	Yes	2 Years
F1DP116Gea	OmniView SMB 1x16 KVM-over-IP Switch	PS/2	PS/2, USB & SUN™	16	1 local, 1 remote	No	Yes	No	Yes	1600x1200@75Hz	No	Yes	1	Yes	16	256	Yes	2 Years
<b>Quad-Bus Series</b>																		
F1DE108Gea	8-Port KVM with IntelliView OSD	PS/2 & USB	PS/2 & USB	8	1 (expand to 4)	No	Yes	Yes	Yes	2048x1536@60/50/50Hz	No	Yes	Up to 4	Yes	16	128	Yes	5 Years
F1DE116Gea	16-Port KVM with IntelliView OSD	PS/2 & USB	PS/2 & USB	16	1 (expand to 4)	No	Yes	Yes	Yes	2048x1536@60/50/50Hz	No	Yes	Up to 4	Yes	16	256	Yes	5 Years
F1DE008Cea	8-Port Expander	N/A	PS/2 & USB	8	0	No	Yes	N/A	Yes	2048x1536@60/50/50Hz	No	N/A	N/A	Yes	16	128	N/A	5 Years
F1DE016Cea	16-Port Expander	N/A	PS/2 & USB	16	0	No	Yes	N/A	Yes	2048x1536@60/50/50Hz	No	N/A	N/A	Yes	16	256	N/A	5 Years
F1DE208Cea	2x8-Port Matrix KVM with IntelliView OSD	PS/2 & USB	PS/2 & USB	8	2 (expand to 4)	No	Yes	Yes	Yes	2048x1536@60/50/50Hz	No	Yes	Up to 4	Yes	16	128	Yes	5 Years
F1DE216Cea	2x16-Port Matrix KVM with IntelliView OSD	PS/2 & USB	PS/2 & USB	16	2 (expand to 4)	No	Yes	Yes	Yes	2048x1536@60/50/50Hz	No	Yes	Up to 4	Yes	16	256	Yes	5 Years
<b>Secure KVM</b>																		
F1DM102Uea	OmniView® Secure 2-Port KVM Switch	USB	USB	2	1	No	No	No	No	1920x1440@75Hz	No	No	1	No	N/A	2	No	3 Years
F1DM104Uea	OmniView® Secure 4-Port KVM Switch	USB	USB	4	1	No	No	No	No	1920x1440@75Hz	No	No	1	No	N/A	4	No	3 Years
F1DM108Uea	OmniView® Secure 8-Port KVM Switch	USB	USB	8	1	No	No	No	No	1920x1440@75Hz	No	No	1	No	N/A	8	No	3 Years
<b>Remote IP Manager</b>																		
F1DE101Hea	Remote IP Manager	PS/2	PS/2	1	1 Local, 1 Remote	No	Yes	Yes	Yes	2048x1536@60/50/50Hz	Yes	N/A	1 Loc, 1 Rem.	N/A	N/A	N/A	N/A	2 Years
<b>SMB Remote IP Device</b>																		
F1DP101Mea	SMB Remote IP Device	PS/2	PS/2	1	1 Local, 1 Remote	No	Yes	Yes	Yes	2048x1536@60/50/50Hz	Yes	N/A	1 Loc, 1 Rem.	N/A	N/A	N/A	N/A	2 Years
<b>ExpandView CAT5</b>																		
F1DW108Aea	8-port Broadcaster	VGA	CAT5 UTP	8	N/A	No	No	N/A	N/A	1600x1200@75Hz	VGA	N/A	1	Yes	1	512	N/A	3 Years
F1DW008Aea	8-port Line splitter	CAT5 UTP	CAT5 UTP	8	N/A	No	No	N/A	N/A	1600x1200@75Hz	VGA	N/A	1	No	64	512	N/A	3 Years
F1DW101Aea	Dual Input Remote Module	CAT5 UTP	VGA	N/A	N/A	No	No	N/A	N/A	1600x1200@75Hz	VGA	N/A	1	No	N/A	512	N/A	3 Years
F1DW102Aea	Dual output Remote Module	CAT5 UTP	VGA	N/A	N/A	No	No	N/A	N/A	1600x1200@75Hz	VGA	N/A	1	No	N/A	512	N/A	3 Years



F1DE208Cea



F1DP108Aea



F1DA108Zea



F1DA108Pea



# KVM Cables & Accessories Overview

# BELKIN®

## KVM Cables and Accessories

For more information  
please visit  
[www.belkin.co.uk/KVM](http://www.belkin.co.uk/KVM)

Part.No	Description	Length (Feet)	Length (Metres)	Packaging type
<b>PROFESSIONAL SERIES</b>				
<b>PRO2 PS/2 Series Cables</b>				
F3X1105006	PS/2 & VGA bonded cable	6 ft	1.8 m	Bag & label
F3X1105010	PS/2 & VGA bonded cable	10 ft	3.0 m	Bag & label
F3X1105015	PS/2 & VGA bonded cable	15 ft	4.5 m	Bag & label
F3X1105025	PS/2 & VGA bonded cable	25 ft	7.5 m	Bag & label
F1D108-CBL	Daisy-Chain cable DB25 M/M	2 ft	0.5 m	Bag & label
<b>PRO3 Cables</b>				
F1D9400-06	Dual Port PS/2 & VGA bonded cable	6 ft	1.8 m	Bag & label
F1D9400-10	Dual Port PS/2 & VGA bonded cable	10 ft	3.0 m	Bag & label
F1D9400-15	Dual Port PS/2 & VGA bonded cable	15 ft	4.5 m	Bag & label
F1D9400-25	Dual Port PS/2 & VGA bonded cable	25 ft	7.5 m	Bag & label
F1D9401-06	Dual Port USB & VGA bonded cable	6 ft	1.8 m	Bag & label
F1D9401-12	Dual Port USB & VGA bonded cable	12 ft	3.5 m	Bag & label
F1D108-CBL	Daisy-Chain cable DB25 M/M	2 ft	0.5 m	Bag & label
<b>SMB SERIES</b>				
<b>SMB CAT5 Series SIMs &amp; SMB KVM-over-IP</b>				
F1DP101AeaAP	PS/2 Server Interface Module	100 ft*	30 m*	Retail box
F1DP101AeaAP-8P	PS/2 Server Interface Module - 8 pack	100 ft*	30 m*	Retail box
F1DP101AeaAU	USB Server Interface Module	100 ft*	30 m*	Retail box
F1DP101AeaAL	SUN Server Interface Module (Legacy System)	100 ft*	30 m*	Retail box
F1D108-CBL	Daisy-Chain cable DB25 M/M	2 ft	0.5 m	Bag & label
* 6 ft CAT5 Cable included. Extendable up to 100 ft.				
<b>Quad-Bus Series Cables</b>				
F1D9400-06	Dual Port PS/2 & VGA bonded cable	6 ft	1.8 m	Bag & label
F1D9400-10	Dual Port PS/2 & VGA bonded cable	10 ft	3.0 m	Bag & label
F1D9400-15	Dual Port PS/2 & VGA bonded cable	15 ft	4.5 m	Bag & label
F1D9400-25	Dual Port PS/2 & VGA bonded cable	25 ft	7.5 m	Bag & label
F1D9401-06	Dual Port USB & VGA bonded cable	6 ft	1.8 m	Bag & label
F1D9401-12	Dual Port USB & VGA bonded cable	12 ft	3.5 m	Bag & label
F1D9402-02	Daisy-Chain cable SCSI M/M	2 ft	0.5 m	Bag & label
F1D9402-06	Daisy-Chain cable SCSI M/M	6 ft	1.8 m	Bag & label
F1D9402-10	Daisy-Chain cable SCSI M/M	10 ft	3.0 m	Bag & label
F1D9402-15	Daisy-Chain cable SCSI M/M	15 ft	4.5 m	Bag & label
F1D9402-20	Daisy-Chain cable SCSI M/M	20 ft	6.0 m	Bag & label
F1D9402-25	Daisy-Chain cable SCSI M/M	25 ft	7.5 m	Bag & label
<b>Secure KVM</b>				
F3X1962006	USB & VGA bonded cable	6 ft	1.8 m	Bag & label
F3X1962010	USB & VGA bonded cable	10 ft	3 m	Bag & label
<b>ACCESSORIES</b>				
F1DC100Ruk	17" Rack Console - 1u integrated keyboard, mouse & monitor	-	-	White box
F1D084vea2	CAT5 Extender - remote and local access	500 ft	150 m	Retail box
F1DC101Suik	17" Single Rail Rack Console - 1U	-	-	White box
F1DE083uk	SUN adapter - MiniDin8/13W3 & SUN USB	N/A	N/A	Retail box
F1DV104uk	4-Port VGA video splitter	N/A	N/A	Retail box
F1DV108uk	8-Port VGA video splitter	N/A	N/A	Retail box

### SECURE KVM SERIES



F1DN104Uea

### EXPANDVIEW CAT5



### SMB 1U RACK-MOUNT CONSOLE



F1DC100Ruk


### ACCESSORIES



F1DE083uk

F1D084vea2

### QUAD-BUS TECHNOLOGY



## SMB CAT5 Series

The SMB CAT5 KVM has all the features of the best selling PRO2 Series, and with CAT5 built-in it significantly reduces wiring clutter and simplifies deployment. By using standard CAT5 Cables and intelligent Server Interface Modules the SMB CAT5 KVM switch improves server stability and uptime.



## PRO2 Series

The PRO2 Series KVM Switches deliver the reliable performance and centralized control required for managing medium-to-large server environments.

The PRO2 Series offers administrators control of up to 256 mixed platform computers from a single console.



## PRO2 PS/2 Series

Based on the best selling PRO2, the PRO2 PS/S has been designed to offer the most cost effective solution for managing PS/2 based servers. With PS/2 based connectivity, the PRO2 PS/2 perfectly caters for over 70% of the server market, at a price that fits any budget.




## KVM-over-IP

The OmniView SMB KVM-over-IP Switch provides enterprise-class remote server management at a small business price. The Switch enables network administrators to monitor and control their servers from anywhere, at anytime. This round-the-clock remote access lets you troubleshoot servers faster and more efficiently, dramatically reducing server downtime and service costs




**Good**



**Standard KVM Cabling**

**Better**



**Micro-Cabling**

# 1U Rack Console



## 1U Rack Console with 17" TFT Monitor

The Belkin 1U rack console fits a standard, 19-inch rack configuration and its special rack-mount bracket design allows the Console to slide beyond mounted KVM switches and servers, ensuring clearance for the full extension of the LCD and keyboard.

The Console features a dual-rail system, allowing the LCD panel to remain displayed—without the keyboard—even with the server rack door closed. A key-locking mechanism prevents unwanted access to the Console and connected servers.

Designed to work seamlessly with any PS/2 platform KVM Switch, the Console offers two power on/off methods: an LCD power-save (with drawer closure); and an LCD panel button. The LCD panel features front-panel controls and on-screen display for easy adjustment.

A colour display delivers 1024x768@65Hz resolution through a protected, tempered-glass overlay. The Console includes an integrated, 105-key PS/2 keyboard including numeric, 10-key pad with centrally located PS/2 touch pad.

Prices								
	Euro Pricing:				GBP Pricing:			
	F1DC100Ruk	F1DC100Rfr	F1DC100Rde	F1DC100Rsp	F1DC100Ruk	F1DC100Rfr	F1DC100Rde	F1DC100Rsp
<b>Street</b> (ex Vat)	€1,230	€1,230	€1,230	€1,230	£850.00	£850.00	£850.00	£850.00
<b>Street</b> (inc Vat)	€1,469	€1,469	€1,469	€1,469	£999.00	£999.00	£999.00	£999.00

For more information on this product please see Rack Console Launch Binder.

# **BELKIN®**

[www.belkin.com](http://www.belkin.com)

Belkin Ltd.  
Express Business Park  
Shipton Way, Rushden  
NN10 6GL, United Kingdom  
+44 (0) 1933 35 2000  
+44 (0) 1933 31 2000 fax

Belkin GmbH  
Hanebergstrasse 2  
80637 Munich  
Germany  
+49 (0) 89 143405 0  
+49 (0) 89 143405 100 fax

Belkin Nordic  
Polhemsgatan 20B  
112 36 Stockholm  
Sweden  
+46 (0) 8 510 630 00  
+46 (0) 8 567 911 68 fax

Belkin B.V.  
Boeing Avenue 333  
1119 PH Schiphol-Rijk  
Netherlands  
+31 (0) 20 654 7300  
+31 (0) 20 654 7349 fax

Belkin SAS  
130 rue de Silly  
92100 Boulogne-Billancourt  
France  
+33 (0) 1 41 03 14 40  
+33 (0) 1 41 31 01 72 fax

Belkin Iberia  
C/ Anabel Segura, 10 planta baja, oficina 2,  
Arroyo de la Vega, 28108, Alcobendas  
Spain  
+34 91 791 23 00  
+34 91 490 23 35 Fax