For Residential and Commercial Applications

Job Name	Engineer / Architect	
Job Location	Wholesaler	
Submittal Date	Contractor	

B0-**IM & B1**IM Speedi Plumb® PLUS Braided Icemaker, Humidifier, & Water Filter Connector

Use: For use in potable water distribution systems in accessible locations only.

Design Features:

- Engineered polymer braided fibers bend freely without kinking or crimping
- Reinforced PVC inner hose provides added durability
- Rubber washers provide a large pliable sealing surface and ensure a long lasting water-tight connection



Operating Specifications:

Temperature: 40°-160° F, intermittent to 180° F

Pressure: 125 PSI maximum


Tubing Diameter: 0.245" ID (0.470" OD)

CONNECTOR MATERIAL SPECIFICATIONS			
Inner Hose	Reinforced PVC		
Braiding	PVC coated yarn		
Barb	Brass		
Ferrule	Stainless steel		
Washer	Rubber		
Compression Nut	Brass, plated		

Part Listing:

B0-12IM F	1/4" compression x 1/4" compression x 12" length, flag labeled
B0-60IM F	1/4" compression x 1/4" compression x 60" length, flag labeled
B0-60IM P	1/4" compression x 1/4" compression x 60" length, bagged
B0-72IM F	1/4" compression x 1/4" compression x 72" length, flag labeled
B0-72IM P	1/4" compression x 1/4" compression x 72" length, bagged
B0-84IM P	1/4" compression x 1/4" compression x 84" length, bagged
B0-96IM P	1/4" compression x 1/4" compression x 96" length, bagged
B0-120IM B	1/4" compression x 1/4" compression x 120" length, bulk
B0-120IM P	1/4" compression x 1/4" compression x 120" length, bagged

B0-**IM & B1**IM Speedi Plumb® PLUS Braided Icemaker, Humidifier, & Water Filter Connector



PART DIMENSIONS (Inches)			
Model	DIM. A		
B0-12IM	12.0 / 13.0		
B0-60IM	60.0 / 61.0		
B0-72IM	72.0 / 73.0		

PART DIMENSIONS (Inches)			
Model	DIM. A		
B0-84IM	84.0 / 85.0		
B0-96IM	96.0 / 97.0		
B0-120IM	120.0 / 121.0		

Listings & Certifications:

- IAPMO listed to ASME A112.18.6 / CSA B125.6
- IAPMO listed to NSF/ANSI 372 for Low-Lead Compliance
- IAPMO listed to NSF/ANSI/CAN 61



