



NovoDS4K



NovoDS



NovoDSmini

Model	DS300	DS200	DS100
Display Resolutions	3840 x 2160 (16:9, 4K-UltraHD at 30 fps); 1920 x 1080 (16:9, 1080p at 60 fps); 1280 x 720 (16:9, 720p at 60 fps)	3840 x 2160 (16:9, 4K-UltraHD at 30 fps); 1920 x 1080 (16:9, 1080p at 60 fps); 1280 x 720 (16:9, 720p at 60 fps)	1920 x 1080 (16:9, 1080p at 60 fps); 1280 x 720 (16:9, 720p at 60 fps)
Output Orientation	Portrait, Landscape	Portrait, Landscape	Portrait, Landscape
Media Formats Supported	Images: JPEG, PNG, GIF, BMP Video: MP2, MP4, H.264, VC-1 (WMV) Audio: MP3, WMA, AAC	Images: JPEG, PNG, GIF, BMP Video: MP2, MP4, H.264, VC-1 (WMV) Audio: MP3, WMA, AAC	Images: JPEG, PNG, GIF, BMP Video: MP2, MP4, H.264, VC-1 (WMV) Audio: MP3, WMA, AAC
NovoDS Studio Software Operating System Requirement	Windows 7 and above, Mac 10.7 and above	Windows 7 and above, Mac 10.7 and above	Windows 7 and above, Mac 10.7 and above
Input / Output Ports	HDMI Output; HDMI Input; Audio Output Jack; Audio Input Jack; USB 2.0 Type A (x 2); microSD Card Slot; RJ45 with PoE; RS232 Jack; DC Power Jack	HDMI Output; USB 2.0 Type A; microSD Card Slot; RJ45; DC Power Jack	HDMI Output; Audio Output Jack; USB 2.0 Type A; microSD Card Slot; RJ45; DC Power Jack
Storage	Internal: 8 GB (5.1 GB available for users) External: microSD Card Slot (Up to 32GB), USB Flash Drive	Internal: 8 GB (5.1 GB available for users) External: microSD Card Slot (Up to 32GB), USB Flash Drive	Internal: 8 GB (5.1 GB available for users) External: microSD Card Slot (Up to 32GB), USB Flash Drive
CPU	ARM Cortex A9 Quad-Core at 1.6 GHz	ARM Cortex A9 Quad-Core at 1.6 GHz	ARM Cortex A9 Quad-Core at 1.6 GHz
Network Connectivity	WiFi: 802.11 AC (2.4 GHz & 5 GHz) Ethernet: 10/100Mbps	WiFi: 802.11 AC (2.4 GHz & 5 GHz) Ethernet: 10/100Mbps	Ethernet: 10/100Mbps
LED	Green: System Power On Red: System in Standby Blue: Network Activity	Green: System Power On Red: System in Standby Blue: Network Activity	Red: System in Standby Blue: System Power On
Button	Reset Button	Reset Button	Reset Button
Security	Kensington® Security Slot	Kensington® Security Slot	Kensington® Security Slot
Power Supply	100 - 240V AC, 50/60 Hz, DC output: 5V@2A. Power over Ethernet (IEEE 802.3af)	100 - 240V AC, 50/60 Hz, DC output: 5V@2A.	100 - 240V AC, 50/60 Hz, DC output: 5V@2A.
Power Consumption	< 10W	< 10W	< 10W
Weight	253 g	128 g	178 g
Dimensions (L x W x H)	152 x 113 x 22.5 mm	120 x 75 x 16 mm	100 x 100 x 20 mm

**Your information
exactly where you need it**