Key Features

Crisp and Clear | Rich Colour from Every Angle | Enjoy The Lifelike Imagery of 10-Bit Colour | Industrial Colour Standard | Seamless viewing with narrow bezel



Product **Description**

The ViewSonic® VG2719-2K is a 27" WQHD full ergonomic monitor with rich and accurate colour performance for graphic design, for office work and for home entertainment. Featuring a WQHD resolution panel (2560 x 1440) and SuperClear® IPS-Type technology, content is displayed in refined detail from virtually any viewing angle. WQHD resolution displays more content on the screen than FHD resolution, reduces scrolling and boosts productivity. The 10-bit colour depth, which produces 1.07 billion colours, and the 99% sRGB colour coverage ensures vivid colour reproduction for web content editing, graphic design or photo editing. VG2719-2K's ergonomic design offers a wide range of tilt, swivel, pivot, and height adjustments, while narrow bezel gives the monitor a clean aesthetic and is convenient for setting up multiple monitors side-by-side to improve workflow management. In addition, with optional ViewSplit software, users can divide, organize, and customize the screen layout for better workflow efficiency.

Visit Us www.viewsonic.com

LCD PANEL POWER

Monitor Size: 27"W (27" Viewable) 3-pin plug (CEE22) x Power:

Panel Technology: IPS Type TFT LCD

AC 100-240V Voltage: Resolution: WQHD 2560 x 1440 (Universal); 50/60Hz

596.74mm (H) x Consumption: 33W Display Area: 335.66mm (V)

27W Optimize: Aspect Ratio: 16:9

Conserve: 21W Brightness: 300 cd/m2 (Typ)

Contrast Ratio: 1000:1 (Typ) Tilt: 22 ~ -5 degrees

Dynamic Contrast Ratio: 50,000,000:1 Swivel: 320°

178 degrees / 178 Viewing Angle: Rotation: 90° degrees (Typ)

Height Adjustment: 110 mm Response Time: GTG: 5ms (Typ)

WALL MOUNT 1.07 Billion colors

Colours: (10 bits) VESA®: 100mm x 100mm

> Adobe RGB: 79.15% **OPERATING CONDITIONS** Panel Coverage 32°F to 104°F (0°C NTSC: 71.66% Panel Temperature (º F / º C):

ERGONOMICS

to 40°C) Coverage sRGB: 99% Panel 20% to 90% (no

Coverage Humidity: Colour Gamut: condensation) REC 709: 99% Panel

> Coverage **DIMENSIONS (W X H X D) (MM)** SMPTE C: 100% 620 mm (W) x 534 Panel Coverage Physical with stand (mm): mm (H) x 245 mm EBU: 99% Panel

(D) Coverage 620 mm (W) x 362

0.2331mm (H) x Physical without stand (mm): Pixel Pitch: mm (H) x 44 mm (D) 0.2331mm (V)

190 mm (W) x 444 **INPUT SIGNAL** mm (H) x 725 mm Packaging (mm):

 $Fh = 15 \sim 120KHz$; (D) Frequency: $Fv = 24 \sim 75Hz$

WEIGHT Sync: TMDS / PCI-E Net with stand (kg): 6.91kg

COMPATIBILITY Net without stand (kg): 5.96kg PC: Windows 10 certified

Gross (kg): 8.6kg Mac®: Power Mac tested

REGULATIONS CONNECTOR CE EMC, CB, RoHS Green BOM & RoHS DoC, ErP, HDMI 1.3 x 2

REACH SVHC List & DoC, EEL, WEEE, EAC, Digital: DisplayPort 1.2 x 1 UkrSEPRO, EnergyStar

Analog: N/A

PACKAGE CONTENTS LCD Display Earphone out x 1

(3.5mm plug) Power Cable (1.5m) HDMI Cable (1.5m) Audio in x1 (3.5mm Audio Cable (1.5m) Audio In: plug)

Audio Out:

SPEAKERS *Actual content may differ from market to market

Quick Start Guide

3W x 2