

Product data sheet

Specifications



Easy Rack PDU, Metered Outlet, 0U, 3 Phase, 22kW, 230V, 32A, 18 C13 and 6 C19 outlets, IEC60309 3P + N + PE inlet

EPDU1232SMBO

Overview

Lead time Usually in Stock

Main

Main Input Voltage 400 V 3 phases

Main Output Voltage 230 V

Input Connection Type IEC 60309 32 A 3P + N + PE

Number of rack unit 0U

Cable length 3 m

Number of cables 1

Communication port protocol SNMP

Provided equipment
Installation guide
Rack mounting brackets
Safety guide

Physical

Colour Black

Height 1800 mm

Width 55 mm

Depth 56 mm

Net weight 8.68 kg

Mounting location Side

Mounting preference No preference

Mounting mode Not rack-mountable

USB compatible No

Mounting position Vertical

Input

[In] rated current 32 A

Max line current 32 A

Input current limits 32 A

Load capacity 22000 VA

Network frequency	50/60 Hz
Plug standard	IEC 60309

Output

Number of power socket outlets	18 IEC 60320 C13 10 A 6 IEC 60320 C19 16 A
--------------------------------	---

Conformance

Product certifications	CE EAC RCM TÜV UKCA
------------------------	---------------------------------

Environmental

Ambient air temperature for operation	-5...45 °C
Relative humidity	5...95 %
Operating altitude	0...3000 m
Ambient air temperature for storage	-25...65 °C
Storage Relative Humidity	5...95 %
Storage altitude	0...15000 m

Batteries & Runtime

Communication network type	10/100BASE-T
----------------------------	--------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2030 mm
Package 1 Width	195 mm
Package 1 Length	130 mm
Package 1 Weight	9.85 kg

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
RoHS exemption information	Yes
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

Recommended replacement(s)