

Philips Signage Solutions Q-Line Display

55"

Direct LED Backlight Ultra HD

**Signage**Solutions

55BDL3010Q

# Stand out

Easy-setup 18/7 display.

Inform and enthrall with a Philips Q-Line Professional 4K Ultra HD Display. This reliable solution can be up and running as quickly as you need-with no additional hardware.

# **Brilliant picture. Reliable performance**

• Ultra-HD. Rich images. Stunning contrast

# Effortless setup. Total control.

• Operate, monitor and maintain with CMND & Control

### **Cost-effective system solution**

- Energy-saving automatic backlight control
- Integrated media player. Easily schedule USB content
- Simple control. Remotely manage networked displays
- FailOver ensures content is always playing



# Highlights

### **CMND & Control**



Run your display network over a local (LAN) connection. CMND & Control allows you to perform vital functions like controlling inputs and monitoring display status. Whether you're in charge of one screen or 100.

## Integrated media player

Easily schedule content to play from USB. Your Philips Professional Display will wake from standby to play the content you want, and then return to standby once playback is done.

### **FailOver**



From waiting room to meeting room, never show a blank screen. FailOver lets your Philips

Professional Display switch automatically between primary and secondary inputs ensuring content keeps playing even if the primary source goes down. Simply set a list of alternate inputs to be sure your business is always on.











# **Specifications**

## Picture/Display

- Diagonal screen size: 54.6 inch / 138.7 cm
- Panel resolution: 3840 x 2160
- Optimum resolution: 3840 x 2160 @ 60 Hz
- Brightness: 350 cd/m<sup>2</sup>
- Contrast ratio (typical): 4000:1
- Dynamic contrast ratio: 500,000:1
- Response time (typical): 8 ms
- Aspect ratio: 16:9
- Viewing angle (H / V): 178 / 178 degree
  Pixel pitch: 0.315 x 0.315 mm
- Display colors: 1.07 Billion

#### **Supported Display Resolution**

Computer formats

Resolution	Refresh rate
1920 x 1080	60Hz
1600 x 1200	60Hz
$1440 \times 900$	60Hz
1280 x 1024	60Hz
$1280 \times 720$	60Hz
$1280 \times 800$	60Hz
$1024 \times 768$	60, 70, 75Hz
$720 \times 400$	70Hz
$640 \times 480$	60, 67, 72, 75Hz
1152 x 870	75Hz
1680 x 1050	60Hz
$800 \times 600$	56, 60, 72, 75Hz

• Video formats

Resolution	Refresh rate
3840 x 2160	60Hz
3840 x 2160	30Hz
1080i	60Hz
1080 <sub>P</sub>	60Hz
720p	60Hz
480i	60Hz
480p	60Hz
1080i	50Hz
576i	50Hz
576p	50Hz

# Connectivity

- Video input: DVI-I x 1, HDMI (x4), USB, VGA (via DVI)
- · Audio input: 3.5 mm jack
- Audio output: Audio Left/Right (RCA)
- External control: RJ45, RS232C (in/out) 2.5 mm jack, IR (in/out) 3.5 mm jack

#### Convenience

- Energy saving functions: Smart Power
- Tiled Matrix: Up to 15 x 15
- Start-up: Switch on delay, Switch on status, Boot
- Start-up window: enable / disable Philips logo
- · Keyboard control: Lockable, Hidden
- Network controllable: RS232, RJ45
- · Signal Loop Through: RS232, IR Loopthrough

#### **Dimensions**

- Bezel width: 12.9 (TLR) / 14.7 (B) mm
- Set dimensions (W x H x D): 1239.2 x 711.6 x 61.71 mm
- Set dimensions in inch (W x H x D):  $48.79 \times 28.02 \times 2.43$  inch
- VESA Mount: 400 x 400 mm/200 x 200 mm, M6
- Product weight: 15.82 kg
- Product weight (lb): 34.88 lb

# **Operating conditions**

- Temperature range (operation):  $5 \sim 40 \, ^{\circ}\text{C}$
- Temperature range (storage): -20  $\sim$  60  $^{\circ}$ C
- MTBF: 50,000 hour(s)
- Humidity range (operation)[RH]:  $20 \sim 80\%$  RH (No condensation)
- Humidity range (storage) [RH]: 5 ~ 95% RH (No condensation)
- Altitude: 0 ~ 3000 m

#### **Power**

- Consumption (On mode): 125 W
- Mains power: 100 ~ 240 VAC
- Standby power consumption: <0.5 W
- comsumption(Max): 180 W
- Consumption (Typical): 140 W

• Built-in speakers: 2 x 10W RMS

# **Multimedia Applications**

- USB Playback Video: MPEG, H.264, JPEG
- USB Playback Picture: JPEG, BMP, PNG
- USB Playback Audio: AAC, HEAAC, MPEG, WMA

#### Accessories

• Included accessories: AC Power Cord, RS232 cable, Remote Control, Batteries for remote control, Quick start guide

sensor cable (1.8 m), RS232 daisy-chain cable Stand: Table stand (BM02542, BM05922)

• Included Accessories: USB Cover and screw x1, IR

#### **Miscellaneous**

- Warranty: 3 year warranty
- On-Screen Display Languages: English, French, German, Italian, Polish, Turkish, Russian, Simplified Chinese, Spanish, Traditional Chinese
- Regulatory approvals: CE, CB, FCC, Class B



Issue date 2020-01-21

 $\hfill \odot$  2020 Koninklijke Philips N.V. All Rights reserved.

Version: 2.0.1

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. or their respective owners.

12 NC: 8670 001 56788 EAN: 87 12581 75410 5

www.philips.com