



GL679 – ESD Nitrile Textured Powder-Free Glove

Features and Benefits

- Resistivity: 10^{10} ohms/sq
- Textured for Better Wet/Dry Grip
- Contains No Latex
- Designed for Industrial Use
- Individually Tested
- Tear Resistant



Product Specifications

Measurements and Tolerance:	Overall Length	250 +/- 10mm
	Width by Size	XS 80 +/- 5mm
		S 85 +/- 5mm
		M 95 +/- 5mm
		L 105 +/- 5mm
XL 115 +/- 5mm		
Thickness:	Finger	0.14 +/- 0.01mm
	Palm	0.13 +/- 0.01mm
	Cuff	0.12 +/- 0.01mm
Physical Properties: (before aging)	Tensile Strength	(Min) 14 Mpa
	Elongation @ Break (%)	(Min) 500%
Physical Properties: (after aging 100° C 22 hrs)	Tensile Strength	(Min) 12 Mpa
	Elongation @ Break (%)	(Min) 400%
Electrical Properties:	Resistivity	10^{10} ohms/sq

Sizes Available

Small	Medium	Large	X-Large	
GL679-S	GL679-M	GL679-L	GL679-XL	

5228 US HWY 421 N · WILMINGTON, NC 28401
 800-537-0351 · 910-763-8111 (tel) · 800-379-9903 · 910-763-5664 (fax)
 sales@allspec.com (email) · www.allspec.com (web)