

# PNOTEPROC6

APC Notebook Surge Protector for AC, phone and network lines, 3 pin connection, 100-240V



## Overview

Lead time	Usually in Stock
-----------	------------------

## Physical

Color	Silver
Maximum Depth	4.33 in (11 cm)
Maximum Height	1.10 in (2.8 cm)
Net Weight	0.22 lb(US) (0.1 kg)
Maximum Width	1.26 in (3.2 cm)

## Input

Input power	300 W
Maximum Line Current per phase	4 A
Input Frequency	50/60 Hz
Plug standard	IEC 60320 C6
Nominal Input Voltage	120 V

## Output

Number of power socket outlets	1
Outlet standard	IEC 60320 C6

## Conformance

UL 1449 TVSS Rating	700
Product certifications	CSA NOM UL Listed
Standards	FCC part 68
Equipment protection policy	Lifetime : \$75000

## Environmental

Ambient air temperature for operation	32...104 °F (0...40 °C)
Relative humidity	0...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	5...113 °F (-15...45 °C)
Storage altitude	0...30000 ft (0.00...9144.00 m)

## Surge Protection and Filtering

NM Surge Response Time (ns)	1 ns common mode
EMI/RFI Noise rejection (100 kHz to 10 MHz)	0 dB
Peak current	12 KA common mode 6.5 kA normal mode
Surge energy rating	600 J
Data Line Protection	RJ11 Modem/Fax protection (two wire single line) RJ45 10/100 Base-T Ethernet protection

## Ordering and shipping details

Category	11309 - APC RESALE PRODUCTS
GTIN	00731304220701
Nbr. of units in pkg.	1
Package weight(Lbs)	1 lb(US) (0.45 kg)
Returnability	No

## Packing Units

Package 1 Height	2.72 in (6.9 cm)
Package 1 width	6.22 in (15.8 cm)
Package 1 Length	7.76 in (19.7 cm)
SCC14	10731304220708
Number of Units in Package 2	12
Package 2 Weight	6 lb(US) (2.72 kg)
Package 2 Height	8.3 in (210.82 mm)
Package 2 width	11.5 in (292.10 mm)
Package 2 Length	16.5 in (419.10 mm)
Number of Units in Package 3	480

## Offer Sustainability

EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
-------------------	---

## Contractual warranty

Warranty	Lifetime
----------	----------