



Technical Data Sheet



Xylene-free

FEATURES:

- Valve-Action markers allow more control over ink flow and keep the ink in the barrel from drying out if the cap is left off.
- Replaceable tips extend the life of your markers.
- Opaque paint markers will clearly mark on dark or light surfaces.
- Great for metal, wood, corrugated, rubber, plastic, glass and other hard to mark surfaces.
- Black and White meet nuclear specs RDT-F7-3T, rev. 5.1
- Minimum of 60% renewable content.
- No hazardous air pollutants

COMPATIBILITY:

- Safe for most porous & non-porous surfaces.
- Test on surfaces prior to use to ensure compatibility.

DIRECTIONS FOR USE:

- Shake marker until you hear the agitator
- Twist the cap off
- Gently pump until the tip is primed

TECH SPECS:

- Standard Stroke Width: 1/8"
- Fill Quantity: ~1/2 oz (~13 cc)
- Barrel Size: .625" Diameter x 4.125" Long

HEALTH & SAFETY:

- Use only with proper ventilation.
- Flammable liquid & vapor: keep away from ignition sources like flames, sparks, or electrostatic charges.
- Avoid skin and eye contact and ingestion.
- No Reportable Prop 65
- Flash Point: 62°F (17°C)
- For complete health & safety data, refer to SDS at www.diagraphmsp.com

PHYSICAL PROPERTIES:

Color	Part No.	Specific Gravity	VOC Level	Total Halogens	Dry Time
White	0940-013	1.22	5.6 lbs/gal	<60 ppm	20-30 Sec
Yellow	0940-014	1.22	6.3 lbs/gal	< 50 ppm	20-30 Sec
Black	0940-001	0.96	5.3 lbs/gal	< 65 ppm	20-30 Sec
Blue	0940-002	1.03	7.0 lbs/gal	< 25 ppm	20-30 Sec
Red	0940-010	1.02	5.6 lbs/gal	< 200 ppm	20-30 Sec
Green	0940-007	1.14	6.5 lbs/gal	< 45 ppm	20-30 Sec
Pink	0940-009	1.19	5.4 lbs/gal	< 200 ppm	20-30 Sec
Light Green	0940-006	1.21	5.9 lbs/gal	< 55 ppm	20-30 Sec
Orange	0940-008	1.01	6.0 lbs/gal	< 45 ppm	20-30 Sec