Dell Web Management for Monitors

This monitor comes with networking capability which lets you remotely access and change settings such as Input Source Selection, Brightness and Volume.

Before accessing the Dell Monitor Web Management feature, ensure that you have a working Ethernet cable connected to the RJ45 port at the rear of the monitor.



Ethernet Enable

Press and hold the Button 1 and Button 3 on the front panel for 3 seconds to turn on , A network icon 📅 appears and is shown on Top - left corner for 5 seconds .

Ethernet Disable

Press and hold the Button 1 and Button 3 on the front panel for 3 seconds to turn off , A network icon \mathbb{X} appears and is shown on Top - left corner for 5 seconds .

To access the Dell Monitor Web Management tool you need to set the IP Addresses for your computer and the monitor.

1. Press the **Menu** key on the remote control to display the IP Address of the monitor, or by navigating to OSD Menu > **Others**. By default, the IP Address is 10.0.50.100





 In the computer's IP Properties tab, specify an IP Address by selecting Use the following IP Address and enter the following values: For IP Address: 10.0.50.101 and for Subnet Mask: 255.0.0.0 (leave all other entries as blanks).

meral						_	
ou can get IP settings assigne his capability. Otherwise, you r or the appropriate IP settings.	d automatically need to ask yo	yify	our	ork	ad	nrk su Iminis	ipport trator
Obtain an IP Address auto	matically						
Use the following IP Addres	95:						
IP Address:	10	. 0		50		101	
Subnet mask:	255	. 0		0		0	
Default gateway:			,				
Obtain DNS server address	automatically	7					
Use the following DNS serv	er addresses	-					
Preferred DNS server:							
Alternate DNS server:		•			•		
much de la companya de la	t			0		dune	red

3. The IP Address configuration would now look like this:



To access and use the web management tool, follow these steps:

1. Open a web browser and type the monitor's IP Address (10.0.50.100) in the address bar.



2. The log-in page opens. Enter the Administrator Password to continue.

Ca (5) (7 http://192.168.0.201/	P × C A DILL 5560 Web Manage. X	
		^
	Monitor Web Management	
	Projector Name: D16815	
	10 Address:	
	192.168.0.201	
	Login	
		 ,
		 î

3. The **Home** page opens:

Monitor W	eb Management		English -
	🕈 Home		2 A.
🛉 Home	Welcome to DELL	C7017T Web Management.	
A Network Settings	Monitor Informatio	n	
 Firmware Update Security 	Model Name	DELL C7017T	
	Monitor Name	D57645	
	Location	no setting	
	Contact	no setting	
	Network FW Version	A52	
	IP Address	10.0.50.100	
	MAC Address	00:60:E9:1A:E1:2D	
	Monitor Status	ON	

4. Click Network Settings tab to see the network settings.

	lanagement						0
.7.	Network Se	ettings					
me							
work Settings	twork Adapter F	roperties					
nitor Control Mo	idel Name:	DELL O	27017T				
mware Update Mo	nitor Name:	D5764	5				
urity Lo	cation:						
Co	ntact:						
					Apply		
IP	Settings						
IP	Settings Obtain IP address	automatically	: @l	Jse the fo	lowing IP address:		
IP ©	Settings Obtain IP address	au tomatically	: • (Jse the fo	lowing IP address:		
IP ©	Settings Obtain IP address Address	au tomatically	: • l	Jse the fo	lowing IP address:		
IP © Sut	Settings Obtain IP address Address bnet Mask	au tomatically 10 255	·: • U	Jse the fo . 50 . 0	lowing IP address:		
IP © IP . Sui Ga	Settings Obtain IP address Address bnet Mask teway	au tomatically 10 255 10 255	: • l	Jse the fo	lowing IP address: . 100 . 0 . 254		
IP © Sub Ga DN	Settings Obtain IP address Address bnet Mask teway IS Server	au tomatically 10 255 10 255	•: • • • •	Jse the fo . 50 . 0 . 0 . 255	lowing IP address:		
IP © Sut Ga DN	Settings Obtain IP address Address binet Mask teway IS Server	au tomatically 10 255 10 255	: • • • •	Jse the fo 50 0 255	Lowing IP address: . 100 . 0 . 255 Apply		
IP © Suti Ga DN Re	Settings Obtain IP address Address benet Mask teway IS Server set Network Settir	au tomatically 10 255 10 255	•: • • • •	Jse the fo	lowing IP address: . 100 . 0 . 254 . 255 Apply Apply		

5. Click **Monitor Control** to see the monitor's status. It takes about 3 to 5 mins for the monitor information to be updated on the Web Management.

Monitor W	/eb Management					English -
Home Hetwork Settings Monitor Control A. Firmware Update G. Security	Monitor Cont Monitor Status Monitor Status Image Control	Power ON Power OFF				
	Source Select Preset Mode Aspect Ratio	SelectSelect		•		
	Brightness Contrast Sharpness	(0-100) 75 (0-100) 75 (0-100) 50	Apply Apply Apply			
	Response Time Audio Control	Select	Apply	•		
	Speaker Keypad Control	Enable	 Disable 			
	Keypad Reset Monitor Control Se	Lock	 Unlock Apply 			

6. Click Security to set a password.

Security	
Web Management Login Option	
Password Login 🔘 Enable 💿 Disable	
Current Password	
New Password	
Confirm Password	
Save	

7. Update Firmware for your monitor's network card. You can download the latest network firmware, if available, from the Dell Support website at www.dell.com/support.

Monitor W	eb Management				English 🗸
骨骨 Home 孟基 Network Settings 으며 Monitor Control	 Firmware Updat Firmware update will take at it has begun.Keep the connection network system will auto reboor 	eut a minute. Do not i on established until co t and you can re-login	interrupt the proc ompletion of proce after update is cor	ess once ss. The mplete.	
▲ Bonnier Lenter	Network Firmware Version:	A53	Update	Cancel	