



Overview

The HP LaserJet Pro MFP M428-focus your time growing your business and staying ahead.

Winning in business means working smarter. The HP LaserJet Pro MFP M428 is designed to let you focus your time where it's most effective-growing your business and staying ahead of the competition.

Built to keep you—and your business moving forward

Scan files directly to Microsoft[®] SharePoint, email, USB, and network folders.[1]

Simply designed to uncomplicate your day

Set up this MFP fast, and easily manage device settings to help increase overall printing efficiency.

Best-in-class security- detect and stop attacks[7]

A suite of embedded security features help protect your MFP from being an entry point for attacks.[7]

Sustainability is smart business

Avoid frustrating reprints, wasted supplies, and service calls using Original HP toner cartridges



Enhanced workflows Enhanced security

New user interface Energy efficient

[1] Some scan apps may require an Internet connection to the printer. Services may require registration. App availability varies by country, language, and agreements. For details, see http://www.hpconnected.com

[7] Based on HP review of 2019 published security features of competitive in-class printers. Only HP offers a combination of security features that can monitor to detect and automatically stop an attack then self-validate software integrity in a reboot. For a list of printers, visit http://hp.com/go/PrintersThatProtect. For more information: http://hp.com/go/printersecurityclaims

Specifications

Print Resolution Technologies	HP FastRes 1200, HP ProRes1200, Economode
Print quality black (best)	Fine Lines (1200 x 1200 dpi)
Print speed black (ISO, A4)	Up to 38 ppm (default) ; Up to 40 ppm (HP High Speed)
Print speed black (ISO, letter)	Up to 40 ppm (default) ; Up to 42 ppm (HP High Speed)
Print speed	Prints up to 40/42 ppm (A4/LTR) (HP High Speed)
Functions	Print, Copy, Scan, Fax, Email
Duplex printing	Automatic (default)
Duty cycle (monthly, A4)	Up to 80,000 pages
Duty cycle (monthly, letter)	Up to 80,000 pages ^[11]
Printer smart software features	Apple AirPrint [™] , Mopria certified, Google Cloud Print 2.0, ROAM capable for easy printing, HP ePrint, and HP Auto-On/Auto-Off Technology, Intuitive 2.7" touchscreen control panel, Scan/Print from Cloud using apps on the control panel, Job Storage with PIN printing, Print from USB, N-up printing, collation
Copier smart software features	Instant-on copy; Duplex copy (2-sided to 2-sided option of "book-style" or "flip style"); up to 999 multiple copies; Scan once print many; Collation; Reduce/enlarge from 25 to 400% (custom page size presets, binding margin, and two pages to one page); Fit to page; Brightness (lighter/darker); Quality (draft/normal/best); ID copy; Enhancements (optimize for content with presets: none, text, photo, mixed); Copy preview (scan glass only)
Scanner advanced features	Single-pass 2-sided scanning ADF, Scan to cloud (Google Drive and DropBox) Scan to email with LDAP email address lookup, Scan to network folder, Scan to USB, Scan to Microsoft SharePoint [®] , Scan to computer with software, Fax archive to network folder, Fax archive to email, Fax to computer, Enable/disable fax, Quick Sets
Fax smart software features	Permanent fax memory backup; Auto fax reduction; Auto redialing; Delayed sending; Fax forwarding; TAM interface; Junk barrier; Distinctive ring detection; Cover page; Block fax; Billing codes; Save and load; Fax activity reports; Dial prefix setting; Print fax log; HP Digital Fax
Energy savings feature technology	HP Auto-On/Auto-Off Technology; Instant-on Technology
Replacement cartridges	AMS: For distribution and use in North America and Latin America only: HP 58A Black LaserJet Toner Cartridge (~3,000 pages), CF258A HP 58X Black LaserJet Toner Cartridge (~10,000 pages), CF258X; EMEA: For distribution and use in Europe, Middle East, Russia, CIS, and Africa only: HP 59A Black LaserJet Toner Cartridge (~3,000 pages), CF259A HP 59X Black LaserJet Toner Cartridge (~10,000 pages), CF259X; APJ: For distribution and use only in Asia Pacific - excluding China (PRC) and India: HP 76A Black LaserJet Toner Cartridge (~3,000 pages), CF276A HP 76X Black LaserJet Toner Cartridge (~10,000 pages), CF276X ^[3]
Supplies feature	HP JetIntelligence Cartridge
Connectivity, standard	1 Hi-Speed USB 2.0; 1 rear host USB; 1 Front USB port; Gigabit Ethernet 10/100/1000BASE-T network; 802.3az(EEE)

Modem	33.6 kbps
Network capabilities	Yes, via built-in 10/100/1000Base-TX Ethernet, Gigabit; Auto-crossover Ethernet; Authentication via 802.1X
Mobile printing capability	HP Smart App; Apple AirPrint™; Google Cloud Print™; HP ePrint; Mobile Apps; Mopria™ Certified; Roam capable for easy printing
Network protocols, supported	TCP/IP, IPv4, IPv6; Print: TCP-IP port 9100 Direct Mode, LPD (raw queue support only), Web Services Printing, HP ePrint, Apple AirPrint [™] , Google Cloud Print 2.0, Mopria, IPP Print; Discovery: SLP, Bonjour, Web Services Discovery; IP Config: IPv4 (BootP, DHCP, AutoIP, Manual), IPv6 (Stateless Link-Local and via Router, Statefull via DHCPv6), SSL Security and Certificate management; Management: SNMPv1, SNMPv2, SNMPv3, HTTP/HTTPS, Syslog, FTP FW Download
Software included	No software solutions are included in the Box, Download software at http://123.hp.com/laserjet or http://hp.com
Compatible Operating Systems	Windows Client OS (32/64 bit), Win10, Win8.1, Win 8 Basic, Win8 Pro, Win8 Enterprise, Win8 Enterprise N, Win7 Starter Edition SP1, UPD Win7 Ultimate, Mobile OS, iOS, Android, Mac, Apple® macOS Sierra v10.12, Apple® macOS High Sierra v10.13, Apple® macOS Mojave v10.14, Discrete PCL6 Printer Driver, For more information on the supported operating systems go to http://support.hp.com, Enter your product name and search, Click on User Guides and enter your product name and search for User Guide, Search for your (Product Name) - User Guide, Search for the Supported Operating Systems section, UPD PCL6 / PS Printer Drivers, Supported Operating systems, For more information on the supported operating systems see http://www.hp.com/go/upd
Environmental	Mercury-free
Energy star certified	Yes
Energy efficiency	CECP; ENERGY STAR [®] qualified; EPEAT [®] Silver ^[16]
Blue Angel compliant	Yes, Blue Angel DE-UZ 205—only ensured when using Original HP supplies
Blue Angel compliant Copy speed (black, normal quality, A4)	Yes, Blue Angel DE-UZ 205—only ensured when using Original HP supplies Up to 38 cpm
Copy speed (black, normal quality,	
Copy speed (black, normal quality, A4)	Up to 38 cpm
Copy speed (black, normal quality, A4) Copy speed black (normal, letter)	Up to 38 cpm Up to 40 cpm
Copy speed (black, normal quality, A4) Copy speed black (normal, letter) Copy speed black duplex (A4)	Up to 38 cpm Up to 40 cpm Up to 31 cpm
 Copy speed (black, normal quality, A4) Copy speed black (normal, letter) Copy speed black duplex (A4) Copy speed black duplex (Letter) 	Up to 38 cpm Up to 40 cpm Up to 31 cpm Up to 33 cpm Scan to email with LDAP email address lookup, Scan to network folder, Scan to USB, Scan to Microsoft SharePoint®, Scan to computer with software, Fax archive to network folder, Fax archive to email, Fax to
Copy speed (black, normal quality, A4) Copy speed black (normal, letter) Copy speed black duplex (A4) Copy speed black duplex (Letter) Digital sending standard features	Up to 38 cpm Up to 40 cpm Up to 31 cpm Up to 33 cpm Scan to email with LDAP email address lookup, Scan to network folder, Scan to USB, Scan to Microsoft SharePoint®, Scan to computer with software, Fax archive to network folder, Fax archive to email, Fax to computer, Enable/disable fax, Quick Sets
 Copy speed (black, normal quality, A4) Copy speed black (normal, letter) Copy speed black duplex (A4) Copy speed black duplex (Letter) Digital sending standard features Fax Resolution Black (best) 	Up to 38 cpmUp to 40 cpmUp to 31 cpmUp to 33 cpmScan to email with LDAP email address lookup, Scan to network folder, Scan to USB, Scan to Microsoft SharePoint®, Scan to computer with software, Fax archive to network folder, Fax archive to email, Fax to computer, Enable/disable fax, Quick SetsUp to 300 x 300 dpi (halftone enabled)
 Copy speed (black, normal quality, A4) Copy speed black (normal, letter) Copy speed black duplex (A4) Copy speed black duplex (Letter) Digital sending standard features Fax Resolution Black (best) Faxing 	Up to 38 cpmUp to 40 cpmUp to 31 cpmUp to 33 cpmScan to email with LDAP email address lookup, Scan to network folder, Scan to USB, Scan to Microsoft SharePoint®, Scan to computer with software, Fax archive to network folder, Fax archive to email, Fax to computer, Enable/disable fax, Quick SetsUp to 300 x 300 dpi (halftone enabled)Yes
 Copy speed (black, normal quality, A4) Copy speed black (normal, letter) Copy speed black duplex (A4) Copy speed black duplex (Letter) Digital sending standard features Fax Resolution Black (best) Faxing Scan speed (normal, A4) 	Up to 38 cpmUp to 40 cpmUp to 31 cpmUp to 33 cpmScan to email with LDAP email address lookup, Scan to network folder, Scan to USB, Scan to Microsoft SharePoint®, Scan to computer with software, Fax archive to network folder, Fax archive to email, Fax to computer, Enable/disable fax, Quick SetsUp to 300 x 300 dpi (halftone enabled)YesUp to 29 ppm/46 ipm (b&w), up to 20 ppm/34 ipm (color)

Scan technology	Contact Image Sensor (CIS)
Scanner type	Flatbed, ADF
Display area (imperial)	2.13 x 1.59 in
Display area (metric)	5.4 x 4.05 cm
Display	2.7" (6.86 cm) intuitive color touchscreen (CGD)
Minimum dimensions (W x D x H)	420 x 390 x 323 mm (without trays and covers not extended)
Minimum dimensions (W x D x H)	16.54 x 15.35 x 12.72 in (without trays and covers not extended)
Weight	12.6 kg
Weight	27.78 lb
Power consumption	510 watts (active printing), 7.5 watts (ready), 0.9 watts (sleep), 0.9 watts (Auto Off/Wake on LAN, enabled at shipment), 0.06 watts (Auto- off/Manual-on), 0.06 (Manual Off) ^[2]
Power supply type	Internal (Built-in) power supply
What's in the box	HP LaserJet Pro M428fdn; Preinstalled HP Black LaserJet Toner Cartridge (59A for EMEA, 58A for AMS, 76A for AP, yield ~3,000 pages); Getting Started Guide; Support Flyer; Warranty Guide; Regulatory Flyer; Power cord; Phone cord; USB cable (AP Only). HP printer software is available at http://www.hp.com/support ^[17]
Services (Care Pack)	UB9R7E - HP 3y NBD LJ Pro MFP M428 M429 M329 SVC; UB9R8E - HP 4y NBD LJ Pro MFP M428 M429 M329 SVC; UB9R9E - HP 5y NBD LJ Pro MFP M428 M429 M329 SVC; UC0R2E - HP 3y4h9x5 LJ Pro MFP M428 M429 M329 SVC; UC0R3E - HP 4y4h9x5 LJ Pro MFP M428 M429 M329 SVC; UC0R4E - HP 5y4h9x5 LJ Pro MFP M428 M429 M329 SVC; UB9S0E - HP 3y NBDExchg LJ ProMFPM428M429M329 SVC; UB9S1E - HP 3y RTD LJ Pro MFP M428 M429 M329 SVC; UB9S2PE - HP 1yPWNBD LJ Pro MFP M428 M429 M329 SVC; UB9S3PE - HP 2yPWNBD LJ Pro MFP M428 M429 M329 SVC; UC0R5PE - HP 1yPW4h9x5 LJProMFP M428 M429 M329 SVC; UB9S4PE - HP1yPWNBDExchg LJProMFP M428M429M329 SVC; UB9S5PE - HP 1yPWRTD LJ Pro MFP M428 M429 M329 SVC;
Warranty	One-year Bench/Depot Repair warranty. Warranty and support options vary by product, country and local legal requirements. Contact your Contractual Vendor or go to hp.com/support to learn about HP award winning service and support options in your region. (wty code 4E; wty ID A033)

Additional specifications

Accessories	HP LaserJet 550-sheet Feeder Tray D9P29A; HP v222w 16 GB Mini USB Drive P0R81AA
Acoustic power emissions (active scan)	6.3 Bel(A) (Scanning with ADF running)
Acoustic power emissions (active, printing)	6.7 Bel(A) (Printing at 38 ppm)
Acoustic power emissions (ready)	Inaudible
Acoustic pressure emissions bystander (active scan)	48 dB(A) (Scanning with ADF running)
Acoustic pressure emissions bystander (active, printing)	53 dB(A)
Acoustic pressure emissions bystander (ready)	Inaudible
Auto fax reduction supported	Yes
Automatic document feeder capacity	Standard, 50 sheets
Automatic paper sensor	No
Bit depth	24-bit
Bottom margin (A4)	5 mm
Cable included	Yes, 1 USB cable (AP only); No, please purchase USB cable separately (EMEA, Americas)
Certifications and compliances	CSA (Canada), ANZ (Australia & New Zealand), TUV and GS Mark (Germany), BSMI (Taiwan), CCC (China), KC & KCC (South Korea), NOM (Mexico), Malaysia, Singapore, Chile, Vietnam, Eastern European approvals, CE Marking, FCC approval, BIS(India), S-Mark(Argentina), UL listed and etc.
Color scanning	Yes
Compatible Network Operating Systems	Windows Server 2008 R2 64-bit, Windows Server 2008 R2 64-bit (SP1), Windows Server 2012 64-bit, Windows Server 2012 R2 64-bit, Windows Server 2016 64-bit, Failover Cluster 2008 R2, Failover Cluster 2012 R2, Terminal server 2008 R2, Remote Desktop server 2012 R2, Citrix Server 6.5, Citrix XenApp & XenDesktop 7.6, Novell iPrint server, Citrix Ready Kit Certification - Upto Citrix Server 7.18 for more information see http://citrixready.citrix.com, Linux- For more information see http://developers.hp.com/hp-linux-imaging-and-printing, Unix- For more information see http://hp.com/go/unixmodelscripts, UPD PCL6 / PS Printer Drivers, Supported for Compatible Network Operating systems please see http://hp.com/go/upd
Control panel	2.7" Color Touchscreen
Copier scaling (ADF)	25 to 400%
Copier settings	ID Copy; Number of copies; Resize (including 2-Up); Lighter/Darker; Enhancements; Original Size; Binding Margin; Collation; Tray Selection; Two-Sided; Quality (Draft/Normal/Best); Save Current Settings; Restore Factory Defaults

Copies, maximum	Up to 999 copies
Copy reduce / enlarge settings	25 to 400%
Copy resolution (black text)	Up to 600 x 600 dpi
Copy resolution (color text and graphics)	Up to 600 x 600 dpi
Count of cartons per pallet layer	6
Count of layers in pallet	5 (NA), 4 (EMEA,AP)
Country of origin	Made in China
Distinctive ring detection supported	Yes
Downloadable software	From http://123.hp.com, HP Easy Start (Guided Software Install for Windows and Mac), From http://hp.com for Windows OS, Full-solution software and drivers, Basic-solution software and drivers, HP PCL6 XPS Discrete Print Driver, Product Documentation and Support, From http://hp.com for Mac OS, HP Easy Start (Guided Software Install), HP Mac PS Print Driver, HP Easy Admin, For Mobile OS, iOS For more information see http://hp.com/go/businessmobileprinting, Android For more information see http://hp.com/go/businessmobileprinting, From http://hp.com for printer administrators, Printer Administrator Resource Kit (Driver Configuration Utility - Driver Deployment Utility - Managed Printing Administrator), HP Universal Print Drivers PCL6 GDI & PS GDI for Windows, HP ePrint Software (Mobile Driver for Windows), SAP Print Drivers for more information see http://support.hp.com/us- en/document/c05051702, HP Web JetAdmin, HP JetAdvantage Security Manager, HP Roam, HPLIP Linux Printer Driver for more information see http://hplipopensource.com/hplip-web/index.html, Unix Model Script Printer Driver for more information see http://hplicom/go/unixmodelscripts, ReadIris
Driver updates	Latest supported operating systems and Print drivers available at http://www.hp.com/support/ljM428MFP
Duplex ADF scanning	Yes
Duty cycle note	Duty cycle is defined as the maximum number of pages per month of imaged output. This value provides a comparison of product robustness in relation to other HP LaserJet or HP Color LaserJet devices, and enables appropriate deployment of printers and MFPs to satisfy the demands of connected individuals or groups.
Electromagnetic compatibility	CISPR 32:2012/EN 55032:2012 - Class B, CISPR 32:2015/EN 55032:2015 - Class B, EN 61000-3-2:2014, EN 61000-3-3:2013, EN 55024:2010+A1:2015, FCC Title 47 CFR, Part 15 Class B / ICES-003, Issue 6;
Enhanced scanning resolution	Up to 1200 x 1200 dpi
Envelope Feeder	No
FCC Class A emissions	FCC Class A emissions - for use in commercial environments, not residential environments
Fax Auto Redial	Yes
Fax Broadcast Locations	119
Fax PC Interface Supported	Yes, only for sending

Fax Polling	Yes (receive only)
Fax Speed Dials, Maximum Number	Up to 120 numbers
Fax Transmission Speed	33.6 kbps
Fax delayed sending	Yes
Fax forwarding	Yes
Fax memory	Up to 400 pages
Fax memory	Up to 400 pages
Fax phone TAM interface supported	Yes
Fax resolution black	Up to 203 x 196 dpi
Fax telephone mode supported	Yes
Fax transmission speed (letter)	3 sec per page ^[15]
Finished output handling	Sheetfeed
First copy out black (A4)	As fast as 7.2 sec
First copy out black (A4, sleep)	As fast as 9.5 sec
First copy out black (letter)	As fast as 6.8 sec
First copy out black (letter, sleep)	As fast as 9.1 sec
First page out black (A4, ready)	As fast as 6.3 sec
First page out black (A4, sleep)	As fast as 8.8 sec
First page out black (letter, ready)	As fast as 6.1 sec
First page out black (letter, sleep)	As fast as 8.6 sec
Fonts and typefaces	84 scalable TrueType fonts
Input capacity	Up to 350 sheets (Tray 1: up to 100 sheets; Tray 2: up to 250 sheets)
Internal Storage	No
Junk fax barrier	Yes, CSID matching only (Caller ID not supported)
Left margin (A4)	4 mm
Levels of grayscale	256
Mac compatible	Yes
Maximum Input Capacity (envelopes)	Up to 10 envelopes
Maximum Memory	512 MB
Maximum dimensions (W x D x H)	430 x 634 x 325 mm
Maximum dimensions (W \times D \times H)	16.93 x 25 x 12.8 in
Maximum input capacity (sheets)	Up to 900 sheets (with Optional 550-sheet tray)
Maximum output capacity (sheets)	Up to 150 sheets
Maximum print area	207.4 x 347.1mm

Media size (ADF)	Letter; Legal; A4; custom sizes 102 x 152 to 216 x 356 mm
Media size, tray 1	Letter; Legal; Executive; Oficio (8.5 x 13 in); A4; A5; A6; B5 (JIS); Oficio (216 x 340 mm); 16K (195 x 270 mm); 16K (184 x 260 mm); 16K (197 x 273 mm); Custom Size; A5-R; 5 x 8 in; B6 (JIS); Statement
Media size, tray 2	Letter; Legal; Executive; Oficio (8.5 x 13 in); A4; A5; A6; B5 (JIS); Oficio (216 x 340 mm); 16K (195 x 270 mm); 16K (184 x 260 mm); 16K (197 x 273 mm); Custom Size; A5-R; 5 x 8 in; B6 (JIS); Statement
Media size, tray 3	Letter; Legal; Executive; Oficio (8.5 x 13 in); A4; A5; A6; B5 (JIS); Oficio (216 x 340 mm); 16K (195 x 270 mm); 16K (184 x 260 mm); 16K (197 x 273 mm); Custom Size; A5-R; 5 x 8 in; B6 (JIS); Statement
Media sizes supported	Tray 1: A4; A5; A6; B5 (JIS); Oficio (216 x 340 mm); 16K (195 x 270 mm); 16K (184 x 260 mm); 16K (197 x 273 mm); Japanese Postcard; Double Japan Postcard Rotated; Envelope #10; Envelope Monarch; Envelope B5; Envelope C5; Envelope DL; Custom Size; 4 x 6 in; 5 x 8 in; Statement; Tray 2 & Tray 3: A4; A5; A6; B5 (JIS); Oficio (216 x 340 mm); 16K (195 x 270 mm); 16K (184 x 260 mm); 16K (197 x 273 mm); Custom Size; A5-R; 4 x 6 in; B6 (JIS)
Media sizes supported	Tray 1: Letter; Legal; Executive; Oficio (8.5 x 13 in); 16K; Japanese Postcard; Double Japan Postcard Rotated; Envelope #10; Envelope Monarch; Envelope B5; Envelope C5; Envelope DL; Custom Size; 4 x 6 in; 5 x 8 in; Statement; Tray 2 & Tray 3: Letter; Legal; Executive; Oficio (8.5 x 13 in); Custom Size; 5 x 8 in; Statement
Media sizes supported, key	4 x 6 in; Letter; Legal; Envelopes
Media sizes supported, key	10 x 15 cm; A4; Envelopes
Media sizes, custom	Tray 1: 3 x 5 to 8.5 x 14 in, Tray 2, 3: 4.13 x 5.85 to 8.5 x 14 in
Media sizes, custom	Tray 1: 76.2 x 127 to 215.9 x 355.6 mm; Tray 2, 3: 104.9 x 148.59 to 215.9 x 355.6 mm
Media type and capacity, ADF	Sheets: 50 uncurled
Media type and capacity, tray 1	Sheets: 100; Envelopes: 10
Media type and capacity, tray 2	Sheets: 250
Media type and capacity, tray 3	Sheets: 550 (optional)
Media types	Paper (plain, EcoEFFICIENT, light, heavy, bond, colored, letterhead, preprinted, prepunched, recycled, rough); envelopes; labels;
Media weight (tray 1)	60 to 200 g/m ²
Media weight (tray 2)	60 to 120 g/m²
Media weight (tray 3)	60 to 120 g/m² (optional 550-sheet tray)
Media weight, supported	Tray 1: 60 to 200 g/m ² ; tray 2, optional 550-sheet tray 3: 60 to 120 g/m ²
Media weight, supported	Tray 1: 16 to 46.6 lb; tray 2, optional 550-sheet tray 3: 16 to 32 lb
Media weights, supported ADF	60 to 120 g/m²
Media weights, supported ADF	16 to 32 lb
Memory	512 MB
Minimum System Requirements	2 GB available hard disk space, Internet connection, USB port, Internet browser. For additional OS hardware requirements see http://microsoft.com

Minimum System Requirements2 GB available hard drive space, Internet connection or USB port, 05 hardware requirements see apple.com;Native scan file formatPDF; JPGNumber of print cartridges1 (black)Number of users3-10 UsersOperating humidity range10 to 80% RH (non-condensing)Operating temperature range50 to 90.5°FOperating temperature range10 to 150 sheetsPackage dimensions (W x D x H)19.56 x 15.66 x 19.29 inPackage dimensions (W x D x H)497 x 398 x 490 mmPackage dimensions (W x D x H)497 x 398 x 490 mmPackage weight34.1 lbPackage weight34.1 lbPackage weight1200 x 1000 x 2605 mm (NA), 47.24 x 39.37 x 83.27 in (EMEA, AP)Pallet dimensions47.24 x 39.37 x 102.56 in (NA), 47.24 x 39.37 x 83.27 in (EMEA, AP)Pallet dimensions (W x D x H)1200 x 1000 x 2605 mm (NA), 1200 x 1000 x 2115 mm (EMEA, AP)Pallet dimensions (W x D x H)1200 x 1000 x 2605 mm (NA), 47.24 x 39.37 x 83.27 in (EMEA, AP)Pallet dimensions (W x D x H)1200 x 1000 x 2605 mm (NA), 1200 x 1000 x 2115 mm (EMEA, AP)Pallet dimensions (W x D x H)1200 x 1000 x 2605 mm (NA), 1200 x 1000 x 2115 mm (EMEA, AP)Pallet dimensions (W x D x H)100-sheet tray 1, 250-sheet input tray 2; 50-sheet Automatic Document Feeder (ADF)Paper handling input, standard100-sheet tray 1, 250-sheet input tray 2; 50-sheet Automatic Document Feeder (ADF)Paper tays, standard2Paper tays, standard2Paper tays, standard100-sheet tray 1, 250-sheet input tray 2; 50-sheet Automatic Documen		
Number of print cartridges1 (black)Number of users3-10 UsersOperating humidity range10 to 80% RH (non-condensing)Operating temperature range50 to 90.5°FOutput capacityUp to 150 sheetsPackage dimensions (W x D x H)19.56 x 19.29 inPackage dimensions (W x D x H)497 x 398 x 490 mmPackage dimensions (W x D x H)34.1 tbPackage weight34.1 tbPackage weight34.1 tbPalet dimensions (W x D x H)1200 x 1000 x 2605 mm (NA), 47.24 x 39.37 x 83.27 in (EMEA, AP)Palet dimensions (W x D x H)1200 x 1000 x 2605 mm (NA), 1200 x 1000 x 2115 mm (EMEA, AP)Palet dimensions (W x D x H)1200 x 1000 x 2605 mm (NA), 1200 x 1000 x 2115 mm (EMEA, AP)Palet dimensions (W x D x H)1200 x 1000 x 2605 mm (NA), 1200 x 1000 x 2115 mm (EMEA, AP)Palet weight0ptional third 550-sheet trayPalet weight100-sheet tray 1, 250-sheet input tray 2; 50-sheet Automatic Document Feeder (ADF)Paper handling input, standard100-sheet tray 1, 250-sheet input tray 2; 50-sheet Automatic Document Feeder (ADF)Paper handling output, standard2Paper trays, standard2Pint technologyLaserPrint technologyLaserPrint tanguagesNoPint tanguagesNormal (nattue 600 x 600 dpi; enhanced up to 4800 x 600 dpi)Print resolution black (fine lines)Fine Lines (1200 x 1200 dpl)Print speed black (Landscape, AS)Up to 43 ppm		• •
Number of users3-10 UsersOperating hundlity range10 to 80% RH (non-condensing)Operating temperature range50 to 90.5°FOperating temperature range10 to 32.5°COutput capacityUp to 150 sheetsPackage dimensions (W x D x H)19.56 x 15.66 x 19.29 inPackage dimensions (W x D x H)497 x 398 x 490 mmPackage weight34.1 lbPackage weight34.1 lbPage yield (set-up/inbox cartridges)~3000 pages blackPallet dimensions (W x D x H)1200 x 1000 x 2605 mm (NA), 47.24 x 39.37 x 83.27 in (EMEA, AP)Pallet weight47.24 x 39.37 x 102.56 in (NA), 47.24 x 39.37 x 83.27 in (EMEA, AP)Pallet dimensions (W x D x H)1200 x 1000 x 2605 mm (NA), 1200 x 1000 x 2115 mm (EMEA, AP)Pallet weight0ptional third 550-sheet trayPallet weight0ptional third 550-sheet trayPallet dimensions (W x D x H)100-sheet tray 1, 250-sheet input tray 2; 50-sheet Automatic Document Feeder (ADF)Paper handling input, optional0ptional third 550-sheet trayPaper trays, maximum3Paper trays, standard100-sheet tray 1, 250-sheet input tray 2; 50-sheet Automatic Document Feeder (ADF)Paper trays, standard2Paper trays, maximum3Paper trays, maximum3Paper trays, maximum3Paper trays, maximum3Paper trays, standard10-volt input voltage: 210 to 127 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); 200-volt input voltage: 210 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); 200-volt input voltage: 200 240 VAC (+/- 10%), 50/60 Hz (+/- 2	Native scan file format	PDF; JPG
Operating humidity range10 to 80% RH (non-condensing)Operating temperature range50 to 90.5°FOperating temperature range10 to 32.5°COutput capacityUp to 150 sheetsPackage dimensions (W x D x H)19.56 x 15.66 x 19.29 inPackage dimensions (W x D x H)497 x 398 x 490 mmPackage weight34.1 lbPackage weight34.1 lbPackage weight34.1 lbPage yield (set-up/lnbox cartridges)~3000 pages blackPallet dimensions (W x D x H)1200 x 1000 x 2605 mm (NA), 1200 x 1000 x 2115 mm (EMEA, AP)Pallet weight072.9 lb (NA), 868.3 lb (EMEA, AP)Pallet weight0ptional third 550-sheet trayPallet weight00-sheet tray, 1, 250-sheet input tray 2; 50-sheet Automatic Document Feeder (ADF)Paper handling input, standard100-sheet up 1, 250-sheet input tray 2; 50-sheet Automatic Document Feeder (ADF)Paper trays, standard2Power110-volt input voltage: 110 to 127 VAC (+/- 10%), 50/60 H2 (+/- 2 H2); 220-volt input voltage: 200 240 VAC (+/- 10%), 50/60 H2 (+/- 2 H2); 220-volt input voltage: 200 240 VAC (+/- 10%), 50/60 H2 (+/- 2 H2); 220-volt input voltage: 200 240 VAC (+/- 10%), 50/60 H2 (+/- 2 H2); 220-volt input voltage: 200 240 VAC (+/- 10%), 50/60 H2 (+/- 2 H2); 220-volt input voltage: 200 240 VAC (+/- 10%), 50/60 H2 (+/- 2 H2); 220-volt input voltage: 200 240 VAC (+/- 10%), 50/60 H2 (+/- 2 H2); 220-volt input voltage: 200 240 VAC (+/- 10%), 50/60 H2 (+/- 2 H2); 220-volt input voltage: 200 240 VAC (+/- 10%), 50/60 H2 (+/- 2 H2); 220-volt input voltage: 200 240 VAC (+/- 10%), 50/60 H2 (+/- 2 H2); 220-volt input voltage: 200 240 VAC (+/- 10%), 50/60 H2 (+/- 2 H	Number of print cartridges	1 (black)
Operating temperature range50 to 90.5°FOperating temperature range10 to 32.5°COutput capacityUp to 150 sheetsPackage dimensions (W x D x H)19.56 x 15.66 x 19.29 inPackage veight497 x 398 x 490 mmPackage weight34.1 lbPackage weight34.1 lbPackage veight-3000 pages blackPallet dimensions (W x D x H)1200 x 1000 x 2505 in (NA), 47.24 x 39.37 x 83.27 in (EMEA, AP)Pallet dimensions47.24 x 39.37 x 102.56 in (NA), 47.24 x 39.37 x 83.27 in (EMEA, AP)Pallet dimensions47.24 x 39.37 x 102.56 in (NA), 1200 x 1000 x 2115 mm (EMEA, AP)Pallet dimensions47.24 x 39.37 x 102.56 in (NA), 1200 x 1000 x 2115 mm (EMEA, AP)Pallet weight100 x 1000 x 2605 mm (NA), 1200 x 1000 x 2115 mm (EMEA, AP)Pallet weight0ptional third 550-sheet trayPaper handling input, optional0ptional third 550-sheet input tray 2; 50-sheet Automatic Document Feeder (ADF)Paper handling output, standard100-sheet tray 1, 250-sheet input tray 2; 50-sheet Automatic Document Feeder (ADF)Paper trays, maximum3Paper trays, standard2Power110-volt input voltage: 110 to 127 VAC (+/- 10%), 50/60 H2 (+/- 2 H2); 220-volt input voltage: 220 to 240 VAC (+/- 10%), 50/60 H2 (+/- 2 H2); 220-volt input voltage: 220 to 240 VAC (+/- 10%), 50/60 H2 (+/- 2 H2); 220-volt input voltage: 220 to 240 VAC (+/- 10%), 50/60 H2 (+/- 2 H2); 220-volt input voltage: 220 to 240 VAC (+/- 10%), 50/60 H2 (+/- 2 H2); 220-volt input voltage: 220 to 240 VAC (+/- 10%), 50/60 H2 (+/- 2 H2); 220-volt input voltage: 220 to 240 VAC (+/- 10%), 50/60 H2 (+/- 2 H2); 220-volt input voltage: 220 to 240 VAC (+/- 10%)	Number of users	3-10 Users
Operating temperature range10 to 32.5°COutput capacityUp to 150 sheetsPackage dimensions (W x D x H)19.56 x 15.66 x 19.29 inPackage dimensions (W x D x H)497 x 398 x 490 mmPackage weight34.1 bPackage weight34.1 bPackage weight34.1 bPalet dimensions47.24 x 39.37 x 102.56 in (NA), 47.24 x 39.37 x 83.27 in (EMEA, AP)Pallet dimensions47.24 x 39.37 x 102.56 in (NA), 47.24 x 39.37 x 83.27 in (EMEA, AP)Pallet dimensions47.24 x 39.37 x 102.56 in (NA), 47.24 x 39.37 x 83.27 in (EMEA, AP)Pallet weight1200 x 1000 x 2605 mm (NA), 1200 x 1000 x 2115 mm (EMEA, AP)Pallet weight072.9 ib (NA), 68.3 ib (EMEA, AP)Pallet weight100-sheet tray 1, 250-sheet input tray 2; 50-sheet Automatic Document Feeder (ADF)Paper handling input, standard150-sheet output binPaper trays, maximum3Paper trays, standard10-ovit input voltage: 210 to 127 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); 20-ovit input voltage: 220 to 200 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); 20-ovit input voltage: 220 to 200 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); 20-ovit input voltage: 210 to 127 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); 20-ovit input voltage: 220 to 200 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); 20-ovit input voltage: 210 to 217 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); 20-ovit input voltage: 220 to 200 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); 20-ovit input voltage: 220 to 200 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); 20-ovit input voltage: 220 to 200 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); 20-ovit input voltage: 220 to 200 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); 20-ovit input voltage: 220 to 200 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); 20-ovit i	Operating humidity range	10 to 80% RH (non-condensing)
Output capacityUp to 150 sheetsPackage dimensions (W x D x H)19.56 x 15.66 x 19.29 inPackage dimensions (W x D x H)497 x 398 x 490 mmPackage weight15.5 kgPackage weight34.1 lbPage yield (set-up/inbox cartridges)-3000 pages blackPallet dimensions47.24 x 39.37 x 102.56 in (NA), 47.24 x 39.37 x 83.27 in (EMEA, AP)Pallet dimensions47.24 x 39.37 x 102.56 in (NA), 47.24 x 39.37 x 83.27 in (EMEA, AP)Pallet weight1002 x 1000 x 2605 mm (NA), 1200 x 1000 x 2115 mm (EMEA, AP)Pallet weight1072.9 lb (NA), 868.3 lb (EMEA, AP)Pallet weight0ptional third 550-sheet trayPallet weight100-sheet tray 1, 250-sheet input tray 2; 50-sheet Automatic Document Feeder (ADF)Paper handling input, standard150-sheet output binPaper trays, maximum3Paper trays, standard150-sheet output binPaper trays, standard2Pint technologyLaserPrint colorsNoPrint technologyLaserPrint quality black (normal)Normal (native 600 x 600 dpi; enhanced up to 4800 x 600 dpi)Print resolution black (fine lines)Fine Lines (1200 x 1200 dpi)Print speed black (Landscape, AS)Up to 63 ppmPrint appeed black (Portrait, AS)Up to 14 ppm	Operating temperature range	50 to 90.5°F
Package dimensions (W x D x H)19.56 x 15.66 x 19.29 inPackage dimensions (W x D x H)497 x 398 x 490 mmPackage weight15.5 kgPackage weight34.1 lbPage yield (set-up/inbox cartridges)-3000 pages blackPallet dimensions47.24 x 39.37 x 102.56 in (NA), 47.24 x 39.37 x 83.27 in (EMEA, AP)Pallet dimensions47.24 x 39.37 x 102.56 in (NA), 1200 x 1000 x 2115 mm (EMEA, AP)Pallet weight1072.9 lb (NA), 868.3 lb (EMEA, AP)Pallet weight00ptional third 550-sheet trayPallet weight100-sheet tray 1, 250-sheet input tray 2; 50-sheet Automatic Document Feeder (ADF)Paper handling input, standard150-sheet output binPaper trays, maximum3Paper trays, standard110-volt input voltage: 110 to 127 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); 220-volt input voltage: product varies by part number with # Option code identifier)Print technologyLaserPrint toolorsNoPrint quality black (normal)Normal (native 600 x 600 dpi; enhanced up to 4800 x 600 dpi)Print resolution black (fine lines)Fine Lines (1200 x 1200 dpi)Print speed black (Landscape, AS)Up to 14 ppm	Operating temperature range	10 to 32.5°C
Package dimensions (W x D x H)497 x 398 x 490 mmPackage weight15.5 kgPackage weight34.1 lbPackage weight34.1 lbPackage weight34.1 lbPackage weight-3000 pages blackPallet dimensions47.24 x 39.37 x 102.56 in (NA), 47.24 x 39.37 x 83.27 in (EMEA, AP)Pallet dimensions (W x D x H)1200 x 1000 x 2605 mm (NA), 1200 x 1000 x 2115 mm (EMEA, AP)Pallet weight1072.9 lb (NA), 868.3 lb (EMEA, AP)Pallet weight0ptional third 550-sheet trayPaper handling input, optional0ptional third 550-sheet trayPaper handling input, standard100-sheet tray 1, 250-sheet input tray 2; 50-sheet Automatic Document Feeder (ADF)Paper trays, maximum3Paper trays, standard150-sheet output binPaper trays, standard110-volt input voltage: 110 to 127 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); 220-wolt input voltage: 220 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); Not dual voltage, product varies by part number with # Option code dimetifier)Print colorsNoPrint colorsNoPrint quality black (normal)Normal (native 600 x 600 dpi; enhanced up to 4800 x 600 dpi) Fine Lines (1200 x 1200 dpi)Print speed black (landscape, AS)Up to 14 ppm	Output capacity	Up to 150 sheets
Package weight15.5 kgPackage weight34.1 lbPackage weight34.1 lbPackage weight-3000 pages blackPalet dimensions47.24 x 39.37 x 102.56 in (NA), 47.24 x 39.37 x 83.27 in (EMEA, AP)Pallet dimensions (W x D x H)1200 x 1000 x 2605 mm (NA), 1200 x 1000 x 2115 mm (EMEA, AP)Pallet weight1072.9 lb (NA), 868.3 lb (EMEA, AP)Pallet weight0ptional third 550-sheet trayPaper handling input, optional0ptional third 550-sheet input tray 2; 50-sheet Automatic Document Feeder (ADF)Paper handling output, standard100-sheet output binPaper trays, maximum3Paper trays, standard2Power110-volt input voltage: 110 to 127 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); 220-volt input voltage: 220 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); 220-volt input voltage: 220 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); 220-volt input voltage: 220 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); 220-volt input voltage: 220 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); 220-volt input voltage: 220 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); 220-volt input voltage: 220 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); 220-volt input voltage: 220 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); 220-volt input voltage: 220 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); 220-volt input voltage: 220 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); 220-volt input voltage: 220 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); 220-volt input voltage: 220 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); 220-volt input voltage: 220 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); 220-volt input voltage; 220 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); 220-volt input voltage; 220 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); 220-volt input voltage; 220 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz	Package dimensions ($W \times D \times H$)	19.56 x 15.66 x 19.29 in
Package weight34.1 lbPage yield (set-up/inbox cartridges)-3000 pages blackPallet dimensions47.24 x 39.37 x 102.56 in (NA), 47.24 x 39.37 x 83.27 in (EMEA, AP)Pallet dimensions (W x D x H)1200 x 1000 x 2605 mm (NA), 1200 x 1000 x 2115 mm (EMEA, AP)Pallet weight1072.9 lb (NA), 868.3 lb (EMEA, AP)Pallet weight0ptional third 550-sheet trayPaper handling input, optional0ptional third 550-sheet input tray 2; 50-sheet Automatic Document Feeder (ADF)Paper handling output, standard150-sheet output binPaper trays, maximum3Paper trays, standard2Power110-volt input voltage: 110 to 127 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); (Not dual voltage; 220 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); (Not dual voltage; 220 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); (Not dual voltage; 220 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); (Not dual voltage; 220 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); (Not dual voltage; 220 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); (Not dual voltage; 220 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); (Not dual voltage; 220 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); (Not dual voltage; 220 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); (Not dual voltage; 220 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); (Not dual voltage; 220 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); (Not dual voltage; 220 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); (Not dual voltage; 220 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); (Not dual voltage; 220 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); (Not dual voltage; 220 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); (Not dual voltage; 220 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); (Not dual voltage; 220 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); (No	Package dimensions (W x D x H)	497 x 398 x 490 mm
Page yield (set-up/inbox cartridges)~3000 pages blackPallet dimensions47.24 x 39.37 x 102.56 in (NA), 47.24 x 39.37 x 83.27 in (EMEA, AP)Pallet dimensions (W x D x H)1200 x 1000 x 2605 mm (NA), 1200 x 1000 x 2115 mm (EMEA, AP)Pallet weight1072.9 lb (NA), 868.3 lb (EMEA, AP)Pallet weight072.9 lb (NA), 868.3 lb (EMEA, AP)Pallet weight487.7 kg (NA), 394.7 kg (EMEA, AP)Paper handling input, optionalOptional third 550-sheet trayPaper handling input, standard100-sheet tray 1, 250-sheet input tray 2; 50-sheet Automatic Document Feeder (ADF)Paper trays, maximum3Paper trays, standard2Power110-volt input voltage: 110 to 127 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); 220-volt input voltage: 220 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); Not dual voltage, product varies by part number with # Option code identifier)Print technologyLaserPrint tolorsNoPrint tanguagesMormal (native 600 x 600 dpi; enhanced up to 4800 x 600 dpi)Print resolution black (fine lines)Fine Lines (1200 x 1200 dpi)Print speed black (Landscape, AS)Up to 63 ppmUp to 14 ppm100 to 14 ppm	Package weight	15.5 kg
cartridges)-3000 pages blackPallet dimensions47.24 x 39.37 x 102.56 in (NA), 47.24 x 39.37 x 83.27 in (EMEA, AP)Pallet dimensions (W x D x H)1200 x 1000 x 2605 mm (NA), 1200 x 1000 x 2115 mm (EMEA, AP)Pallet weight1072.9 lb (NA), 868.3 lb (EMEA, AP)Pallet weight0ptional third 550-sheet trayPaper handling input, optional0ptional third 550-sheet input tray 2; 50-sheet Automatic Document Feeder (ADF)Paper handling output, standard150-sheet output binPaper trays, maximum3Paper trays, standard2Power110-volt input voltage: 110 to 127 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); 220-volt input voltage: 220 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); 220-volt input voltage: 220 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); 220-volt input voltage: 220 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); 220-volt input voltage: 220 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); 220-volt input voltage: 220 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); 220-volt input voltage: 220 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); 220-volt input voltage: 220 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); 220-volt input voltage: 220 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); 220-volt input voltage: 220 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); 220-volt input voltage: 220 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); 220-volt input voltage: 220 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); 220-volt input voltage: 220 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); 220-volt input voltage: 220 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); 220-volt input voltage: 220 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); 220-volt input voltage: 220 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); 220-volt input voltage: 220 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); 	Package weight	34.1 lb
Pallet dimensions (W x D x H)1200 x 1000 x 2605 mm (NA), 1200 x 1000 x 2115 mm (EMEA, AP)Pallet weight1072.9 lb (NA), 868.3 lb (EMEA, AP)Pallet weight487.7 kg (NA), 394.7 kg (EMEA, AP)Paper handling input, optionalOptional third 550-sheet trayPaper handling input, standard100-sheet tray 1, 250-sheet input tray 2; 50-sheet Automatic Document Feeder (ADF)Paper handling output, standard150-sheet output binPaper trays, maximum3Paper trays, standard2Power110-volt input voltage: 110 to 127 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); 220-volt input voltage: 220 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); (Not dual voltage, product varies by part number with # Option code identifier)Print colorsNoPrint languagesHP PCL 6, HP PCL 5e, HP postscript level 3 emulation, PDF, URF, Native Office, PWG RasterPrint quality black (normal)Normal (native 600 x 600 dpi; enhanced up to 4800 x 600 dpi)Print speed black (Landscape, AS)Up to 63 ppmUp to 14 ppm140 to 14 ppm		~3000 pages black
Pallet weight1072.9 lb (NA), 868.3 lb (EMEA, AP)Pallet weight487.7 kg (NA), 394.7 kg (EMEA, AP)Paper handling input, optional0ptional third 550-sheet trayPaper handling input, standard100-sheet tray 1, 250-sheet input tray 2; 50-sheet Automatic Document Feeder (ADF)Paper handling output, standard150-sheet output binPaper trays, maximum3Paper trays, standard2Paper trays, standard2Power110-volt input voltage: 110 to 127 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); 220-volt input voltage: 220 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); Not dual voltage, product varies by part number with # Option code identifier)Print TechnologyLaserPrint languagesMP PCL 6, HP PCL 5e, HP postscript level 3 emulation, PDF, URF, Native Office, PWG RasterPrint quality black (normal)Normal (native 600 x 600 dpi; enhanced up to 4800 x 600 dpi)Print speed black (Landscape, A5)Up to 63 ppmPrint speed black (Portrait, A5)Up to 14 ppm	Pallet dimensions	47.24 x 39.37 x 102.56 in (NA), 47.24 x 39.37 x 83.27 in (EMEA, AP)
Pallet weight487.7 kg (NA), 394.7 kg (EMEA, AP)Paper handling input, optionalOptional third 550-sheet trayPaper handling input, standard100-sheet tray 1, 250-sheet input tray 2; 50-sheet Automatic Document Feeder (ADF)Paper handling output, standard150-sheet output binPaper trays, maximum3Paper trays, standard2Power110-volt input voltage: 110 to 127 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); 220-volt input voltage: 220 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); 220-volt input voltage: 220 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); 220-volt input voltage: 20 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); 20-volt input voltage: 20 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); 20-volt input voltage: 20 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); 20-volt input voltage: 20 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); 20-volt input voltage: 20 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); 20-volt input voltage: 20 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); 20-volt input voltage: 20 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); 20-volt input voltage: 20 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); 20-volt input voltage: 20 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); 20-volt input voltage: 20 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); 20-volt input voltage: 20 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); 20-volt input voltage: 20 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); 20-volt input voltage: 20 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); 20-volt input voltage: 20 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); 20-volt input voltage: 20 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); 20-volt input voltage: 20 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); 20-volt input voltage: 20 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); 20-volt input voltage: 20 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); <br< th=""><th>Pallet dimensions (W x D x H)</th><th>1200 x 1000 x 2605 mm (NA), 1200 x 1000 x 2115 mm (EMEA, AP)</th></br<>	Pallet dimensions (W x D x H)	1200 x 1000 x 2605 mm (NA), 1200 x 1000 x 2115 mm (EMEA, AP)
Paper handling input, optionalOptional third 550-sheet trayPaper handling input, standard100-sheet tray 1, 250-sheet input tray 2; 50-sheet Automatic Document Feeder (ADF)Paper handling output, standard150-sheet output binPaper trays, maximum3Paper trays, standard2Power110-volt input voltage: 110 to 127 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); 220-volt input voltage: 220 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); (Not dual voltage, product varies by part number with # Option code identifier)Print TechnologyLaserPrint colorsNoPrint languagesHP PCL 6, HP PCL 5e, HP postscript level 3 emulation, PDF, URF, Native Office, PWG RasterPrint resolution black (fine lines)Fine Lines (1200 x 1200 dpi)Print speed black (Landscape, A5)Up to 13 ppm	Pallet weight	1072.9 lb (NA), 868.3 lb (EMEA, AP)
Paper handling input, standard100-sheet tray 1, 250-sheet input tray 2; 50-sheet Automatic Document Feeder (ADF)Paper handling output, standard150-sheet output binPaper trays, maximum3Paper trays, standard2Power110-volt input voltage: 110 to 127 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); 220-volt input voltage: 220 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); (Not dual voltage, product varies by part number with # Option code identifier)Print TechnologyLaserPrint colorsNoPrint languagesMormal (native 600 x 600 dpi; enhanced up to 4800 x 600 dpi)Print resolution black (fine lines)Fine Lines (1200 x 1200 dpi)Print speed black (Portrait, A5)Up to 14 ppm	Pallet weight	487.7 kg (NA), 394.7 kg (EMEA, AP)
Paper handling input, standardFeeder (ADF)Paper handling output, standard150-sheet output binPaper trays, maximum3Paper trays, standard2Power110-volt input voltage: 110 to 127 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); 220-volt input voltage: 220 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); 220-volt input voltage: 220 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); (Not dual voltage, product varies by part number with # Option code identifier)Print TechnologyLaserPrint colorsNoPrint languagesHP PCL 6, HP PCL 5e, HP postscript level 3 emulation, PDF, URF, Native Office, PWG RasterPrint resolution black (fine lines)Fine Lines (1200 x 1200 dpi)Print speed black (Landscape, A5)Up to 63 ppmPrint speed black (Portrait, A5)Up to 14 ppm	Paper handling input, optional	Optional third 550-sheet tray
Paper trays, maximum3Paper trays, standard2Power110-volt input voltage: 110 to 127 VAC (*/- 10%), 50/60 Hz (*/- 2 Hz); 220-volt input voltage: 220 to 240 VAC (*/- 10%), 50/60 Hz (*/- 2 Hz); (Not dual voltage, product varies by part number with # Option code identifier)Print TechnologyLaserPrint colorsNoPrint languagesNP PCL 6, HP PCL 5e, HP postscript level 3 emulation, PDF, URF, Native Office, PWG RasterPrint quality black (normal)Normal (native 600 x 600 dpi; enhanced up to 4800 x 600 dpi)Print resolution black (fine lines)Fine Lines (1200 x 1200 dpi)Print speed black (Landscape, A5)Up to 63 ppm	Paper handling input, standard	100-sheet tray 1, 250-sheet input tray 2; 50-sheet Automatic Document Feeder (ADF)
Paper trays, standard2Power10-volt input voltage: 10 to 127 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); 20-volt input voltage: 220 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); 20-volt input voltage: 220 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); 20-volt input voltage: 220 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); 	Paper handling output, standard	150-sheet output bin
Power110-volt input voltage: 110 to 127 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); 220-volt input voltage: 220 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz); 220-volt input voltage, product varies by part number with # Option code identifier)Print TechnologyLaserPrint colorsNoPrint languagesHP PCL 6, HP PCL 5e, HP postscript level 3 emulation, PDF, URF, Native Office, PWG RasterPrint quality black (normal)Normal (native 600 x 600 dpi; enhanced up to 4800 x 600 dpi)Print speed black (Landscape, A5)Up to 63 ppmPrint speed black (Portrait, A5)Up to 14 ppm	Paper trays, maximum	3
Power220-volt input voltage: 220 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz) Not dual voltage, product varies by part number with # Option code identifier)Print TechnologyLaserPrint colorsNoPrint languagesHP PCL 6, HP PCL 5e, HP postscript level 3 emulation, PDF, URF, Native Office, PWG RasterPrint quality black (normal)Normal (native 600 x 600 dpi; enhanced up to 4800 x 600 dpi)Print speed black (Landscape, A5)Up to 63 ppmPrint speed black (Portrait, A5)Up to 14 ppm	Paper trays, standard	2
Print colors No Print languages HP PCL 6, HP PCL 5e, HP postscript level 3 emulation, PDF, URF, Native Office, PWG Raster Print quality black (normal) Normal (native 600 x 600 dpi; enhanced up to 4800 x 600 dpi) Print resolution black (fine lines) Fine Lines (1200 x 1200 dpi) Print speed black (Landscape, A5) Up to 63 ppm Up to 14 ppm Up to 14 ppm	Power	220-volt input voltage: 220 to 240 VAC (+/- 10%), 50/60 Hz (+/- 2 Hz) (Not dual voltage, product varies by part number with # Option code
Print languagesBP PCL 6, HP PCL 5e, HP postscript level 3 emulation, PDF, URF, Native Office, PWG RasterPrint quality black (normal)Normal (native 600 x 600 dpi; enhanced up to 4800 x 600 dpi)Print resolution black (fine lines)Fine Lines (1200 x 1200 dpi)Print speed black (Landscape, A5)Up to 63 ppmPrint speed black (Portrait, A5)Up to 14 ppm	Print Technology	Laser
Print tanguagesOffice, PWG RasterPrint quality black (normal)Normal (native 600 x 600 dpi; enhanced up to 4800 x 600 dpi)Print resolution black (fine lines)Fine Lines (1200 x 1200 dpi)Print speed black (Landscape, A5)Up to 63 ppmPrint speed black (Portrait, A5)Up to 14 ppm	Print colors	No
Print resolution black (fine lines)Fine Lines (1200 x 1200 dpi)Print speed black (Landscape, A5)Up to 63 ppmPrint speed black (Portrait, A5)Up to 14 ppm	Print languages	
Print speed black (Landscape, A5)Up to 63 ppmPrint speed black (Portrait, A5)Up to 14 ppm	Print quality black (normal)	Normal (native 600 x 600 dpi; enhanced up to 4800 x 600 dpi)
Print speed black (Portrait, A5) Up to 14 ppm	Print resolution black (fine lines)	Fine Lines (1200 x 1200 dpi)
	Print speed black (Landscape, A5)	Up to 63 ppm
Print speed duplex (A4) Up to 31 ipm	Print speed black (Portrait, A5)	Up to 14 ppm
	Print speed duplex (A4)	Up to 31 ipm

Print speed duplex (letter)	Up to 33 ipm
Print speed footnote number (A5)	[9]
Print technology	Laser
Printer Management	HP Printer Assistant, HP Utility (Mac), HP Device Toolbox, HP Web JetAdmin Software, HP JetAdvantage Security Manager, HP SNMP Proxy Agent, HP WS Pro Proxy Agent, Printer Administrator Resource Kit for HP Universal Print Driver (Driver Configuration Utility - Driver Deployment Utility - Managed Printing Administrator)
Processor speed	1200 MHz
Product long name specifications	HP LaserJet Pro MFP M428fdn - Print, Copy, Scan, and Fax; Prints up to 40 ppm (Letter); Scan to email/Folder/USB/Cloud; Up to 80,000 page duty cycle; 750-4,000 recommended monthly page volume; Gigabit ethernet networking; Auto-duplex printing; Single-pass 2 sided scanning
Quantity per pallet	30 (NA), 24 (EMEA,AP)
RMN number	SHNGC-1801-00
Recommended media weight (duplex)	60 to 120 g/m²
Recommended media weight (duplex)	16 to 32 lb
Recommended monthly page volume	750 to 4000 ^[12]
Recommended monthly scan volume	750 to 4000
Recommended monthly scan volume note	750 - 4,000
Recommended operating humidity range	30 to 70% RH
Recommended operating temperature range	15 to 27℃
Recommended operating temperature range	59 to 80.6°F
Resolution	Up to 1200 x 1200 dpi
Resolution (black and white, standard mode)	203 x 98 dpi
Resolution (black and white, superfine mode)	Up to 300 x 300 dpi (no halftone)
Resolution (black photo grayscale)	300 x 300 dpi (halftone)
Right margin (A4)	4 mm
Safety	IEC 60950-1:2005 +A1:2009+A2:2013/EN 60950-1:2006 +A11:2009+A1:2010+A12:2011+A2:2013; IEC 60825-1:2014/EN 60825- 1:2014 (Class 1 Laser/LED Product); IEC 62479:2010/EN 62479:2010;
Scan resolution, hardware	Flatbed (Up to 1200 x 1200 dpi); ADF (Up to 300 x 300 dpi)
Scan resolution, optical	Up to 1200 x 1200 dpi

Scan size (ADF), maximum	216 x 356 mm
Scan size (ADF), maximum	8.5 x 14 in
Scan size (ADF), minimum	4 x 6 in
Scan size (ADF), minimum	102 x 152 mm
Scan size, maximum	216 x 297 mm
Scan size, maximum	8.5 x 11.7 in
Scan speed duplex (normal, A4)	Up to 46 ipm (b&w), up to 34 ipm (color)
Scan speed duplex (normal, letter)	Up to 49 ipm (b&w), up to 36 ipm (color)
Security management	Secure Boot, Secure Firmware Integrity, Runtime Code Integrity, password protected EWS, secure browsing via SSL/TLS 1.0, TLS 1.1, TLS 1.2; IPP over TLS; Network: enable/disable network ports and features, unused protocol and service disablement, SNMPv1, SNMPv2, and SNMPv3, community password change; HP ePrint: HTTPS with certificate validation, HTTP Basic Access Authentication, SASL authentication; LDAP authentication and authorization; Firewall and ACL; control panel lock, certificates configuration, UPD PIN printing, Syslog, signed firmware, administrator settings, access control, 802.1x authentication (EAP-TLS, and PEAP); Encrypted data storage; Secure data erase; Automatic firmware updates; Secure Encrypted Print via optional job storage, compatible with optional HP JetAdvantage Security Manager
Software scan file format	Windows HP Scan SW supports PDF, searchable PDF, JPG, RTF, TXT, BMP, PNG, TIFF. Mac HP Easy Scan SW supports PDF, searchable PDF, JPG, RTF, TXT, JPG-2000, PNG, TIFF;
Standard media sizes (duplex)	A4; Oficio; Letter; Legal
Standard media sizes (duplex) Standard media sizes (duplex, imperial)	A4; Oficio; Letter; Legal Letter; Legal; Oficio; A4
Standard media sizes (duplex,	
Standard media sizes (duplex, imperial) Standard output capacity	Letter; Legal; Oficio; A4
Standard media sizes (duplex, imperial) Standard output capacity (envelopes) Storage device and direct print	Letter; Legal; Oficio; A4 Up to 10 envelopes USB Printing; Optional job storage via external rear host USB port
Standard media sizes (duplex, imperial) Standard output capacity (envelopes) Storage device and direct print support	Letter; Legal; Oficio; A4 Up to 10 envelopes USB Printing; Optional job storage via external rear host USB port (Minimum 16GB)
Standard media sizes (duplex, imperial)Standard output capacity (envelopes)Storage device and direct print supportStorage temperature range	Letter; Legal; Oficio; A4 Up to 10 envelopes USB Printing; Optional job storage via external rear host USB port (Minimum 16GB) -4 to 104°F
 Standard media sizes (duplex, imperial) Standard output capacity (envelopes) Storage device and direct print support Storage temperature range Storage temperature range 	Letter; Legal; Oficio; A4 Up to 10 envelopes USB Printing; Optional job storage via external rear host USB port (Minimum 16GB) -4 to 104°F -20 to 40°C
 Standard media sizes (duplex, imperial) Standard output capacity (envelopes) Storage device and direct print support Storage temperature range Storage temperature range SureSupply supported 	Letter; Legal; Oficio; A4 Up to 10 envelopes USB Printing; Optional job storage via external rear host USB port (Minimum 16GB) -4 to 104°F -20 to 40°C Yes
 Standard media sizes (duplex, imperial) Standard output capacity (envelopes) Storage device and direct print support Storage temperature range Storage temperature range SureSupply supported Target user and print volume 	Letter; Legal; Oficio; A4 Up to 10 envelopes USB Printing; Optional job storage via external rear host USB port (Minimum 16GB) -4 to 104°F -20 to 40°C Yes For teams up to 10 users; Prints up to 4,000 pages/month
 Standard media sizes (duplex, imperial) Standard output capacity (envelopes) Storage device and direct print support Storage temperature range Storage temperature range Storage temperature range SureSupply supported Target user and print volume Tariff numbers Telecom compliance (fax 	Letter; Legal; Oficio; A4 Up to 10 envelopes USB Printing; Optional job storage via external rear host USB port (Minimum 16GB) -4 to 104°F -20 to 40°C Yes For teams up to 10 users; Prints up to 4,000 pages/month (AM) 8443310000; (EU) 8443310000; (AP) 84433131 Fax Telecom: ETSI ES 203 021; FCC Rules and Regulations 47 CFR Part 68;
 Standard media sizes (duplex, imperial) Standard output capacity (envelopes) Storage device and direct print support Storage temperature range Storage temperature range SureSupply supported Target user and print volume Tariff numbers Telecom compliance (fax capability) 	Letter; Legal; Oficio; A4 Up to 10 envelopes USB Printing; Optional job storage via external rear host USB port (Minimum 16GB) -4 to 104°F -20 to 40°C Yes For teams up to 10 users; Prints up to 4,000 pages/month (AM) 8443310000; (EU) 8443310000; (AP) 84433131 Fax Telecom: ETSI ES 203 021; FCC Rules and Regulations 47 CFR Part 68; Other Telecom approvals as required by individual countries.
 Standard media sizes (duplex, imperial) Standard output capacity (envelopes) Storage device and direct print support Storage temperature range Target user and print volume Tariff numbers Telecom compliance (fax capability) Top key features 	Letter; Legal; Oficio; A4 Up to 10 envelopes USB Printing; Optional job storage via external rear host USB port (Minimum 16GB) -4 to 104°F -20 to 40°C Yes For teams up to 10 users; Prints up to 4,000 pages/month (AM) 8443310000; (EU) 8443310000; (AP) 84433131 Fax Telecom: ETSI ES 203 021; FCC Rules and Regulations 47 CFR Part 68; Other Telecom approvals as required by individual countries. Scan to email; Two-sided scanning
 Standard media sizes (duplex, imperial) Standard output capacity (envelopes) Storage device and direct print support Storage temperature range Storage temperature range Storage temperature range Storage temperature range Target user and print volume Tariff numbers Telecom compliance (fax capability) Top key features Top margin (A4) 	Letter; Legal; Oficio; A4Up to 10 envelopesUSB Printing; Optional job storage via external rear host USB port (Minimum 16GB)-4 to 104°F-20 to 40°CYesFor teams up to 10 users; Prints up to 4,000 pages/month(AM) 8443310000; (EU) 8443310000; (AP) 84433131Fax Telecom: ETSI ES 203 021; FCC Rules and Regulations 47 CFR Part 68; Other Telecom approvals as required by individual countries.Scan to email; Two-sided scanning5 mm

UPC number	(696) 194441428988; (697) 194441428995; (AB0) 192018914889; (ABT) 192018914919; (ABY) 192018914926; (AC8) 194441429008; (ACQ) 192018914933; (B13) 192018914940; (B19) 192018914957; (BAZ) 192018914964; (BBU) 192018914896; (BGJ) 192018914971; (BGM) 192018914902
Warm-up time	As fast as 45 sec
Waste electrical and electronic weight	12.6 kg
Web address for additional information	http://www.hp.com/go/support

[2] Power requirements are based on the country/region where the printer is sold. Do not convert operating voltages. This will damage the printer and void the product warranty. Power consumption values typically based on measurement of 115 V device.

[3] Toner cartridges designed for distribution and use within a designated region only; will not work outside of designated region.

[11] Duty cycle is defined as the maximum number of pages per month of imaged output. This value provides a comparison of product robustness in relation to other HP LaserJet or HP Color LaserJet devices, and enables appropriate deployment of printers and MFPs to satisfy the demands of connected individuals or groups.

[12] HP recommends that the number of pages per month of imaged output be within the stated range for optimum device performance, based on factors including supplies replacement intervals and device life over an extended warranty period

[15] Rates achieved with Fast(V.34), standard resolution and simple images.

[16] EPEAT® registered where applicable. EPEAT registration varies by country. See http://www.epeat.net for registration status by country.

[17] In box cartridge yields 3,000 black pages based on ISO/IWC 19752 and continuous printing. Actual yields vary considerably based on images printed and other factors. For details see: http://www.hp.com/go/learnaboutsupplies. Pages may vary based on customer printing conditions and usage.

[18] TEC is equal to Best TEC. Power requirements are based on the country/region where the printer is sold. Do not convert operating voltages. This will damage the printer and void the product warranty. Energy Star value typically based on measurement of 115 V device.

Accessories

Paper Handling

Input Trays

HP LaserJet Pro 550-sheet Feeder Tray

★ : Recommended

D9P29A ★

Ink/Toner/Paper/Printer Supplies

HP Laser Toner Cartridges and Kits

★ : Recommended

HP Black and White Laser Toner Printer Cartridges

HP 58A Black Original LaserJet Toner Cartridge	CF258A
HP 58X High Yield Black Original LaserJet Toner Cartridge	CF258X
HP 59A Black Original LaserJet Toner Cartridge	CF259A
HP 59X High Yield Black Original LaserJet Toner Cartridge	CF259X
HP 76A Black Original LaserJet Toner Cartridge	CF276A
HP 76X High Yield Black Original LaserJet Toner Cartridge	CF276X
HP 77A Black Original LaserJet Toner Cartridge	CF277A
HP 77X High Yield Black Original LaserJet Toner Cartridge	CF277X

HP Paper Designed for Laser Printers

HP Laser Everyday Paper

HP Everyday Laser Glossy FSC Paper 120 gsm-150 sht/A3/297 x 420 mm	7MV81A
HP Everyday Laser Glossy FSC Paper 120 gsm-150 sht/A4/210 x 297 mm	7MV82A
HP Everyday Laser Glossy FSC Paper 120 gsm-150 sht/Letter 8.5 x 11 in	4WN08A
HP Everyday Laser Glossy FSC Paper 120 gsm-150 sht/Tabloid/11 x 17 in	4WN07A

HP Professional Laser Paper

HP Professional Glossy Laser Paper 120 gsm-250 sht/A3/297 x 420 mm	CG969A
HP Professional Glossy Laser Paper 150 gsm-150 sht/A4/210 x 297 mm	CG965A
HP Professional Laser Glossy FSC Paper 200 gsm-150 sht/A4/210 x 297 mm	7MV83A
HP Professional Laser Glossy FSC Paper 200 gsm-150 sht/Letter/8.5 x 11 in	4WN10A
HP Professional Laser Matte FSC Paper 200 gsm-150 sht/A4/210 x 297 mm	7MV80A
HP Professional Laser Matte FSC Paper 200 gsm-150 sht/Letter/8.5 x 11 in	4WN05A

Solutions

JetAdvantage Printing Solutions

 \star : Recommended

JetAdvantage Print Management

HP JetAdvantage Insights

HP Universal Print Driver

HPJETADINSIGHTS

HPUNIVPRNTDRV

Disclaimer — Copyright

© Copyright 2020 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Generated by Dynamic Collateral Tool – (ww-en) – Oct 07, 2020 6:07 AM UTC+0000