# **MECHANICAL CONTROL MODELS**

### ZWN432 / ZDE3SR / ZDG3SR



Huebsch<sup>®</sup> washers and dryers are designed, tested and built to deliver 25 years of commercial-grade performance in your home. Our mechanical timer models offer the perfect balance of simplicity and longevity by combining an easy-to-operate control with long-lasting commercial quality.

#### **BUILT BETTER TO LAST LONGER**

- Constructed with premium, metal components
- » Tested to deliver 25 years of commercialgrade performance
- » Three-coat, commercial-grade finish keeps machine's looking new for years to come
- » Galvanized steel cylinder won't corrode, chip or crack
- » 3.3 cu. ft. stainless steel tub won't corrode, chip, crack or pit with normal use

#### **CLEANER CLOTHES**

- » Perfected mechanical action moves more laundry through the water
- » A 210-degree agitator with 68 strokes per minute provides maximum waterto-laundry contact
- » Tub spins during draining to prevent dirt from being left behind

#### THE ULTIMATE DRY


- » Ideally balances temperature, airflow and mechanical action
- » Quiet, highly efficient blower for faster dry times

#### TRANSFERRABLE WARRANTY

- » Industry-leading 3-year warranty
- » Covers all parts and in-home labor









## **MECHANICAL CONTROL MODEL SPECIFICATIONS**

Model Number	WASHER ZWN432SP- 113CW01	DRYER ZDE3SRGS- 173CW01	DRYER ZDG3SRGS- 113CW01
Load (Front/Top)	Тор	Front	Front
Control Location (Front/Rear)	Rear	Rear	Rear
Color	White	White	White
Outer Draintub/Cylinder Material	Porcelain	Commercial Steel	Commercial Steel
Extra-Large Door Opening	N/A	2.06 sq. ft.	2.06 sq. ft.
Width - in	25 5/8	26 7/8	26 7/8
Depth - in	28	28	28
Height - in	43	43	43
Work Surface Height - in	36	36	36
Approx. Shipping Weight - Ib	195	140	145
Preset Cycles	4	3	3
Motor Size - HP	0.5	1/3	1/3
Electrical Requirements	120V/60/1	240V/60/1	120V/60/1
Breaker Size	15 Amp	30 Amp	15 Amp
Temperature Selections	3	3	3
Agency Approvals	cULus	cULus, CSAus St	ar, MA Gas Board
Washer Only			
Stainless Steel Washtub - cu ft	3.3		
Flex Vane Agitator	Yes		
Cabinet Material	Galvanized Steel		
Tuff Guard Coated Top	Yes		
10" Stainless Steel Hinge	N/A		
Average Water Consumption - gal	20.0		
Motor Speeds	2		
Max Spin Speed - RPM	710		
G-Force	150		
Fill Hoses Included	Yes		
Automatic Balancing System	Yes		
Rear Self-Leveling Legs	Yes		
Variable Water Level Selector	Yes		
Extra Rinse Option	Yes		
Bleach Dispenser	Yes		
Fabric Softener Dispenser	Yes		
Prewash	Yes		
Soak	Yes		
Dryer Only			
Electric / Gas		Electric	Gas
Secured Lint Filter		Yes	Yes
Reversible Door		Yes	Yes
Drum Capacity		7.0 cubic feet	7.0 cubic feet
Gas Consumption - BTU		N/A	22,500
Electric Heating Wattage		5,350	22,500 N/A
Automatic Dry Cycles		2	2
Multiple Vent Options		Yes	Yes
Heavy-Duty 220 cfm Exhaust Fan		Yes	Yes
Quiet, Efficient Blower		Yes	Yes
ADA Compliant		Yes	Yes







#### **ABOUT HUEBSCH°**

Huebsch laundry equipment is designed, built and tested to deliver 25 years of commercialgrade performance. We use metal components where others use plastic. We rigorously test our products beyond their limit to ensure consistent, reliable performance and superior wash results. And because we make no distinction between the machines we engineer for use in commercial applications and the machines we offer for the home, you can be sure that your Huebsch equipment is built better to last longer.



For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications are subject to change without notice. The quality management system of Alliance Laundry Systems' Ripon facility has been registered to ISO 9001:2008. Printed in the USA.