

6 ft USB to DB25 Parallel Printer Adapter Cable - M/F

Product ID: ICUSB1284D25



The ICUSB1284D25 6 ft USB to DB25 Parallel Printer Adapter Cable turns an available USB port on a host PC into a DB25 Female Parallel port - allowing you to connect a DB25 printer to the computer as if the necessary parallel port was built-on.

A cost-effective and reliable solution, the USB to DB25 adapter saves the expense of replacing a parallel printer for the sake of USB capability.

Backed by a StarTech.com 2-year warranty and free lifetime technical support .





Certifications, Reports and Compatibility











Applications

- Allows you to quickly add a parallel port to your computer for use with printers with DB25 connectors
- Ideal solution for notebooks or desktops without a Parallel port

Features

- Fully Plug & Play for easy installation
- USB bus-powered operation, no external power adapter required
- Eliminates the need for manual or automatic parallel switch boxes



Data Sheet

Chipset ID		Warranty	2 Years
Performance Maximum Data Transfer Rate 1.5Mbps Connector(s) Connector A 1 - USB Type-A (4 pin) USB 2.0 Male Connector B 1 - DB-25 (25 pin, D-Sub) Female Software OS Compatibility Windows Server® 2000, 2003, 2008 R2, 2012, 2012 R2, 2016, 2019 Mac OS X® 10.6 to 10.15 Linux 2.6.x to 4.11.x LTS Versions only Environmental Humidity 0~80% RH non-condensing Operating Temperature 5°C to 40°C (41°F to 140°F) Storage Temperature -20°C to 70°C (-4°F to 158°F) Physical Characteristics Product Height 0.000 Product Length 1.8 m [6 ft] Product Width 0.000 Weight of Product 110 g [3.9 oz] Packaging Information Package Height 22 cm [8.7 in] Package Width 20 cm [7.9 in] Shipping (Package) Weight 119 g [4.2 oz]	Hardware	Bus Type	USB 2.0
Ports 1		Chipset ID	Prolific - PL2305
Performance Maximum Data Transfer Rate 1.5Mbps Connector(s) Connector A 1 - USB Type-A (4 pin) USB 2.0 Male Connector B 1 - DB-25 (25 pin, D-Sub) Female Software OS Compatibility Windows@ 98SE, ME, 2000, XP, Vista, 7, 8, 8.1, 10 Windows Server® 2000, 2003, 2008 R2, 2012, 2012 R2, 2016, 2019 Mac OS X® 10.6 to 10.15 Linux 2.6.x to 4.11.x LTS Versions only Environmental Humidity 0~80% RH non-condensing Operating Temperature 5°C to 40°C (41°F to 140°F) Storage Temperature -20°C to 70°C (-4°F to 158°F) Physical Characteristics Product Height 0.000 Product Length 1.8 m [6 ft] Product Width 0.000 Weight of Product 110 g [3.9 oz] Packaging Information Package Height 22 cm [8.7 in] Package Width 20 cm [7.9 in] Shipping (Package) Weight 119 g [4.2 oz]		Interface	Parallel
Connector(s) Connector A 1 - USB Type-A (4 pin) USB 2.0 Male Connector B 1 - DB-25 (25 pin, D-Sub) Female Software OS Compatibility Windows® 98SE, ME, 2000, XP, Vista, 7, 8, 8.1, 10 Windows Server® 2000, 2003, 2008 R2, 2012, 2012 R2, 2016, 2019 Mac OS X® 10.6 to 10.15 Linux 2.6.x to 4.11.x LTS Versions only Environmental Humidity 0~80% RH non-condensing Operating Temperature 5°C to 40°C (41°F to 140°F) Storage Temperature -20°C to 70°C (-4°F to 158°F) Physical Characteristics Product Height 0.000 Product Length 1.8 m [6 ft] Product Width 0.000 Weight of Product 110 g [3.9 oz] Packaging Information Package Height 22 cm [8.7 in] Package Width 20 cm [7.9 in] Shipping (Package) Weight 119 g [4.2 oz]		Ports	1
Connector B 1 - DB-25 (25 pin, D-Sub) Female	Performance	Maximum Data Transfer Rate	1.5Mbps
Software OS Compatibility Windows® 98SE, ME, 2000, XP, Vista, 7, 8, 8.1, 10 Windows Server® 2000, 2003, 2008 R2, 2012, 2012 R2, 2016, 2019 Mac OS X® 10.6 to 10.15 Linux 2.6x to 4.11.x LTS Versions only Environmental Humidity 0~80% RH non-condensing Operating Temperature 5°C to 40°C (41°F to 140°F) Storage Temperature -20°C to 70°C (-4°F to 158°F) Physical Characteristics Product Height 0.000 Product Length 1.8 m [6 ft] Product Width 0.000 Weight of Product 110 g [3.9 oz] Packaging Information Package Height 22 mm [0.9 in] Package Width 20 cm [7.9 in] Shipping (Package) Weight 119 g [4.2 oz]	Connector(s)	Connector A	1 - USB Type-A (4 pin) USB 2.0 Male
Windows Server® 2000, 2003, 2008 R2, 2012, 2012 R2, 2016, 2019 Mac OS X® 10.6 to 10.15 Linux 2.6.x to 4.11.x LTS Versions only Environmental Humidity Operating Temperature Soc to 40°C (41°F to 140°F) Storage Temperature -20°C to 70°C (-4°F to 158°F) Physical Characteristics Product Height O.000 Product Length 1.8 m [6 ft] Product Width O.000 Weight of Product 110 g [3.9 oz] Packaging Information Package Height 22 cm [8.7 in] Package Width Shipping (Package) Weight 119 g [4.2 oz]		Connector B	1 - DB-25 (25 pin, D-Sub) Female
Operating Temperature 5°C to 40°C (41°F to 140°F) Storage Temperature -20°C to 70°C (-4°F to 158°F) Physical Cable Length 1.8 m [6 ft] Product Height 0.000 Product Length 1.8 m [6 ft] Product Width 0.000 Weight of Product 110 g [3.9 oz] Packaging Information Package Height 22 cm [8.7 in] Package Width 20 cm [7.9 in] Shipping (Package) Weight 119 g [4.2 oz]	Software	OS Compatibility	Windows Server® 2000, 2003, 2008 R2, 2012, 2012 R2, 2016, 2019 Mac OS X® 10.6 to 10.15
Physical Characteristics Cable Length Product Height Product Length Product Width Product Width Neight of Product Packaging Information Package Length Package Width Shipping (Package) Weight Pacy C to 70°C (-4°F to 158°F) 1.8 m [6 ft] 1.8 m [6 ft] 1.8 m [6 ft] 1.8 m [6 ft] 2.000 1.8 m [6 ft] 2.000 1.8 m [6 ft] 2.000	Environmental	Humidity	0~80% RH non-condensing
Physical CharacteristicsCable Length1.8 m [6 ft]Product Height0.000Product Length1.8 m [6 ft]Product Width0.000Weight of Product110 g [3.9 oz]Packaging InformationPackage Height22 mm [0.9 in]Package Length22 cm [8.7 in]Package Width20 cm [7.9 in]Shipping (Package) Weight119 g [4.2 oz]		Operating Temperature	5°C to 40°C (41°F to 140°F)
Characteristics Product Height 0.000 Product Length 1.8 m [6 ft] Product Width 0.000 Weight of Product 110 g [3.9 oz] Packaging Information Package Height 22 mm [0.9 in] Package Length 22 cm [8.7 in] Package Width 20 cm [7.9 in] Shipping (Package) Weight 119 g [4.2 oz]		Storage Temperature	-20°C to 70°C (-4°F to 158°F)
Product Length Product Width 0.000 Weight of Product 110 g [3.9 oz] Packaging Information Package Length Package Width Package Width Shipping (Package) Weight 1.8 m [6 ft] 0.000 22 mm [0.9 in] 22 mm [0.9 in] 110 g [3.9 oz] 110 g [3.9 oz]	-	Cable Length	1.8 m [6 ft]
Product Width Weight of Product 110 g [3.9 oz] Packaging Information Package Height 22 mm [0.9 in] Package Length Package Width 20 cm [7.9 in] Shipping (Package) Weight 119 g [4.2 oz]		Product Height	0.000
Weight of Product 110 g [3.9 oz] Packaging Information Package Height 22 mm [0.9 in] Package Length 22 cm [8.7 in] Package Width 20 cm [7.9 in] Shipping (Package) Weight 119 g [4.2 oz]		Product Length	1.8 m [6 ft]
Packaging Information Package Height Package Length Package Width Package Width Shipping (Package) Weight Package Midth 119 g [4.2 oz]		Product Width	0.000
Package Length 22 cm [8.7 in] Package Width 20 cm [7.9 in] Shipping (Package) Weight 119 g [4.2 oz]		Weight of Product	110 g [3.9 oz]
Package Width 20 cm [7.9 in] Shipping (Package) Weight 119 g [4.2 oz]	Packaging Information	Package Height	22 mm [0.9 in]
Shipping (Package) Weight 119 g [4.2 oz]		Package Length	22 cm [8.7 in]
		Package Width	20 cm [7.9 in]
What's in the Box Included in Package 1 - USB to Parallel Adapter Cable		Shipping (Package) Weight	119 g [4.2 oz]
	What's in the Box	Included in Package	1 - USB to Parallel Adapter Cable

Product appearance and specifications are subject to change without notice.