

USB-C to Parallel Printer Cable

Product ID: ICUSBCPLLD25



This USB-C™ to parallel printer cable allows you to connect your USB-C enabled laptop or desktop computer to a DB25 printer.

Cost-saving solution

A cost-effective and reliable solution, the USB to DB25 adapter saves you the expense of replacing a parallel printer for the sake of USB compatibility. It turns an available USB-C port on your laptop or desktop computer into a DB25 female parallel port, allowing you to connect a DB25 printer to your computer as if the necessary parallel port was built-in.

Easy installation and portability

The printer cable is supported by a broad range of operating systems, including Windows®, Linux®, and macOS, which makes it easy to integrate into mixed OS environments. It supports plug-and-play installation, saving you time and hassle.

The printer cable is USB powered, so there's no need for an external power adapter.

The ICUSBCPLLD25 is backed by a StarTech.com 2-year warranty and free lifetime technical support.

Certifications, Reports and Compatibility



Applications

- Enables you to quickly add a parallel port to your USB-C enabled laptop or computer, for use with printers with DB25 connectors
- Ideal solution for notebooks or desktop computers lacking a parallel port

Features

- Connect your USB-C enabled laptop or desktop computer to a DB25 printer
- Compatible with Windows®, Linux®, and macOS
- Turns an available USB-C port on your laptop or desktop computer into a DB25 Female parallel port
- Easy plug-and-play installation

Hardware	Warranty	2 Years
	Bus Type	USB-C
	Chipset ID	Prolific - PL2305
	Interface	Parallel
	Ports	1
Performance	Maximum Data Transfer Rate	1.5Mbps
Connector(s)	Connector Type(s)	1 - USB Type-C (24-pin) USB 2.0 (480Mbps) Male
		1 - DB-25 (25 pin, D-Sub) Female
Software	OS Compatibility	Windows® 7, 8.1, 10 Windows Server® 2008 R2, 2012 R2, 2016 Mac OS X® 10.11 and 10.14 Linux 2.6.x to 4.4x <i>LTS Versions only</i>
Special Notes / Requirements	System and Cable Requirements	One available USB-C port
Power	Power Source	USB-Powered
Environmental	Humidity	0~80% RH non-condensing
	Operating Temperature	5°C to 40°C (41°F to 140°F)
	Storage Temperature	-20°C to 70°C (-4°F to 158°F)
Physical Characteristics	Product Length	6.1 ft [1.8 m]
	Weight of Product	3.2 oz [92 g]
Packaging Information	Package Height	0.4 in [10 mm]
	Package Length	8.7 in [22 cm]
	Package Width	7.9 in [20 cm]
	Shipping (Package) Weight	3.8 oz [108 g]
What's in the Box	Included in Package	1 - parallel printer adapter cable
		1 - quick-start guide

Product appearance and specifications are subject to change without notice.