

# Cisco GLC-EX-SMD Compatible SFP Transceiver Module - 1000BASE-EX

Product ID: GLCEXSMDST



The GLCEXSMDST is a Cisco GLC-EX-SMD compatible fiber transceiver module that has been designed, programmed and tested to work with Cisco® brand switches and routers. It delivers dependable 1 GbE connectivity over fiber cable, for 1000BASE-EX compliant networks, with a maximum distance of up to 40 km (24.8 mi).

#### **Technical Specifications:**

• Wavelength: 1310 nm

Maximum Data Transfer Rate: 1.25 Gbps

• **Type:** Single Mode Fiber

• Connection Type: LC Connector

• Maximum Transfer Distance: 40 km (24.8 mi)

MTBF: 3,013,496 hours

Power Consumption: Less than 1 Watt

Digital Diagnostics Monitoring (DDM): Yes



## **Data Sheet**

This SFP fiber module is hot-swappable, making upgrades and replacements seamless by minimizing network disruptions.

### StarTech.com SFPs

All StarTech.com SFP & SFP+ transceiver modules are backed by a lifetime warranty and free lifetime multilingual technical support. StarTech.com offers a wide variety of SFP modules and direct-attach SFP cables, providing the convenience and reliability you need to ensure dependable network performance.



# **Data Sheet**

# Certifications, Reports and Compatibility













### **Applications**

- Replacing defective or damaged SFP modules in Cisco switches and routers
- Expand your network to remote segments

#### **Features**

- 100% compatibility with Cisco GLC-EX-SMD guaranteed
- StarTech.com SFP modules are backed by a lifetime warranty
- Meets or exceeds OEM specifications and Multi-Source Agreement (MSA) industry standards
- Low power consumption of less than 1 W
- Hot-swappable with fiber-optic modules



# **Data Sheet**

	Warranty	Lifetime
Hardware	Compatible Brand	Cisco
	Industry Standards	IEEE 802.3z 1000BASE-EX
Performance	Compatible Networks	1000 Mbps (1 Gbps)
	DDM	Yes
	Fiber Operating Mode	Full-Duplex
	Max Transfer Distance	40 km (24.8 mi)
	Maximum Data Transfer Rate	1.25 Gbps
	MTBF	3,013,496 hours
	Туре	Single Mode
	Wavelength	1310nm
Connector(s)	Local Unit Connectors	1 - Fiber Optic LC Duplex Female
Special Notes / Requirements	Note	For use in Gigabit fiber networking equipment and media converters
	System and Cable Requirements	MSA or Cisco compliant SFP port
Power	Power Consumption (In Watts)	< 1 W
Physical Characteristics	Color	Silver
	Enclosure Type	Aluminum
	Product Height	0.5 in [1.3 cm]
	Product Length	2.2 in [56.6 mm]
	Product Width	0.5 in [13.7 mm]
	Weight of Product	0.7 oz [19 g]
Packaging Information	Package Height	1.3 in [32 mm]
	Package Length	4.7 in [12 cm]
	Package Width	3.6 in [92 mm]
	Shipping (Package) Weight	1.6 oz [46 g]
	Shipping (rackage) Weight	[ 9]

Product appearance and specifications are subject to change without notice.