



Overview

Presentation	Universal Sensor that monitors third-party dry contact state sensors.
Lead time	Usually Ships within 2 Weeks

General

Provided equipment	Cable ties
--------------------	------------

Physical

Depth	18.7 Cm
Height	1.9 Cm
Net weight	0.15 Kg
Width	14.6 Cm

Environmental

Ambient air temperature for operation	0...45 °C
Operating altitude	0...10000 ft
Relative humidity	0...95 %
Ambient air temperature for storage	-15...65 °C
Storage altitude	0.00...15240.00 M
Storage Relative Humidity	0...95 %

Packing Units

Package 1 Weight	0.27 Kg
Package 1 Height	4.8 Cm
Package 1 width	23.2 Cm
Package 1 Length	16.4 Cm

Offer Sustainability

EU RoHS Directive	Compliant EU RoHS Declaration
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

Product Life Status :	Commercialised
-----------------------	----------------