

2 Port SuperSpeed Mini PCI Express USB 3.0 Adapter Card w/ Bracket Kit and UASP Support

Product ID: MPEXUSB3S22B



The MPEXUSB3S22B 2-Port Mini PCI Express USB 3.0 Card with Bracket Kit adds two external USB 3.0 ports to small form-factor systems, for connecting a variety of different peripherals. The card also includes optional standard and low profile brackets to fit a rear expansion bay if needed.

The Mini PCIe USB 3.0 card supports the full SuperSpeed USB specification, with fast data transfer speeds (up to 5Gbps), as well as 900mA of power per port, making it a convenient addition for connecting your USB 3.0 peripheral devices.

Enhanced with UASP support (USB Attached SCSI Protocol), this USB 3.0 controller performs up to 70% faster than conventional USB 3.0 when paired with a [UASP supported enclosure](#) (Note: UASP requires a compatible operating system). Using a more efficient protocol than the traditional USB BOT (Bulk-Only Transport), UASP technology optimizes transfers by allowing multiple commands to be processed simultaneously, significantly increasing transfer speeds for less wait time on data transfers. See our UASP test results below for further details.

Using the Mini PCI Express (Mini Card) form factor and offering compliance with PCI Express Gen 2, this adapter card is designed for use in the latest small form factor computer systems, such as Mini-ITX or custom embedded solutions where a standard PCIe card would not fit.



Backed by a StarTech.com 2-year warranty and free lifetime technical support.

Improved Performance with UASP

UASP is supported in Windows® 8, Server 2012 and Linux kernel 2.6.3 or later. In testing UASP performed with up to a 70% faster read / 40% faster write speed over traditional USB 3.0 at peak performance.

At the same peak in testing, UASP also showed up to an 80% reduction in required processor resources.

Test results were obtained using an Intel® Ivy Bridge system, StarTech.com add-on USB 3.0 cards, a UASP-enabled StarTech.com enclosure, and a SATA III solid state drive.



Certifications, Reports and Compatibility



Applications

- System builders creating a small form factor HTPC with external USB 3.0 storage or other peripherals
- Add two USB 3.0 device connections to a mini-ITX or custom embedded system with no room for a standard PCI Express card
- Connecting external USB 3.0 storage devices for quick backup or archiving

Features

- Two external USB 3.0 type A ports
- UASP support for more efficient data transfer
- Provides up to 900mA of power per port
- Fully Compliant with USB 3.0 and Intel xHCI Specification
- Backward compatible with USB 2.0 and USB 1.0/1.1 devices
- PCI Express Base Specification 2.0 Compliant (backward compatible with 1.0a/1.1)
- Supports Control / Bulk / Interrupt / Isochronous USB Transfer Modes

Hardware	Warranty	2 Years
	Bus Type	Mini PCI Express
	Card Type	Embedded
	Chipset ID	Renesas/NEC - μ PD720202
	Industry Standards	Intel xHCI PCI Express Base Specification 2.0 (backward compatible with 1.0a/1.1)
	Interface	USB 3.0
	Ports	2
Performance	Maximum Data Transfer Rate	5 Gbps
	Type and Rate	USB 3.0 - 5 Gbit/s
	UASP Support	Yes
Connector(s)	Connector Type(s)	1 - Mini PCI Express x1 (52 pin) Male
	External Ports	2 - USB Type-A (9 pin) USB 3.0 Female
	Internal Ports	1 - IDC (20 pin, USB 3.0, Motherboard Header) Male 1 - SP4 (4 pin, Small Drive Power) Male
Software	OS Compatibility	Windows® Vista, 7, 8, 8.1, 10 Windows Server® 2008 R2, 2012, 2012 R2, 2016, 2019 Linux 2.6.31 to 4.11.x <i>LTS versions only</i>
Special Notes / Requirements	System and Cable Requirements	Available Mini PCI Express expansion slot (full length) Case/Chassis with available Low or Full profile expansion card slot
Environmental	Humidity	5~95% RH
	Operating Temperature	0°C to 55°C (32°F to 131°F)
	Storage Temperature	-20°C to 85°C (-4°F to 185°F)
Physical Characteristics	Cable Length	600 mm [23.6 in]
	Product Length	51 mm [2 in]
	Product Width	30 mm [1.2 in]
	Weight of Product	61 g [2.2 oz]
Packaging Information	Package Height	32 mm [1.3 in]

	Package Length	17.6 cm [6.9 in]
	Package Width	14.4 cm [5.7 in]
	Shipping (Package) Weight	207 g [7.3 oz]
What's in the Box	Included in Package	1 - Mini PCIe USB 3.0 Card 1 - USB Header to 2 Port Cable 1 - Low Profile Bracket 1 - Standard Profile Bracket 1 - LP4 Power Cable 1 - Screw Kit 1 - Driver CD 1 - Instruction Manual

Product appearance and specifications are subject to change without notice.