

1-Port USB 2.0 over Cat5 or Cat6 Extender Kit - Locally or Remotely Powered - 330 ft. (100 m)

Product ID: USB2001EXT2P





This single-port USB 2.0 extender lets you access and use your USB device up to 100 m away over Cat5e or Cat6 cable. And, because it can be powered by either the local or the remote unit, you have more flexibility to place your USB device exactly where you need it. It's the perfect USB extension solution for warehouses, factories, classrooms, boardrooms, homes, or offices.

Flexible power input options

Many USB-to-Ethernet extenders require that the remote unit has a power source connected for operation, which can make installation difficult. This versatile extender overcomes that restriction, letting you connect the power adapter to either the local (transmitter) unit or the remote (receiver) unit as needed.



Data Sheet

When the power adapter is connected to the local unit, the extender delivers power over your Cat5e or Cat6 cable, eliminating the need for a power adapter in the remote location. Now you have the added convenience to install your USB device even in a remote location where a power outlet is unavailable, up to 100 m away.

Eliminates hassle and smashes distance limitations

This USB extender overcomes the 16 ft. cable length limitations of traditional USB 2.0 cables, so you can create a more efficient, more flexible workspace. It's perfect for connecting webcams, printers, flash drives, and virtually any USB peripheral.

Plus, with the included power adapter, you can connect power-hungry USB devices such as external hard drives. For added installation convenience, the USB-to-Ethernet extender features built-in cable-tie slots for mounting to a pole.

Supports any operating system and older devices

The USB 2.0-over-Cat5-or-Cat6 extender is multi-platform compatible, so it supports a variety of operating systems such as Windows®, Mac, Linux® and Chrome OS™. Setup is easy with no additional drivers or software required, and the universal USB extender is backward compatible with USB 1.1 and 1.0 peripherals.

The USB2001EXT2P is backed by a StarTech.com 2-year warranty and free lifetime technical support.





Certifications, Reports and Compatibility











Applications

- Place your USB device virtually anywhere, even in locations where a power outlet is unavailable
- Use as a mid-point repeater to increase the connection distance of your USB peripheral and to reduce cable clutter
- Perfect for environments where the host computer is in an inaccessible location
- No need to run new wiring, you can extend USB connections between rooms using existing direct, in-wall Cat5 or Cat6 cable

Features

- Flexible power input, with the versatility to power the USB extender from the local unit (transmitter), or from the remote unit (receiver)
- Place your USB device exactly where you need it (up to 100 m), with this cost-effective USB-to-Ethernet extender
- Universal, multi-platform compatible, and OS independent with no drivers required, for fast, hassle-free setup
- Features built-in cable-tie slots for mounting to a pole
- Supports transfer rates of up to 480Mbps
- Supports plug-and-play operation, as well as and hot-swap and hotplugging



Data Sheet

| | Warranty | 2 Years |
|---------------------------------|-------------------------------|--|
| Hardware | Cabling | Cat 5e UTP or better |
| | Ports | 1 |
| Performance | Max Distance | 100 m / 330 ft |
| | Maximum Data Transfer Rate | 480Mbps |
| Connector(s) | Local Unit Connectors | 1 - USB B (4 pin) Female |
| | | 1 - RJ-45 Female |
| | Remote Unit Connectors | 1 - USB Type-A (4 pin) USB 2.0 Female |
| | | 1 - RJ-45 Female |
| Software | OS Compatibility | OS Independent; No additional drivers or software required |
| Special Notes / Requirements | System and Cable Requirements | A host computer with an available USB-A port (USB Type-A) |
| | | An RJ45-terminated UTP Cat5e or better Ethernet cable |
| Indicators | LED Indicators | 1 - Power |
| | | 1 - Link |
| | | 1 - Host |
| | | 1 - Activity |
| Power | Center Tip Polarity | Positive |
| | Input Current | 0.58 A |
| | Input Voltage | 100 ~ 240 AC |
| | Output Current | 1 A |
| | Output Voltage | 24 DC |
| | Plug Type | М |
| | Power Consumption (In Watts) | 24 |
| | Power Source | AC Adapter Included |
| Environmental | Humidity | 20~80% RH (Non-condensing) |
| | Operating Temperature | 0°C to 50°C (32°F to 122°F) |
| | Storage Temperature | -20°C to 70°C (-4°F to 158°F) |
| Physical Characteristics | Color | Black |
| | | |
| | Enclosure Type | Plastic |



Data Sheet

| | Product Length | 3.5 in [88 mm] |
|--------------------------|---------------------------|--|
| | Product Weight | 6 oz [171 g] |
| | Product Width | 2.6 in [65 mm] |
| Packaging Information | Shipping (Package) Weight | 2.5 lb [1.1 kg] |
| What's in the Box | Included in Package | 1 - USB 2.0 extender local unit |
| | | 1 - USB 2.0 extender remote unit |
| | | 1 - USB 2.0 cable 6.1 ft [1.8 m] |
| | | 1 - universal power adapter (NA/JP, UK, EU, ANZ) |
| | | 1 - quick-start guide |

Product appearance and specifications are subject to change without notice.