

USB-C Multiport Adapter with DVI - USB 3.0 Port - 60W PD - White

Product ID: DKT30CDVPD



This USB-C multiport adapter equips your USB-C Windows or MacBook laptop with essential connections, including a DVI output, a Gigabit Ethernet port and a USB 3.0 (Type-A) port. Plus, you can power both the adapter and your laptop simultaneously, with 60 W USB Power Delivery 2.0 and a USB-C power adapter.

All the Connections You Need

The versatile adapter combines the performance of three single-function adapters into one powerful solution.

- USB-C to DVI adapter
- USB-C Ethernet adapter
- USB-C to USB -A adapter

Add a second display through the DVI port. Get fast, reliable network access through the Gigabit Ethernet RJ45 port and connect a USB 3.0 peripheral device, such as a mouse or USB flash drive, all with one, simple-to-use device.





Charge and Power Your Laptop While You Work

The multiport adapter's USB-C port supports 60 W USB Power Delivery 2.0, so you can power and charge your laptop while you work.

Bring Productivity Wherever You Go

The USB Type-C multiport adapter is highly portable and features an integrated USB-C cable and USB-powered performance, so there's no need to carry a separate power adapter with you.

The StarTech.com Advantage for Docking Stations

- **Maximum compatibility** StarTech.com has a docking station to fit every operating system, laptop brand, and connectivity need
 - **Get more done faster** More ports and more displays maximize end user connectivity and productivity
- Quick installation eliminate deployment headaches that waste time and frustrate end users
 - **IT Grade quality** trusted by IT pros around the world for our rigorous in-house product testing, robust compliance, and lifetime multilingual technical support

The DKT30CDVPD is backed by a StarTech.com 3-year warranty and free lifetime technical support.

Note: To ensure full adapter functionality, your laptop's USB-C port must support USB Power Delivery and DP Alt Mode.





Certifications, Reports and Compatibility











Applications

- Connect your MacBook, Ultrabook™, or Chromebook™ to wired Gigabit internet, in locations where Wi-Fi® isn't available
- Integrate the compact adapter into small work spaces in offices and home offices

Features

- Provides DVI video output, a USB 3.0 port, and a Gigabit Ethernet port to your USB-C Windows or MacBook Laptop
- Power your laptop with 60W Power Delivery using this multiport adapter and a USB Type-C power adapter
- Connect your existing USB devices using the USB Type-A port Gigabit Ethernet RJ45 port supports Wake-on-LAN (WOL), jumbo frames, VLAN tagging, and Energy-Efficient Ethernet
- Thunderbolt 3 port compatible



Data Sheet

	Warranty	3 Years
Hardware	4K Support	Yes
	Audio	Yes
	Bus Type	USB-C
	Chipset ID	VIA/VLI - VL813 VIA/VLI - VL100 Parade - PS171 Realtek - RTL8153
	Displays Supported	1
	Fast-Charge Port(s)	No
	Industry Standards	IEEE 802.3, IEEE 802.3u, IEEE 802.3ab USB 3.0 - Backward compatible with USB 2.0 and 1.1
Performance	Auto MDIX	Yes
	Compatible Networks	10/100/1000 Mbps
	Full Duplex Support	Yes
	Maximum Data Transfer Rate	5 Gbps (USB 3.0) 2 Gbps (Ethernet; Full-Duplex)
	Maximum Digital Resolutions	1920 × 1200 - 60 Hz (DVI)
	Type and Rate	USB 3.0 - 5 Gbit/s
	UASP Support	Yes
Connector(s)	Connector Type(s)	1 - USB Type-C (24 pin) USB 3.0 (5Gbps) Male
		1 - DVI-I (29 pin) Female
		1 - RJ-45 Female
		1 - USB Type-A (9 pin) USB 3.0 Female
		1 - USB-C (24 pin) USB Power Delivery only Female
Software	OS Compatibility	Windows® 7, 8.1, 10 Mac OS® 10.11 to 10.14 Chrome OS $^{\text{TM}}$
Special Notes / Requirements	Note	Not all USB-C ports support the full functionality of the USB Type-C standard. Ensure that your host USB-C port supports USB Power Delivery 2.0 and DP alt mode.
		The adapter can connect to a host laptop's USB-C port that doesn't support USB Power Delivery 2.0. However, in this configuration if a power adapter is connected to the multifunction adapter, it will not pass power through to your host laptop.



Data Sheet

adapter functionality, the host USB-C port must support USB Power Delivery 2.0 and DP alt mode) Optional: USB-C power adapter (for example, your laptor USB-C based power adapter) Power Power Source USB-Powered Environmental Humidity 0~85% RH (Non-condensing) Operating Temperature 0°C to 45°C (32°F to 113°F) Storage Temperature -10°C to 70°C (14°F to 158°F) Physical Characteristics Color White Product Height 0.7 in [17 mm] Product Length 3.8 in [97 mm] Product Weight 1.8 oz [50 g] Product Width 1.6 in [41 mm] Packaging Information Adapter functionality, the host USB-C port must support USB Power 2.0 and DP alt mode) Appear 2.0 and DP alt mode) Optional: USB-C power adapter (for example, your laptor USB-C based power adapter) Appear 2.0 and DP alt mode) Optional: USB-C power adapter (for example, your laptor USB-C based power adapter) Appear 2.0 and DP alt mode) Optional: USB-C power adapter (for example, your laptor USB-C based power adapter) Power 2.0 and DP alt mode) Appear 2.0 and DP alt mode) Optional: USB-C power adapter (for example, your laptor USB-C based power adapter) Optional: USB-C power adapter (for example, your laptor USB-C based power adapter) Optional: USB-C power adapter) Optional: USB-C power adapter (for example, your laptor USB-C based power adapter) Optional: USB-C power adapter (for example, your laptor USB-C based power adapter) Optional: USB-C power adapter) Optional: USB-C power adapter) Optional: USB-C power adapter) Optional USB-C power adapter			USB 3.0 is also known as USB 3.1 Gen 1; this connectivity standard offers speeds up to 5Gbps.
Power Power Delivery 60W Power Source USB-Powered Environmental Humidity 0~85% RH (Non-condensing) Operating Temperature 0°C to 45°C (32°F to 113°F) Storage Temperature -10°C to 70°C (14°F to 158°F) Physical Cable Length 5.5 in [140 mm] Characteristics Color White Product Height 0.7 in [17 mm] Product Length 3.8 in [97 mm] Product Weight 1.8 oz [50 g] Product Width 1.6 in [41 mm] Packaging Information What's in the Box Included in Package 1 - multiport adapter		System and Cable Requirements	A host laptop with an available USB-C port (to ensure full adapter functionality, the host USB-C port must support USB Power Delivery 2.0 and DP alt mode)
Power Source USB-Powered Humidity O~85% RH (Non-condensing) Operating Temperature O°C to 45°C (32°F to 113°F) Storage Temperature -10°C to 70°C (14°F to 158°F) Physical Characteristics Color White Product Height O.7 in [17 mm] Product Length 3.8 in [97 mm] Product Weight Product Weight 1.8 oz [50 g] Product Width 1.6 in [41 mm] Packaging Information Shipping (Package) Weight 4.6 oz [130 g] What's in the Box Included in Package 1 - multiport adapter			Optional: USB-C power adapter (for example, your laptop's USB-C based power adapter)
Humidity 0~85% RH (Non-condensing) Operating Temperature 0°C to 45°C (32°F to 113°F) Storage Temperature -10°C to 70°C (14°F to 158°F) Physical Characteristics Color White Product Height 0.7 in [17 mm] Product Length 3.8 in [97 mm] Product Weight 1.8 oz [50 g] Product Width 1.6 in [41 mm] Packaging Information Physical Characteristics Included in Package 1 - multiport adapter	Power	Power Delivery	60W
Operating Temperature Storage Temperature -10°C to 70°C (14°F to 158°F) Physical Characteristics Color White Product Height O.7 in [17 mm] Product Length 3.8 in [97 mm] Product Weight Product Width 1.8 oz [50 g] Product Width 1.6 in [41 mm] Packaging Information Physical Shipping (Package) Weight 1 - multiport adapter		Power Source	USB-Powered
Storage Temperature -10°C to 70°C (14°F to 158°F) Physical Cable Length 5.5 in [140 mm] Color White Product Height 0.7 in [17 mm] Product Length 3.8 in [97 mm] Product Weight 1.8 oz [50 g] Product Width 1.6 in [41 mm] Packaging Information Physical Cable Length 5.5 in [140 mm] 4.6 oz [130 g] What's in the Box Included in Package 1 - multiport adapter	Environmental	Humidity	0~85% RH (Non-condensing)
Physical Characteristics Cable Length 5.5 in [140 mm] Color White Product Height 0.7 in [17 mm] Product Length 3.8 in [97 mm] Product Weight 1.8 oz [50 g] Product Width 1.6 in [41 mm] Packaging Information Shipping (Package) Weight 4.6 oz [130 g] What's in the Box Included in Package 1 - multiport adapter		Operating Temperature	0°C to 45°C (32°F to 113°F)
Color White Product Height 0.7 in [17 mm] Product Length 3.8 in [97 mm] Product Weight 1.8 oz [50 g] Product Width 1.6 in [41 mm] Packaging Information What's in the Box Included in Package 1 - multiport adapter		Storage Temperature	-10°C to 70°C (14°F to 158°F)
Product Height 0.7 in [17 mm] Product Length 3.8 in [97 mm] Product Weight 1.8 oz [50 g] Product Width 1.6 in [41 mm] Packaging Information Shipping (Package) Weight 4.6 oz [130 g] What's in the Box Included in Package 1 - multiport adapter	Physical Characteristics	Cable Length	5.5 in [140 mm]
Product Length 3.8 in [97 mm] Product Weight 1.8 oz [50 g] Product Width 1.6 in [41 mm] Packaging Information Shipping (Package) Weight 4.6 oz [130 g] What's in the Box Included in Package 1 - multiport adapter		Color	White
Product Weight 1.8 oz [50 g] Product Width 1.6 in [41 mm] Packaging Information What's in the Box Included in Package 1 - multiport adapter		Product Height	0.7 in [17 mm]
Product Width 1.6 in [41 mm] Packaging Information Shipping (Package) Weight 4.6 oz [130 g] What's in the Box Included in Package 1 - multiport adapter		Product Length	3.8 in [97 mm]
Packaging Shipping (Package) Weight 4.6 oz [130 g] Information What's in the Box Included in Package 1 - multiport adapter		Product Weight	1.8 oz [50 g]
Information What's in the Box Included in Package 1 - multiport adapter		Product Width	1.6 in [41 mm]
	Packaging Information	Shipping (Package) Weight	4.6 oz [130 g]
1 - instruction manual	What's in the Box	Included in Package	1 - multiport adapter
			1 - instruction manual

Product appearance and specifications are subject to change without notice.