

# Product data sheet

Specifications



## EasyPDU, Switched, Zero U, 22 kW, 230V, (18) C13 & (6) C19 ; IEC309

EPDU1232S

### Overview

Lead time	Usually in Stock
-----------	------------------

### Physical

Colour	Black
Depth	62 mm
Height	1794 mm
Net weight	8.17 kg
Width	55 mm

### Input

Input current limits	32 A
Load capacity	22 kW
Network frequency	50/60 Hz
Plug standard	IEC 60309
Plug standard	IEC 60309 32 A 3P + N + PE
Input voltage	400 V 3 phases

### Output

Number of power socket outlets	18 IEC 60320 C13 6 IEC 60320 C19
--------------------------------	-------------------------------------

### Conformance

Product certifications	CE EAC RCM TÜV
------------------------	-------------------------

### Environmental

Ambient air temperature for operation	-5...45 °C
Relative humidity	5...95 %
Operating altitude	0...3000 m
Ambient air temperature for storage	-25...65 °C

---

<b>Storage Relative Humidity</b>	5...95 %
----------------------------------	----------

---

## Packing Units

---

<b>Number of Units in Package 1</b>	1
-------------------------------------	---

---

<b>Package 1 Weight</b>	9.45 kg
-------------------------	---------

---

<b>Package 1 Height</b>	1950 mm
-------------------------	---------

---

<b>Package 1 width</b>	160 mm
------------------------	--------

---

<b>Package 1 Length</b>	110 mm
-------------------------	--------

---

## Offer Sustainability

---

<b>EU RoHS Directive</b>	Compliant <a href="#">EU RoHS Declaration</a>
--------------------------	--

---

<b>Mercury free</b>	Yes
---------------------	-----

---

<b>RoHS exemption information</b>	<a href="#">Yes</a>
-----------------------------------	---------------------

---