# INF6502WBAG



Interactive Whiteboard and Display with Capacitive Touch and Anti-Glare Part #: INF6502WBAG

Stop taking photos of your old dry-erase board and step up to a digital whiteboard. You'll never lose an idea and your meetings will be more efficient and productive. The JTouch Whiteboard is durable, affordable, and creates an engaging, interactive experience that everyone can see.

#### **Key Features**

- ♦ 65-inch 1080p touch display
- ♦ Built-in, full-featured interactive whiteboard
- Wirelessly cast from any device, browse the web, or view documents
- Multi-point capacitive touchscreen with sleek bezel-less design and effortless gestures
- Display a PC, Mac or Chromebook via HDMI and enable touch via USB
- Anti-glare screen is smooth to the touch and eliminates distracting reflections
- No calibration required

This model is available outside the Americas, and to K-12 schools in the US. If you are in the Americas and not a K-12 school, the <a href="INF6502WBAGp">INF6502WBAGp</a> is the model for you.





## Interactive Whiteboard

Draw, write, and capture notes on a multi-screen canvas, with room for free-form drawings, diagrams, and more. Multiple people can write or draw at the same time with a complete collection of digital pens, highlighters, shapes, lines, and colors, then view and annotate over PowerPoint, Word, or images.

"I frequently teach from the [JTouch] whiteboard. The students get a chance to pop up and do a problem, too. They beg to go up to show off their skills. The learning is very engaging and I am seeing a greater mastery in our multiplication unit." -- 4th Grade Teacher and JTouch Whiteboard User

"In addition to saving time, installing the interactive displays inhouse also saved the district money. The only cost of the

installation involved purchasing a mounting bracket for each display." -- K-12 TechDecisions Magazine

#### LightCast Wireless Collaboration

Use the LightCast Key to easily connect and share content from your Apple, Windows, Android, or Chrome devices. Access the internet with a built-in web browser, and view or present documents, videos, and photos.

#### **Full Touch Control**

Display your PC, Mac, or Chromebook via HDMI, VGA, or component video, then control it from the display via touch. Just enable touch from the computer via USB and easily extend the reach of your computer's USB ports with the easily accessible 4-port USB hub.

# Projected Capacitive Touch (PCAP)

The ultra-responsive and sleek bezel-less technology found in tablets and smart phones is now available in the JTouch Whiteboard. Draw or write smoothly with your finger, a stylus, or with medical grade gloves.

## Specifications\*

Display	INF6502WBAG
Diagonal Size	65"
Resolution – Native	Full HD (1920 x 1080)
Display Technology	Direct WLED backlight
Touch Screen Features	Projected capacitive, Multi-touch, Anti-glare
Glass Strength	2,5 mm d'épaisseur, traité chimiquement pour une résistance à la détérioration
Scratch Resistance	7 Mohs
Contrast Ratio	5,000:1
Display Brightness	350 cd/m2
Refresh Rate	120 Hz
Response Time	6.5 ms
Pixel Pitch	0.744 mm
Viewing Angle	176°
Speakers	Stereo 10W x 2
Display Connectors – Inputs	3.5mm microphone line in, RCA stereo audio, 3.5mm mono audio, RS232, Component video, HDMI $\times$ 4, VGA, USB-A $\times$ 4 on panel, USB-A $\times$ 2 (on bottom for embedded software)
Display Connectors – Outputs	3.5mm stereo audio, RCA stereo audio, USB-B for touchscreen control
Power Standard	AC 100 to 240V, 50/60
PC	
System	
Included Accessories	Power cord, Remote, Stylus, VGA cable, Quick Start Guide, USB A-B cable, LightCast Key
Wireless Collaboration	LightCast-Ready
	< 40 dBA at 77°F / 25°C
Audible Noise	140 dbA at 771 / 25 C
Audible Noise  Operating Conditions	32 to 104°F at 0 to 10000 ft / 0 to 40°C at 0 to 3048 m
	32 to 104°F at 0 to 10000 ft /
Operating Conditions	32 to 104°F at 0 to 10000 ft / 0 to 40°C at 0 to 3048 m
Operating Conditions  Mounting Pattern	32 to 104°F at 0 to 10000 ft / 0 to 40°C at 0 to 3048 m VESA 400×400mm with M8 screws
Operating Conditions  Mounting Pattern  Product Warranty	32 to 104°F at 0 to 10000 ft / 0 to 40°C at 0 to 3048 m VESA 400×400mm with M8 screws 2 years 35.2 x 59.9 x 3.2 in /
Operating Conditions  Mounting Pattern  Product Warranty  Product Dimensions	32 to 104°F at 0 to 10000 ft / 0 to 40°C at 0 to 3048 m  VESA 400×400mm with M8 screws 2 years  35.2 x 59.9 x 3.2 in / 895.1 x 1521.5 x 81.3 mm

 $<sup>^{\</sup>star}$  Product specifications, terms, and offerings are subject to change at any time without notice.

#### Accessories

1 Year Extended Warranty for Select 65-inch Touchscreens (EPW-65JT1)

Mobile Cart for up to 75-inch Displays (INF-MOBCART)

SimpleShare Presentation System (INA-SIMPS1)

SimpleShare (INA-SIMS1)

SimpleShare Touch Presentation System (INA-SIMINT1)

LiteShow 4 DB+ Dual Band Wireless Adapter (INLITESHOW4DB+)

Remote Control for Mondopad, BigTouch or JTouch (INA-REMOTEPNL)

Stylus for Mondopad, BigTouch or JTouch (INA-STYLUS)

Wall Mount for up to 75-inch Display (INF-WALLMNT2)

Extra Large Wall Mount for up to 86-inch Display (INF-WALLMNT3)

Mobile Cart Pro for up to 75-inch Displays (Black) (INF-MOBCARTPRO-B)

Deluxe Mobile Cart for up to 100-inch Display (INA-MCARTDX)

Mobile Cart for Vertical Lift Mount (INA-CARTBB)

Vertical Lift Display Wall Mount (INA-MNTBB70)

VESA Interface Bracket for Vertical Lift Mounts (INA-VESABB)

Floor Support for Lift Wall Mount (INA-SUPPORTBB)

Lift Case for 55-inch to 65-inch Displays (CA-ATALIFT65)

Lift Case for 70-inch or 75-inch Display (CA-ATALIFT70)

Qwizdom Software Bundle (INS-QBUNDLE)

Ximbus Software (INS-QXIM1T40-1Y)

Oktopus Blend Software (INS-QBLEND1T40-1Y)

BigNote Whiteboarding Software (INS-BNOTE1)

BigNote, 10 Seat (INS-BNOTE10)

2 Year Extended Warranty for Select 65-inch Touchscreens (EPW-65JT2)

3 Year Extended Warranty for Select 65-inch Touchscreens (EPW-65JT3)