



Ultrastar® SN100 Series

Highlights

- Supports standard NVMe drivers
- Up to 3.2TB capacity in both the HH-HL add-in card and SFF 2.5-inch drive form factors
- Supports the latest generation PCIe Gen 3.0 server platforms
- UEFI boot support
- Advanced power management
- Enterprise-grade reliability: Flash-aware RAID, end-to-end data-path protection, advanced ECC, secure erase, power fail protection



PCIe SSDs for Application Acceleration

The HGST Ultrastar® SN100 Series offers unprecedented performance acceleration for today's most demanding cloud, hyperscale and enterprise applications, allowing them to scale to new heights. The HGST architecture has been designed to tightly integrate different kinds of Flash media, hardware and software to deliver memory-class performance with storage-class capacity and persistence. The Ultrastar SN100 Series comes in multiple form factors, as a low-profile HH-HL expansion card and as a highly-serviceable SFF 2.5-inch drive.



NVMe™ Support Eases Deployment and Management

To enable broad product interoperability and improve ease of deployment, the Ultrastar SN100 Series supports standard NVM Express (NVMe) drivers. NVMe is an interface specification that was created to deliver the full potential of non-volatile memory in PCIe-based solid-state storage devices to meet the needs of enterprise and client platforms. The NVMe standard allows the Ultrastar SN100 Series of products to effectively use the high speed PCIe interconnect with a standard OS driver. As a result, NVMe enables simplified configuration management and control in enterprise environments.



Leading Performance

The Ultrastar SN100 Series delivers consistent performance across all application workloads over the lifecycle of the product, even when the device is fully utilized. In addition, the products provide high performance for various workloads, whether it is random, sequential or mixed I/O. By offering 310,000 mixed random I/O performance, the Ultrastar SN100 Series will allow OLTP applications to scale to new levels.



High Density

Offered in up to 3.2TB capacity in both form factors, the Ultrastar SN100 Series delivers high storage density in a very compact size. In fact, the SFF form factor in this product family delivers the highest density amongst NVMe compliant SFF devices in the industry today.



Lower Capital and Operating Cost

By combining high performance, high density, support for the NVMe standard and trusted HGST reliability, less infrastructure is required to meet the the demanding requirements of enterprise and hyperscale data centers, directly resulting in overall lower total cost of ownership.



HGST Quality and Service

HGST Ultrastar SN100 Series family extends the company's long-standing tradition of performance and reliability leadership. A balanced combination of new and proven technologies enables high reliability and availability to customer data.

HGST drives are backed by an array of technical support and services, which may include customer and integration assistance. HGST is dedicated to providing a complete portfolio of SSD/HDD solutions to satisfy today's monumental computing needs.

Applications/Environments

- Cloud, hyperscale, enterprise and high performance computing
- Suitable for the most demanding scale-out database workloads
- Online Transaction Processing (OLTP) and Online Analytical Processing (OLAP)
- High Frequency Trading (HFT)
- Virtualized computing
- Space and/or power constrained environments



Ultrastar SN150 | 3200GB and 1600GB
Ultrastar SN100 | 3200GB, 1600GB and 800GB
MLC | HH-HL, 2.5" SFF | PCIe 3.0

Features & Benefits

	Performance	Flexibility	Low Latency	Capacity	Reliability
Feature/function	<ul style="list-style-type: none"> • 3000MB/s / 1600MB/s sequential R/W • 743k / 140k IOPS random R/W • 310k IOPS on 70/30 mix R/W 	<ul style="list-style-type: none"> • PCIe Gen 3.0 • HH-HL and SFF form factors 	<ul style="list-style-type: none"> • < 20 µs write latencies 	<ul style="list-style-type: none"> • 3200GB • 1600GB • 800GB 	<ul style="list-style-type: none"> • 0.44% AFR (2M hours MTBF) • Power-safe write processing • End-to-end data-path protection • Advanced ECC and global wear-leveling, T10 DIF support
Benefit	Maximum performance delivers unprecedented application throughput	Support for latest generation server platforms, including SFF-capable servers	DRAM-like performance	High capacity, all presented as a single volume	Higher reliability increases return on investment



a Western Digital brand

Ultrastar® SN100 Series

Specifications

	ULTRASTAR SN150		ULTRASTAR SN100	
Model/Part #	HUSPR3232AHP301 / OT00833 HUSPR3216AHP301 / OT00831	HUSPR3232ADP301 / OT00839 HUSPR3216ADP301 / OT00837	HUSPR3280ADP301 / OT00835	
Configuration				
Default capacities (GB ¹)	3200 / 1600	3200 / 1600	800	
Capacity range ² (min-max GB)	2240-3820 / 1120-1910	2240-3820 / 1120-1910	560-955	
Interface	PCIe 3.0 x4	PCIe 3.0 x4 (8639)	←	
Form factors	HH-HL add-in card	SFF 2.5-inch drive	←	
Performance³				
Read throughput (max MB/s, sequential 128k)	3000	←	2600	
Write throughput (max MB/s, sequential 128k)	1600	←	1400	
Read IOPS (max IOPS, random 4k)	743,000	←	634,000	
Write IOPS (max IOPS, random 4k)	140,000	←	80,000	
Mixed IOPS (70/30 R/W, random 4k)	310,000	←	190,000	
Read IOPS (max IOPS, random 8k)	385,000	←	330,000	
Write IOPS (max IOPS, random 8k)	75,000	←	42,000	
Latency 512B (µs)	20	←	←	
Reliability				
MTBF ⁴ (M hours)	2.0	←	←	
Annual failure rate ⁴ (AFR)	0.44%	←	←	
Endurance	3 DW/D	←	←	
Warranty	5 Years	←	←	
Physical				
Dimensions, without bracket (mm)	167.65 x 68.9 x 14.49	100.45 x 69.85 x 15	←	
Weight, without bracket (g)	232 / 231	177 / 174	166	
Environmental				
Power consumption (active/idle)	25 Watts / 8 Watts	←	←	
Operating temperature	0° to 55°C	0° to 70°C	←	
Non-operating temperature	-40° to 70°C	←	←	
Airflow (LFM)	300	←	←	
Thermal throttling		Supported		
Temperature monitoring		In-band and out-band using SMBus		
PowerSafe® technology		Data protection during power loss		
Power throttling		Supported		
Power rails		3.3V aux, 12V supply rail		
JEDEC compliance		3-month retention at 40°C at EOL		
Operating Systems				
Linux		RHEL 6/7, SLES 12, CentOS 6/7, Open SUSE 12		
Windows		Microsoft Server 2008 R2, Windows 2012, Windows 2012 Server		
Software				
HGST Device Manager (HDM)		HDM 3.2 (CLI)		
NVMe standard		1.1a		
Manufacturing Standards				
Penang, Malaysia		ISO 9001:2008 certified, ISO 14001:2004 certified		

How to Read the Ultrastar Model Number

HUSPR3238AHP301 = 3200GB, HH-HL, PCIe Gen 3.0

H = HGST

U = Ultrastar

S = Standard

PR = PCIe read intense

32 = Max nominal capacity (3200GB)

32 = Actual capacity this model (32 = 3200GB, 16 = 1600GB, 80 = 800GB)

A = Generation code

H = HH-HL form factor (vs. D for SFF form factor)

P3 = Interface, PCIe Gen 3.0

O = Reserved

1 = NVMe compatible

¹ One gigabyte (GB) is equal to one billion bytes, one terabyte (TB) is equal to 1,000GB (one trillion bytes), and one petabyte (PB) is equal to 1,000TB (one quadrillion bytes) when referring to solid-state drive or hard drive capacity. Accessible capacity will vary from the stated capacity due to formatting and partitioning of the drive, the computer's operating system, and other factors.

² Performance and endurance will vary with changes in usable capacity. Consult product manual for further details.

³ All performance measurements are in full sustained mode.

⁴ MTBF and AFR targets are based on a sample population and are estimated by statistical measurements and acceleration algorithms under median operating conditions. MTBF and AFR ratings do not predict an individual drive's reliability and do not constitute a warranty.