



7.68TB, 3.84TB, 1.92TB, 960GB, 480GB | 1DW/D
 3.2TB, 1.6TB, 800GB, 400GB | 3DW/D
 2.5-inch SFF | SAS 12Gb/s

Highlights

- Enterprise-grade 12Gb/s SAS SSD; backward compatible with 6Gb/s SAS
- Capacity points: 400GB to 7.68TB in 2.5-inch drive form factor
- Maximum read throughput up to 1,800MB/s
- Up to 250,000 4KiB IOPS in random reads
- Up to 1,000MB/s sequential writes
- Endurance of 3 or 1 random drive writes per day (DW/D) for 5 years
- Instant Secure Erase (ISE) & Self-Encrypting Drive (SED) options including TCG Enterprise
- 5-year limited warranty

Mixed Use Applications & Workloads (400GB – 3.2TB)

- Online Transaction Processing (OLTP) Databases
- Financial Transactions
- E-Commerce
- E-Mail / Messaging / Collaboration
- Virtual Environments

Read-intensive Workloads (480GB – 7.68TB)

- ERP, CRM, and Data Warehouse
- Video Streaming, Video-on-Demand
- File Servers
- Database Analytics

Easily Scale Enterprise Flash Storage with Workload-Optimized SAS SSDs

Leveraging widely deployed SAS storage infrastructure to scale out enterprise flash is critical for budget-conscious data centers trying to keep pace with an ever increasing volume and velocity of data generated daily. The Ultrastar® DC SS200* solid state drive (SSD) is a 12Gb/s SAS Enterprise SSD that helps transform hybrid and all-flash data centers by scaling flash storage capacities using workload-optimized solutions to deliver exceptional value.

Data center managers can target performance acceleration of mixed-use application workloads such as Online Transaction Processing (OLTP) or push the capacity envelope on read-intensive workloads like data warehousing and corporate file servers. Western Digital continues to build on its strong tradition of leading-edge SAS SSD products to deliver more capacity, improved performance and continued emphasis on reliability to enable universal flash adoption in enterprise storage.

Delivering High Capacity, High Performance SAS SSD with Cost-Effectiveness and Data Reliability

Ultrastar DC SS200 SSDs integrate Western Digital 15nm NAND and the enterprise-tested Guardian Technology™ platform to deliver enterprise-grade reliability, endurance and performance. Delivering up to 1,800MB/s and 250,000 4KiB IOPS read performance combined with exceptional write performance, DC SS200 enables valuable application acceleration without compromise. With significantly improved performance consistency and associated Quality of Service (QoS) metrics, this generation of SAS SSDs can help meet stringent enterprise application service level agreements (SLAs).

Available in capacity points from 400GB to 7.68TB, Ultrastar DC SS200 SSDs also offer a choice of endurance options of either 3 random drive writes per day (DW/D) for mixed-use workloads or 1 random DW/D for read-intensive workloads. All drives support the DW/D endurance rating over a 5-year limited warranty.

Proven Provider of Enterprise-Grade SSD Products

Ultrastar SSDs leverage decades of proven enterprise storage expertise in Serial Attached SCSI (SAS) design, reliability, firmware, customer qualification and system integration to this key member of the Ultrastar line-up.

The Ultrastar DC SS200 SAS SSD is protected by the Guardian Technology™ platform, a comprehensive suite of enterprise features comprised of FlashGuard™, DataGuard™ and EverGuard™ technologies.

- **FlashGuard** technology combines aggregated flash management and advanced signal processing to reliably extract significantly more life from commercial-grade MLC flash for read-intensive application workloads.
- **DataGuard** technology features full data path protection, to help safeguard user data from corruption along all data paths in the SSD.
- **EverGuard** technology helps protect against loss of user data in the event of unexpected power interruptions using a third-generation backup power circuit design and high reliability discrete capacitors.

Features & Benefits

	Performance	Capacity & Endurance	Reliability	Integration
Feature	<ul style="list-style-type: none"> Up to 1800MB/s Read & 1000MB/s Write Bandwidth Up to 250K Read IOPS (4K) 	<ul style="list-style-type: none"> 400GB to 7.68TB capacities Endurance-optimized or Capacity-optimized options 	<ul style="list-style-type: none"> UBER of < 1 in 10¹⁷ AFR 0.35% Guardian Technology 	SAS 12Gb/s
Benefit	Increase application performance and reduce storage system bottlenecks	Broad portfolio offering that is optimized to offer most value based on workload requirements	Enterprise-grade reliability helps reduce service incidents to help lower support costs	Wide industry adoption for easy and reliable scale out flash storage

Specifications

Configuration	3 DW/D	1 DW/D
Base Model	Ultrastar DC SS200	
Interface	SAS 12Gb/s	
Form Factor	2.5-inch	
Flash Memory Technology	15nm MLC NAND	
Capacity ¹	3.2TB, 1.6TB, 800GB, 400GB	7.68TB, 3.84TB, 1.96TB, 960GB, 480GB
Endurance (Drive writes per day) ²	3	1
Performance³		
Sequential Read (max MB/s, 128KiB)	1,800	
Sequential Write (max MB/s, 128KiB)	1,000	
Random Read (max IOPS, 4KiB)	250,000	
Random Write (max IOPS, 4KiB)	86,000	37,000
Mixed Random Read/Write (max IOPS 70%R/30%W, 4KiB)	154,000	90,000
Latency ⁴ (µs)	100	
Reliability		
Unrecoverable Bit Error Rate (UBER)	< 1 in 10 ¹⁷	
MTBF ⁵	2.5M hours	
Annual Failure Rate ⁵ (AFR)	0.35%	
Limited Warranty ⁶	5 years	
Data Retention	3-month at 40°C	
Power		
Requirement (DC +/- 5%)	5V & 12V	
Operating (W, typical)	9 or 11 (configurable)	
Idle (W)	3.8 to 4.3	
Physical		
z-height (mm)	15	
Dimensions (width x depth, mm)	69.85 x 100.45	
Weight (g, max)	200	
Environmental		
Operating Temperature (case)	0°C to 70°C	
Non-operating Temperature	-40°C to 85°C	

¹ One megabyte (MB) is equal to one million bytes, one gigabyte (GB) is equal to 1,000MB (one billion bytes), and one terabyte (TB) is equal to 1,000GB (one trillion bytes) when referring to storage capacity. Accessible capacity will vary from the stated capacity due to formatting, system software, and other factors.

² Endurance rating based on DW/D using 4KiB random write workload over 5 years

³ Performance will vary by capacity point, or with the changes in usable capacity. Consult product manual for further details. All performance measurements are in full sustained mode and are peak values. Preliminary and subject to change.

⁴ Average R/W Latency at 4KiB QD=1

⁵ MTBF and AFR targets are based on a sample population and are estimated by statistical measurement and acceleration algorithms under median operating conditions. MTBF and AFR rating do not predict an individual drive's reliability and do not constitute a warranty.

⁶ The warranty for the product will expire on the earlier of (i) the date when the flash media has reached one-percent (1%) of its remaining life or (ii) the expiration of the time period associated with the product.

Western Digital

5601 Great Oaks Parkway
San Jose, CA 95119, USA
US (Toll-Free): 800.801.4618
International: 408.717.6000

www.westerndigital.com

© 2017-18 Western Digital Corporation or its affiliates. All rights reserved. Produced 2/17. Rev. 9/18. Western Digital, the Western Digital logo, DataGuard, EverGuard, FlashGuard, Guardian Technology, and Ultrastar are registered trademarks or trademarks of Western Digital Corporation or its affiliates in the U.S. and/or other countries. All other marks are the property of the respective owners. References in this publication to Western Digital products, programs, or services do not imply that they will be made available in all countries. Product specifications provided are sample specifications that are subject to change and do not constitute a warranty. Please visit the Support section of our website, www.wdc.com/dc-support, for additional information on product specifications. Pictures shown may vary from actual products.