



Key Benefits and Features:

- Read speeds up to 6,600 MB/s¹ (1TB² and 2TB² models)
- Remarkable reliability features to help protect your content
- NVMe™ power management
- Slim M.2 2280 form factor
- Save on space with a single-sided M.2 2280 PCIe® Gen4 x4 NVMe™ SSD

Western Digital® PC SN810 NVMe™ SSD Performance Has Evolved

PCIe® Gen4 and the NVMe™ Architecture

The Western Digital PC SN810 NVMe™ SSD brings a new standard in performance and pushes the boundaries of client computing with a scalable NVMe™ architecture that is ready for tomorrow's higher demand storage applications.

An easy choice for computing customers looking for thin and light storage devices, the Western Digital PC SN810 comes in a variety of high-capacity points ranging from 256GB² to 2TB² so no one has to sacrifice performance for storage.

Designed around the PCIe® Gen4x4 interface, the Western Digital PC SN810 is ideal for applications that require high performance. Users will see the benefits of this performance boost in applications such as gaming, high-definition video content creation, postproduction processing and high demand computing such as software development and rendering.

Dedicated Quality

Designed as a fully integrated solution, the Western Digital PC SN810 NVMe™ SSD includes an in-house controller, firmware and thorough testing ensuring a robust supply and reliable design. The Western Digital PC SN810 NVMe™ SSD brings a new level of performance with sequential read speeds of 6,600 MB/s¹ and sequential write speeds of 5,000 MB/s¹ and a high endurance of up to 500 TBW³. All of this is available in the compact M.2 2280 form factor.

Summary

Delivering incredible performance to tackle the most challenging applications, the Western Digital PC SN810 NVMe™ SSD pulls no punches and brings a reliable design with high-capacity points from 256GB² to 2TB².

Western Digital® PC SN810 NVMe™ SSD

PRODUCT BRIEF

NVMe™ SSD

Product Features and Specifications

Form Factor	M.2 2280			
Interface ⁴	PCIe® Gen4 x4 NVMe™			
Formatted Capacities ²	256GB ² , 512GB ² , 1TB ² , 2TB ²			

Performance ⁵	256GB ²	512GB ²	1TB ²	2TB ²
Sequential Read up to (MB/s) ⁶	5,700	6,000	6,600	6,600
Sequential Write up to (MB/s) ⁶	1,900	4,000	5,000	5,000
Random Read up to (IOPS)	400K	750K	760K	760K
Random Write up to (IOPS)	490K	630K	650K	650K
Endurance ³ (TBW)	200	300	400	500

Power	256GB ²	512GB ²	1TB ²	2TB ²
Average Active Power ⁷ (mW)	200	200	200	200
Low Power (PS3) (mW)	25	25	25	25
Sleep (PS4) (mW)	5	5	5	5
Maximum Operating Power (mW) ⁸	7,000	8,000	8,000	8,250

Reliability	256GB ²	512GB ²	1TB ²	2TB ²
MTTF ⁹	Up to 1,752,000 hours			

Environmental	256GB ²	512GB ²	1TB ²	2TB ²
Operating Temperature ¹⁰	32°F to 176°F (0°C to 80°C)			
Non-Operating Temperature ¹¹	-67°F to 185°F (-55°C to +85°C)			
Operating Vibration	5 gRMS, 10–2000Hz, 15min/axis on 3 axes			
Non-Operating Vibration	4.9 gRMS, 7–800Hz, 15min/axis on 3 axes			
Shock	1,500G @0.5 ms half sine			
Certifications	Windows® HCK, Windows HLK, FCC, UL, TUV, KCC, BSMI, VCCI, C-Tick			
Limited Warranty ¹²	5 years			

Physical Dimensions	256GB ²	512GB ²	1TB ²	2TB ²
Width	22mm ±0.15mm			
Length	80mm ±0.15mm			
Thickness (max)	2.38mm			
Weight	6.5g ±0.5g			

Ordering Information	256GB ²	512GB ²	1TB ²	2TB ²
Security Type: Non-SED	SDCPNRY-256G	SDCPNRY-512G	SDCPNRY-1T00	SDCPNRZ-2T00
Security Type: SED	SDCQNRY-256G	SDCQNRY-512G	SDCQNRY-1T00	SDCQNRZ-2T00

¹ As used for transfer speed, megabyte per second (MB/s) = one million bytes per second. Performance will vary depending on your hardware and software components and configurations.

² 1GB = 1 billion bytes and 1TB = 1 trillion bytes. Actual user capacity may be less depending on operating environment.

³ TBW (terabytes written) values calculated using JEDEC client workload (JESD219) and vary by product capacity.

⁴ Backward compatible with PCIe® Gen3 x4, PCIe® Gen3 x2, PCIe® Gen3 x1, PCIe® Gen2 x4, PCIe® Gen2 x2 and PCIe® Gen2 x1

⁵ Test Conditions: Performance is measured by CrystalDiskMark™ 7.0.0f using 1GB LBA range. Windows® 10 using Microsoft® driver build 18362.116, Primary drive FOB. ASUS™ ROG Crosshair VIII Hero X570 platform with AMD Ryzen™ 9 3950X 16-Core, HyperX Fury 32GB 3200Mhz DDR4 CL 16 DIMM. Performance may vary based on host device, usage conditions, drive capacity, and other factors. 1 MB = 1,000,000 bytes. IOPS = input/output operations per second.

⁶ Based on read/write speed. 1 MB/s = 1 million bytes per second. Based on internal testing; performance may vary depending upon host device, usage conditions, drive capacity, and other factors.

⁷ Measured using MobileMark™ 2014 on AMD Ryzen™ 5 3500 6-core, 16GB DRAM, NVIDIA™ GeForce GT 710, C-State on, Windows® 10 Pro.

⁸ Measured during continuous sequential read or write activity and indicates the average over 1 second intervals.

⁹ Mean Time To Failure based on internal testing using Telcordia™ stress part testing (Telcordia™ SR-332, GB, 25°C). MTTF is based on a sample population and is estimated by statistical measurements and acceleration algorithms. MTTF does not predict an individual drive's reliability and does not constitute a warranty.

¹⁰ Operational temperature is measured by an on board temperature sensor. The SSD box package is rated up to 60°C.

¹¹ Non-operational storage temperature does not guarantee data retention.

¹² 5 years or Max Endurance (TBW) limit, whichever occurs first. See <http://support.westerndigital.com> for more details.



5601 Great Oaks Parkway
San Jose, CA 95119, USA
US (Toll-Free): 800.275.4932
International: 408.717.6000
www.westerndigital.com

Western Digital and the Western Digital logo are registered trademarks or trademarks of Western Digital Corporation or its affiliates. NVMe is a trademark of NVM Express, Inc. PCIe is a registered trademark of PCI-SIG Corporation. Microsoft and Windows are trademarks of Microsoft Corporation. All other marks are the property of their respective owners. Product specifications are subject to change without notice. Pictures shown may vary from actual products. Please visit our website, <http://www.westerndigital.com> for additional information on product specifications.

© 2023 Western Digital Corporation or its affiliates. All rights reserved.